

PRODUCT DATA SHEET

EVERBUILD® Quick Drying Clear Varnish

ENHANCES THE NATURAL QUALITIES OF WOOD AND PROVIDES LONG LASTING PROTECTION

PRODUCT DESCRIPTION

EVERBUILD® Quick Drying Clear Varnish is a professional, low solvent varnish that enhances the natural qualities of wood, and provides long lasting protection. It has been developed specifically to give an ultra-hard, scratch resistant and heat resistant, non-yellowing finish.

USES

Ideal for use on interior wood such as:

- Tables
- Chairs
- Doors
- Skirtings
- Furniture etc.

CHARACTERISTICS / ADVANTAGES

- Low solvent formula
- Touch dry in 30 minutes, overcoat after 1 hour
- Long lasting protection
- Clear finish, no discoloration
- Ultra hard finish
- Scratch resistant
- Heat resistant
- Non-yellowing finish
- Easy to apply

PRODUCT INFORMATION

Packaging	250ml, 750ml and 2.5ltr tins
Colour	Clear Varnish in Gloss, Matt and Satin finishes
Shelf Life	24 months from date of manufacture when stored as directed.
Storage Conditions	Store in cool dry conditions between + 5 and +25°C. Storage outside these conditions will dramatically reduce shelf life. Protect from frost.
Density	1.0 - 1.1 g/cm ³
pH-Value	7.5 - 9
Volatile organic compound (VOC) content	Volatile Organic Compounds contribute to atmospheric pollution. EU limit value for this product (cat A/e): 130g/L (2010). This product contains max 60g/L VOC.

APPLICATION INFORMATION

Consumption	Up to 16m ² /litre depending on porosity of wood and number of coats applied
Ambient Air Temperature	Do not use in temperatures below 10°C.

APPLICATION INSTRUCTIONS

MIXING

Stir product well before use and intermittently during application.

SUBSTRATE PREPARATION

Ensure wood is clean, dry and free from dirt or dust by wiping with a lint free cloth dampened with white spirit, allow to dry before applying EVERBUILD® Quick Drying Clear Varnish.

On varnished wood, remove any unsound varnish and sand the surface with medium grade sandpaper to a uniformed appearance and then clean with white spirit. Allow to dry thoroughly before applying EVERBUILD® Quick Drying Clear Varnish. On bare wood, sand the surface with fine sandpaper. Always remove excess dust with a cloth before applying varnish.

APPLICATION

Brush apply EVERBUILD® Quick Drying Clear Varnish, following the direction of the wood grain. Always apply the varnish to a wet edge, working systematically across the surface keeping the wet edge moving together as much as possible. The film is touch dry in 30 minutes. Approximately 2-3 coats will be required for full coverage. Allow 1 hour between each coat. Lightly sand the surface before applying the final coat.

Note: on application, the varnish will appear slightly white; this quickly turns completely clear as the drying process starts.

CLEANING OF TOOLS

Clean brushes thoroughly with water after use; a little washing up liquid will assist brush cleaning.

MAINTENANCE

CLEANING

If water is accidentally spilt on the surface within 2-3 days of application, remove by wiping gently (do not rub) with a soft cloth.

LIMITATIONS

- Do not use on wood floors or decking.
- Do not use externally.
- Protect from frost and do not use in temps below 10°C.
- To avoid risk of spillage, always transport this tin in a secure and upright position.
- As the manufacturer cannot know all the uses their products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services Department for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED
Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
EVERBUILD® Quick Drying Clear Varnish
May 2019, Version 01.01
020405030040000015

EVERBUILDQuickDryingClearVarnish-en-IE-(05-2019)-1-1.pdf

