

# PRODUCT DATA SHEET

## EVERBUILD® DEEP GAP FILLER

FILLS DEEP HOLES IN ONE APPLICATION

### PRODUCT DESCRIPTION

EVERBUILD® DEEP GAP FILLER is a revolutionary new filler, formulated using ceramic spheres that fill most holes and cracks; especially deep holes, in just one quick application with no need for secondary filling to level off. EVERBUILD® DEEP GAP FILLER will not shrink, sag or crack and dries to a light grey finish. EVERBUILD® DEEP GAP FILLER finishes smooth, requiring little or no sanding and can be ready to paint or wallpaper in just 30 minutes. It can be used for repairs to wood, plaster, masonry, cement, stone, brick and rendering.

### USES

Fills gaps and holes in

- Plaster
- Brick
- Stone
- Wood
- Render
- Cement
- Masonry

Internal use only.

### CHARACTERISTICS / ADVANTAGES

- Fills in one go- No need to build up layers of filler - fills up to 50mm deep in one application
- Easy to use - lightweight paste is incredibly easy to apply
- No sanding required - finishes to a smooth surface
- No sagging - the lightweight properties of DEEP GAP FILLER prevent sagging even on ceilings.
- Non-shrink - will not shrink back whilst drying
- Quick drying - ready to paint/paper in just 30 minutes (subject to ambient temperature/conditions)
- Overpaintable with most solvent based and emulsion paints
- Overstainable

|                       |                                     |
|-----------------------|-------------------------------------|
| Movement Accomodation | Low/Moderate                        |
| Maximum Width         | 50mm                                |
| pH                    | 8.3 - 9.9                           |
| Viscosity             | 60,000-150,000 cP @<br>20°C 50% R.H |

### PRODUCT INFORMATION

|                         |   |
|-------------------------|---|
| Packaging               | 1ltr tub  |
| Appearance / Colour     | Lightweight light grey paste  |
| Shelf Life              | 24 months from date of manufacture when stored according to manufacturers instructions. |
| Storage Conditions      | Store at moderate (5-30°C) temperatures.  |
| Density                 | 1.15-1.25g/cm <sup>3</sup>  |
| Layer Thickness         | 50mm in one coat – further layers may be built up                                       |
| Ambient Air Temperature | 5°C to 30°C   |

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry, free from dust, grease and other contamination.

### APPLICATION

Stir EVERBUILD® DEEP GAP FILLER to a smooth paste. If product is too dry, add a few drops of water and re-stir. Apply using a flexible filler knife, smoothing down to achieve a perfect surface that won't need sanding. When filling a large surface area, it may not always be possible to achieve a completely level finish. However, EVERBUILD® DEEP GAP FILLER is very easy to sand if necessary.

Deep holes up to 50mm can be filled in one application with no need to build up in several layers.

Any nail or screw heads should be painted over before filling, to prevent rusting.

### LIMITATIONS

- Do not use in areas subject to constant water immersion.
- Do not use externally.
- Do not use for structural repairs or to nail/screw into.
- Absorption of the filler may be different to the surrounding area. If filler shows through after painting, simply apply further coats.

### VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @Sikalreland



Product Data Sheet  
EVERBUILD® DEEP GAP FILLER  
May 2019, Version 01.01  
020406010050000005

EVERBUILDDEEPGAPFILLER-en-IE-(05-2019)-1-1.pdf