

## PRODUCT DATA SHEET

# EVERBUILD® Tarmac Restorer

HIGH PERFORMANCE SURFACE COATING TO MAKE TARMAC LOOK NEW

### PRODUCT DESCRIPTION

EVERBUILD® Tarmac Restorer is a high performance surface coating specially formulated to make existing tarmac look like new. Once dry EVERBUILD® Tarmac Restorer provides a tough, durable, low sheen finish which protects from weathering, oil and petrol spills and unsightly plant/weed growth. The quick drying formula enables driveways to be used after only 4 hours.

### USES

- Tarmac drives

### CHARACTERISTICS / ADVANTAGES

- Tough and long-lasting
- Protects against common spills and plant / weed growth
- Fast-drying

### PRODUCT INFORMATION

<b>Chemical Base</b>	Water-based acrylic polymer
<b>Packaging</b>	5L jerry can
<b>Appearance / Colour</b>	Black
<b>Shelf Life</b>	12 months from date of manufacture.
<b>Storage Conditions</b>	Store in original containers in cool dry conditions above 5°C (max 25°C). Do not allow to freeze.
<b>Density</b>	0.9 – 1.1 g/cm <sup>3</sup>
<b>Viscosity</b>	400 - 700 cP
<b>Chemical Resistance</b>	Resistant to: most salt solutions, dilute acids and alkalis, water and limited oil. Not resistant to: solvents and some detergent solutions.
<b>Consumption / Yield / Dosage (PRINT single line)</b>	4 – 6m <sup>2</sup> per litre depending on porosity of substrate
<b>Product Temperature</b>	-20°C to +50°C
<b>Ambient Air Temperature</b>	5°C to 35°C. Surfaces must be free from ice and water.
<b>Curing Time</b>	4-6 hours depending on drying conditions

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean and free from any loose dirt or debris. The surface may be damp, however any surface water/puddles must be removed. Use Everbuild® Oil Away to remove any oil or grease spills. Lichen or surface mould can be removed using Everbuild® Fungicidal Wash and cleaned using fresh water and a stiff bristle brush. Surface imperfections should be repaired using Everbuild® Quick Mac or suitable repair compound.

### APPLICATION

Always read instructions prior to use. Stir well before and periodically during use. Apply with a brush or long pile roller in an even coat across the entire surface. Apply in 2 coats allowing 4 hours between coats.

### CLEANING OF TOOLS

Clean all equipment immediately after use with clean water and detergent.

### LIMITATIONS

- Do not use if ambient air or surface temperature is below 5°C.
- Do not use if rain is imminent (within 6 hours).
- Do not use over fresh tarmac. Allow tarmac to dry for a minimum of 3 months prior to application.
- Do not subject to vehicular traffic within 4 hours of application.
- At lower temperatures drying times will be significantly extended. Always check surface is dry before trafficking.
- Oil, petrol or chemical spills should be removed from EVERBUILD® Tarmac Restorer as quickly as possible with warm water, detergent and a clean cloth.
- Do not use a high pressure spray to clean EVERBUILD® Tarmac Restorer.
- It is the user's responsibility to determine suitability for use. If in any doubt contact Technical Services for advice.

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @Sikalreland



Product Data Sheet  
EVERBUILD® Tarmac Restorer  
March 2020, Version 01.01  
020816990010000007

EVERBUILD Tarmac Restorer-en-IE-(03-2020)-1-1.pdf

