

PRODUCT DATA SHEET

SikaProof® Tape A+

Self-adhesive tape for internal jointing of SikaProof® A+ waterproofing system

PRODUCT DESCRIPTION

SikaProof® Tape A+ is a self-adhesive tape based on a polyacrylate adhesive with a carrier film and a release liner.

USES

SikaProof® Tape A+ installation works to be carried out only by Sika Approved Contractors. Please observe information given by Product Data Sheets.

- Sealing and bonding overlap joints, connections and details within the SikaProof® A+ membrane system.

CHARACTERISTICS / ADVANTAGES

- Fully bonded to the concrete structure (identical to SikaProof® A+)
- No lateral water migration between the concrete structure and the membrane system
- High adhesion and sealing capability, especially in cold and damp conditions
- Simple and fast to install

APPROVALS / STANDARDS

- Watertightness of a Surface Sealing System SikaProof® A+ 12 / SikaProof® Tape A+, WISSBAU, Test report No. 2018-275

PRODUCT INFORMATION

Packaging	2 rolls packed in one cardboard box	
	Individual roll size	Length: 25 m Width: 150 (± 5) mm
Appearance / Colour	Top layer	Light grey hybrid bonding layer with yellow waterproofing layer
	Bottom layer	Transparent polyacrylate adhesive covered with a white release liner
Shelf Life	18 months from date of production	
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Always refer to packaging.	
Thickness	1,80 mm	

SYSTEM INFORMATION

System Structure	SikaProof® Tape A+ is a system component for internal jointing of the SikaProof® A+ membrane system. For more detailed information, refer to Sika® Method Statement: SikaProof® A+ system
-------------------------	---

APPLICATION INFORMATION

Ambient Air Temperature	+5 °C min. / +45 °C max.
-------------------------	--------------------------

Substrate Temperature	+5 °C min.
-----------------------	------------

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTS

- Sika® Method Statement: SikaProof® A+
- Sika® Application Manual: SikaProof® A+
- Product Data Sheet: SikaProof® A+ 12

LIMITATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Do not install SikaProof® Tape A+ during continuous or prolonged rain or snowfall.
- The substrate quality and conditions must be fulfilled or appropriate measures must be taken. Contact Sika® Technical Services for more information.
- SikaProof® Tape A+ is not permanently UV resistant.
- The structural concrete must be placed within 90 days after the SikaProof® A+ membrane system is installed.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulations is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1% (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface is the grey SikaProof® A+ hybrid bonding layer. It must be dry (or slightly damp), clean and free of any materials that could impair the adhesion. If the substrate requirements are not achieved, suitable measures must be taken. Contact Sika® Technical Services for more information.

APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Installation Procedure

Remove the release liner, apply onto the grey SikaProof® A+ membrane side and press tape firmly using a pressure roller.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
SikaProof® Tape A+
May 2021, Version 03.01
02072030800000007

SikaProofTapeA+-en-IE-(05-2021)-3-1.pdf

