

## PRODUCT DATA SHEET

# EVERBUILD® PINKGRIP® SF BUT IT'S WHITE

### SOLVENT FREE DIRECT BOND ADHESIVE

#### PRODUCT DESCRIPTION

EVERBUILD® PINKGRIP® SF BUT IT'S WHITE is a solvent free, white version of the brand leading Pinkgrip Direct Bond Adhesive. It has all the unique benefits of Pinkgrip and will stick just about anything on a building site without the need for under pinning, thanks to the product's no-slump formula.

#### USES

- Bonding dado rails, architrave's and skirting.
- Fixing wall cladding direct to internal wall surfaces or timber battens.
- Fixing battens directly onto walls without fastenings.
- Bonding carpet gripper systems to most floors without the need for nails or tacks.
- Bonding stair nosing to concrete or wooden stairs.
- Securing aluminium or other skin panels to the framework or portable industrial buildings and caravans.

#### CHARACTERISTICS / ADVANTAGES

- Solvent free - environmentally friendly formulation
- Excellent adhesion/bond strength - adheres to most common surfaces.
- Enhanced slump resistance for quick simple direct bonding without the need for temporary support in many applications.
- Good "nip off" quality to prevent messy stringing of adhesive.
- High solids formulation - excellent gap filling properties without shrinkage.
- Extended open time - allows for easy repositioning after fixing.
- Will adhere to damp surfaces.
- Water clean up - no hazardous solvents.

<b>Form</b>	White thixotropic paste (ready to use)
<b>Viscosity</b>	approx. 350,000 cPs
<b>Solids</b>	75-80%
<b>Flash Point</b>	None (solvent free)
<b>Application Temp</b>	+4 to +35°C
<b>Compatibility</b>	Can be used in contact with most building materials but should not be used against bituminous compounds or mirror backings.

#### PRODUCT INFORMATION

<b>Packaging</b>	380ml
<b>Colour</b>	White
<b>Shelf Life</b>	24 months
<b>Storage Conditions</b>	Store in original unopened containers between 15 and 20 °C
<b>Density</b>	~1.6 g/cm <sup>3</sup>

## TECHNICAL INFORMATION

Service Temperature -10 to +70°C

## APPLICATION INFORMATION

Consumption 1.5 x 380ml cartridges per m<sup>2</sup>

Curing Rate Final cure: 24 - 48 hours depending on substrates

Open Time Max 10 mins at 23°C and 50% R.H

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

The surfaces to be glued should be clean and free from dust, grease and other contaminants. Wood, plaster and brick may be damp but not running wet. Use mechanical abrasion to clean porous surfaces if necessary before application.

### APPLICATION METHOD / TOOLS

Apply EVERBUILD® PINKGRIP® SF BUT IT'S WHITE to one side either in strips or daubs (or by trowel for low viscosity grade). Position the object to be fixed, then move from side to side and simultaneously apply pressure to achieve an even bond. If the object is wrongly positioned, slide it to the correct position. Finally, apply maximum pressure for a short time (up to 1 minute). Wipe away any excess with a damp cloth making a neat joint between the two bonded surfaces. Temporary mechanical fixings may be required for heavy objects while full bond strength is reached.

## LIMITATIONS

- Do not use in situations where both surfaces are non-porous (eg. plastic/plastic - metal/metal) - use PINK GRIP.
- Do not use as a mirror adhesive: use EVERBUILD MIRROR MATE.
- Caution: The product will cure at a dramatically slower rate when used externally. For this reason, we recommend EVERBUILD PINK GRIP for external applications (solvent based product).

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

SIKA IRELAND LIMITED  
Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @Sikalreland



Product Data Sheet  
EVERBUILD® PINKGRIP® SF BUT IT'S WHITE  
May 2019, Version 01.01  
020513030000000025

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILDPINKGRIPSF BUT IT'S WHITE-en-IE-(05-2019)-1-1.pdf