

PRODUCT DATA SHEET

Sika® Stabilising Solution

A fine polymer emulsion to bind, seal and strengthen unstable surfaces for overcoating with paint, wallpaper or tiles.

PRODUCT DESCRIPTION

Sika® Stabilising Solution is a high performance primer. It is formulated with a microscopically fine polymer emulsion enabling it to penetrate deeply into dusty/chalky and badly weathered surfaces to leave a stable sound base for subsequent decoration with paint/wallpaper/tiling etc.

USES

- Brickwork & Blockwork.
- Stone.
- Render.
- Plaster.
- Existing paint surfaces.
- Pebbledashing/stucco etc.

CHARACTERISTICS / ADVANTAGES

- Quick drying.
- Ready to use.
- Stabilises and binds interior and exterior friable surfaces prior to overcoating.
- Seal and bonds together chalky, dirty and weathered surfaces.
- Exterior and interior use.

PRODUCT INFORMATION

Packaging	5 L Jerry Can
Appearance / Colour	Milky white liquid - dries clear
Shelf Life	12 months from date of manufacture when stored according to the manufacturer's instructions.
Storage Conditions	Store in cool, dry conditions, between +5 °C and +25 °C. PROTECT FROM FROST.
Density	1.01 g/cm ³
pH-Value	7 - 9
Solid Content	11 - 14 %
Viscosity	Approx. 30 cP

APPLICATION INFORMATION

Consumption	5 - 10 m ² per litre depending on porosity of surface and method of application.
--------------------	---

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Do not dilute.
- Do not apply externally if rain is imminent (within 6 hours).
- Do not apply below +5 °C.
- Do not allow to enter watercourses.
- Will not restore badly disintegrated render/plaster etc. This will require removing and subsequent re-application.

It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for further advice.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

- Surfaces must be clean, dry (to touch) and free from grease and other contaminants.
- Remove all loose and flaking material with a scraper and a stiff brush back to a sound surface.
- Cure all root causes of penetrating damp and remove all mould contamination with Sika® 404 Fungicidal Wash.

APPLICATION

- This is a ready to use product. **DO NOT DILUTE.**
- Stir or shake well before use.
- Apply by brush in a liberal even coat.
- Work from bottom to top to avoid run marks.
- For extremely porous surfaces, apply a second coat when dry.
- Drying time 2-4 hours depending on temperature, humidity etc.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
Sika® Stabilising Solution
November 2025, Version 01.01
02189010000245328

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.