

Revision Date: 14.08.2024 Date of last issue: - Version 1.0

Print Date 28.03.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikalastic<sup>®</sup> M 860 Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd
		Sika House
		Ballymun Industrial Estate
		Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person	:	EHS@UK.Sika.com
responsible for the SDS		

#### **1.4 Emergency telephone number**

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Version 1.0 Print Date 28.03.2025 Date of last issue: -Hazard pictograms Signal word Danger H317 Hazard statements May cause an allergic skin reaction. Harmful if inhaled. H332 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. Harmful to aquatic life with long lasting effects. H412 Prevention: Precautionary statements P261 Avoid breathing mist or vapours. Avoid release to the environment. P273 P280 Wear protective gloves. P284 In case of inadequate ventilation wear respiratory protection. Response: P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. If experiencing respiratory symptoms: Call a P342 + P311 POISON CENTER/ doctor.

#### Hazardous components which must be listed on the label:

aliphatic prepolymer (d-polyether based) 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

#### **Additional Labelling**

"As from 24 August 2023 adequate training is required before industrial or professional use."

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 14.08.2024 Date of last issue: - Version 1.0

Print Date 28.03.2025

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
aliphatic prepolymer (d-polyether based)	39323-37-0 Not Assigned	Skin Sens. 1; H317	>=80
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 1 - < 2,5
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 = specific concentration limit Resp. Sens. 1; H334 >= 0,5 % = specific concentration limit Skin Sens. 1; H317 >= 0,5 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 0,031 mg/l	>= 1 - < 2,5

For explanation of abbreviations see section 16.



Revision Date: 14.08.2024 Date of last issue: - Version 1.0

Print Date 28.03.2025

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

4.1 Description of first alu mea	50165
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
4.2 Most important symptoms a	and effects, both acute and delayed
Symptoms	<ul> <li>Asthmatic appearance Respiratory disorder Allergic reactions Headache See Section 11 for more detailed information on health effects and symptoms.</li> </ul>

Risks : May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. sensitising effects

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.
-----------	---	------------------------

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.

# Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: -		Version 1.0	Print Date 28.03.2025
5.2 Special hazards arising from t	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	)
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breath	ing apparatus.
Further information	:	Standard procedure for chemical fires.	
6.1 Personal precautions, protect	tiv	e equipment and emergency procedures	
• • •		Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary sew If the product contaminates rivers and lakes or respective authorities.	
6.3 Methods and material for cont	tai	nment and cleaning up	
		Soak up with inert absorbent material (e.g. sar	d cilico dol

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

## 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation ma, allergies, chronic or recurrent respirate not be employed in any process in which t used. Smoking, eating and drinking should be pr plication area. Provide sufficient air exchange and/or exh Follow standard hygiene measures when I
---

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: -		Version 1.0	Print Date 28.03.2025
		products	
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygie practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the er	using do not
7.2 Conditions for safe storage, i	nc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-v place. Containers which are opened must be ca sealed and kept upright to prevent leakage. Stor ance with local regulations.	refully re-
Recommended storage tem- perature	:	> 5 - < 30 °C	
Further information on stor- age stability	:	No decomposition if stored and applied as direc	ted.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet puse.	prior to any

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
3-isocyanatomethyl-3,5,5-	4098-71-9	OELV - 8 hrs	0,005 ppm	IE OEL
trimethylcyclohexyl isocyanate		(TWA)	(NCO)	
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asth- ma, rhinitis or extrinsic allergic alveolitis			

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

:

#### Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water

Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Version 1.0 Print Date 28.03.2025 Date of last issue: -Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work. Respiratory protection In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas. **Environmental exposure controls** General advice

#### General advice : Do no

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: light yellow
Odour	: bitter almond

Melting point/ range / Freez-	:	No data available
-------------------------------	---	-------------------

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: -		Version 1.0	Print Date 28.03.2025
ing point			
Boiling point/boiling range	:	> 100 °C	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	0.01	Nosive limits	
Upper explosion limit / Upper flammability limit	-		
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 101 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	7 - 9 Concentration: 100 %	
Viscosity			
Viscosity, dynamic	:	6.600 mPa.s (20 °C)	
Viscosity, kinematic	:	No data available	
Solubility(ies)			
Water solubility	:	emulsifiable	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	No data available	
Density	:	ca. 1,06 g/cm3 (20 °C)	
Relative vapour density	:	No data available	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: -		Version 1.0	Print Date 28.03.2025
Particle characteristics	:	No data available	
9.2 Other information Explosives	:	Not explosive	
Metal corrosion rate	:	Not corrosive to metals	

## **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

#### **10.2 Chemical stability**

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if inhaled.

#### **Components:**

#### aliphatic prepolymer (d-polyether based):

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

#### Hydrocarbons, C9, aromatics:

Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: -	Version 1.0	Print Date 28.03.2025
Acute oral toxicity	: LD50 Oral (Rat): > 2.000 mg/kg	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg	
3-isocyanatomethyl-3,5,5-tr	methylcyclohexyl isocyanate:	
Acute oral toxicity	: LD50 Oral (Rat): 4.814 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
	Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	: LD50 Dermal (Rat): > 7.000 mg/kg	
Skin corrosion/irritation Not classified due to lack of c	ata.	
Components:		
Hydrocarbons, C9, aromati	s:	
Assessment	: Repeated exposure may cause skin dr	yness or cracking.
Serious eye damage/eye iri Not classified due to lack of c		
Respiratory or skin sensitis	ation	
<b>Skin sensitisation</b> May cause an allergic skin re	iction.	
<b>Respiratory sensitisation</b> May cause allergy or asthma	symptoms or breathing difficulties if inhaled	
Germ cell mutagenicity Not classified due to lack of c	ata.	
<b>Carcinogenicity</b> Not classified due to lack of c	ata.	
<b>Reproductive toxicity</b> Not classified due to lack of c	ata.	
STOT - single exposure Not classified due to lack of c	ata.	
STOT - repeated exposure Not classified due to lack of c		

# Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: - Version 1.0

Print Date 28.03.2025

#### Aspiration toxicity

Not classified due to lack of data.

### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

	aliphatic prepolymer (d-polyeth	ner based):
	Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia (water flea)): > 100 mg/l
		NOEC (Daphnia (water flea)): > 100 mg/l
	Toxicity to algae/aquatic : plants	EC50 (algae): > 100 mg/l Exposure time: 72 h
	Hydrocarbons, C9, aromatics:	
	Toxicity to algae/aquatic : plants	(Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l Exposure time: 72 h
12.2	Persistence and degradability	
	No data available	
12.3	Bioaccumulative potential No data available	
12.4	<b>Mobility in soil</b> No data available	
12.5	i Results of PBT and vPvB asse	ssment
	Product:	
	Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: - Version 1.0

Print Date 28.03.2025

#### 12.6 Endocrine disrupting properties

Product:		
Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

:	Not regulated as a dangerous good
:	Not regulated as a dangerous good
:	Not regulated as a dangerous good
:	Not regulated as a dangerous good
:	Not regulated as a dangerous good
	:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: -	Version 1.0	Print Date 28.03.2025
ΙΑΤΑ	: Not regulated as a dangerous good	
14.3 Transport hazard class(e	)	
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA (Passenger)	: Not regulated as a dangerous good	
<b>14.5 Environmental hazards</b> Not regulated as a dangero	is good	
14.6 Special precautions for u Not applicable	er	
<b>14.7 Maritime transport in bull</b> Not applicable for product a	according to IMO instruments supplied.	

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH Information:

----

: Not applicable

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 52: 1,2-Benzenedicarboxylic acid, di-C8-10branched alkyl esters, C9-rich

Number on list 74: 3isocyanatomethyl-3,5,5trimethylcyclohexyl isocyanate

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: -	Version 1	.0	Print Date 28.03.2025
			Number on list 75:
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable
Regulation (EC) on substances th layer	nat deplete the ozone	:	Not applicable
Regulation (EU) 2019/1021 on pe tants (recast)	ersistent organic pollu-	:	Not applicable
Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable
Seveso III: Directive 2012/18/EU jor-accident hazards involving dar		ent	and of the Council on the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: <= 3% w/w
	emissions (integrated p	ollu	4 November 2010 on industrial ution prevention and control) Is (VOC) content: 2% w/w
If other regulatory information app Sheet, then it is described in this		rov	ided elsewhere in the Safety Data
Health, safety and environ- : mental regulation/legislation specific for the substance or mixture:	Health and Safety at W Control of Substances (COSHH)	ork Haz Con	Act 1990 & Subsidiary Regulations Act 1974 & Subsidiary Regulations zardous to Health Regulations trol of Major Accident Hazards d amendments.

## Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations,

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Date of last issue: - Version 1.0

Print Date 28.03.2025

where applicable.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### Full text of H-Statements

H226 H304 H315 H317 H319 H330 H334 H335 H336 H411		Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Full text of other abbreviatio	ns	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occu-
		pational Exposure Limit Values - Code of Practice, Schedule 1
		and 2
IE OEL / OELV - 8 hrs (TWA) ADR	:	Occupational exposure limit value (8-hour reference period) European Agreement concerning the International Carriage of
ADR	·	Dangerous Goods by Road
CAS		Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	÷	International Air Transport Association
IMDG	÷	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic<sup>®</sup> M 860 Part B



Revision Date: 14.08.2024 Version 1.0 Print Date 28.03.2025 Date of last issue: -Ships, 1973 as modified by the Protocol of 1978 OEL **Occupational Exposure Limit** : PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament REACH and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency Substances of Very High Concern SVHC Very persistent and very bioaccumulative vPvB ٠

#### **Further information**

Classification of the	e mixture:	Classification procedure:
Acute Tox. 4	H332	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN