

PRODUCT DATA SHEET

Sika® Igoalflex®-301 Accelerator

Additive for Sika® Igoalflex®-301

PRODUCT DESCRIPTION

Sika® Igoalflex®-301 Accelerator is an additive to accelerate the total drying time of Sika® Igoalflex®-301 in critical conditions, such as cold temperatures, winter, on damp substrate, high air humidity or potential rain.

USES

- Sika® Igoalflex®-301 Accelerator is used exclusively with Sika® Igoalflex®-301 to improve the total drying time

CHARACTERISTICS / ADVANTAGES

- Allows the use of Sika® Igoalflex®-301 in all climates
- Increases the drying time
- Improves rain resistant time
- Easy to mix
- Supplied in pre-measured quantities for the packs of Sika® Igoalflex®-301

PRODUCT INFORMATION

Chemical Base	Hardening additives
Packaging	50 g, 100 g and 200 g Refer to current price list for packaging variations
Appearance / Colour	Blue
Shelf Life	12 months from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.

APPLICATION INFORMATION

Consumption	Sika® Igoalflex®-301 Accelerator is supplied with the correct quantity for the packs of Sika® Igoalflex®-301.	
	Quantities	
	Sika® Accelerator	Sika® Igoalflex®-301
	50 g	5 kg
	100 g	10 kg
	200 g	20 kg

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Once opened, keep packaging tightly closed to prevent moisture ingress.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Note: The mixed product is workable up to 1 hour after the mixing.

- Immediately after opening the bottle of Sika® Accelerator, mix thoroughly with Sika® Igoflex®-301 using manual or mechanical methods.
- Reference must be made to the Sika® Igoflex®-301 Product Data Sheet.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
Sika® Igoflex®-301 Accelerator
February 2025, Version 01.01
020706802000000005

Sikalgoflex-301Accelerator-en-IE-(02-2025)-1-1.pdf