

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaRoof® Primer-600

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Ireland Ltd  
Sika House  
Ballymun Industrial Estate  
Dublin 11  
Telephone : +353 1862 0709  
E-mail address of person : EHS@UK.Sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166  
(available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Country IE 000000123613

1 / 17

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P261	Avoid breathing mist or vapours.
P273	Avoid release to the environment.

**Response:**

P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.

**Hazardous components which must be listed on the label:**

cyclohexane

**Additional Labelling**

EUH208 Contains zinc bis(dibutyldithiocarbamate). May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
cyclohexane	110-82-7 203-806-2 601-017-00-1 01-2119463273-41-XXXX	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 40 - < 60
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not Assigned 921-024-6 649-328-00-1 01-2119475514-35-XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - < 10
zinc bis(dibutyldithiocarbamate)	136-23-2 205-232-8 006-081-00-9 01-2119535161-51-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

- |                         |   |   |
|-------------------------|---|---|
| If inhaled              | : | Move to fresh air.<br>Consult a physician after significant exposure.   |
| In case of skin contact | : | Take off contaminated clothing and shoes immediately.<br>Wash off with soap and plenty of water.<br>If symptoms persist, call a physician.                                      |
| In case of eye contact  | : | Remove contact lenses.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.  |
| If swallowed            | : | Do not induce vomiting without medical advice.<br>Rinse mouth with water.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person. |

### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |  |
|----------|---|--|
| Symptoms | : | Erythema<br>Dermatitis<br>Loss of balance<br>Vertigo<br>See Section 11 for more detailed information on health effects and symptoms. |
| Risks    | : | irritant effects<br><br>Causes skin irritation.<br>May cause drowsiness or dizziness.  |

### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |   |                        |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- |                                |   |   |
|--------------------------------|---|---|
| Suitable extinguishing media   | : | Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical |
| Unsuitable extinguishing media | : | Water<br>High volume water jet  |

### 5.2 Special hazards arising from the substance or mixture

- |                                       |   |   |
|---------------------------------------|---|---|
| Specific hazards during fire-fighting | : | Do not use a solid water stream as it may scatter and spread fire.<br>Do not allow run-off from fire fighting to enter drains or water courses. |
|---------------------------------------|---|---|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025

Version 3.0

Print Date 01.07.2025

Date of last issue: 11.10.2024

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
cyclohexane	110-82-7	TWA	200 ppm 700 mg/m <sup>3</sup>	2006/15/EC
Further information: Indicative				
		OELV - 8 hrs (TWA)	200 ppm 700 mg/m <sup>3</sup>	IE OEL
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017/164/EU
Further information: Indicative				
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
		OELV - 8 hrs (TWA)	200 ppm 734 mg/m <sup>3</sup>	IE OEL
		OELV - 15 min (STEL)	400 ppm 1.468 mg/m <sup>3</sup>	IE OEL

\*The above mentioned values are in accordance with the legislation in effect at the date of the re-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

lease of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

- |                          |   |   |
|--------------------------|---|---|
| Eye/face protection      | : | Safety glasses with side-shields conforming to EN166<br>Eye wash bottle with pure water   |
| Hand protection          | : | Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.<br>Suitable for short time use or protection against splashes:<br>Butyl rubber/nitrile rubber gloves (> 0,1 mm)<br>Contaminated gloves should be removed.<br>Suitable for permanent exposure:<br>Viton gloves (0.4 mm),<br>breakthrough time >30 min.   |
| Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.   |
| Respiratory protection   | : | In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.<br>organic vapor filter (Type A)<br>A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm<br>Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. |

#### Environmental exposure controls

- |                |   |  |
|----------------|---|--|
| General advice | : | Prevent product from entering drains.<br>If the product contaminates rivers and lakes or drains inform respective authorities. |
|----------------|---|--|

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

Physical state : liquid  
Colour : black

Odour : slight

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : ca. 60 °C

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit  
per flammability limit : 8,3 %(V)

Lower explosion limit / Lower flammability limit : Lower flammability limit  
1,3 %(V)

Flash point : ca. -18 °C  
Method: closed cup

Auto-ignition temperature : 427 °C

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

### Viscosity

Viscosity, dynamic : ca. 900 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : ca. 175 hPa (20 °C)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

Density : ca. 0,84 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Components:

ethyl acetate:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): ca. 1.600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

### **zinc bis(dibutyldithiocarbamate):**

Acute oral toxicity : LD50 Oral: > 5.000 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Not classified due to lack of data.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified due to lack of data.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

#### **Carcinogenicity**

Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified due to lack of data.

#### **Aspiration toxicity**

Not classified due to lack of data.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

Not classified due to lack of data.

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l  
Exposure time: 96 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025

Version 3.0

Print Date 01.07.2025

Date of last issue: 11.10.2024

Product	: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	: 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	: 15 01 10* packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR	: UN 1133
IMDG	: UN 1133
IATA	: UN 1133

#### 14.2 UN proper shipping name

ADR	: ADHESIVES
IMDG	: ADHESIVES (cyclohexane)
IATA	: Adhesives

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

#### 14.4 Packing group

ADR	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

Labels : 3  
Tunnel restriction code : (D/E)  
Remarks : Transport according to 2.2.3.1.4 ADR.

### IMDG

Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Remarks : Transport according to 2.3.2.2 IMDG.

### IATA (Cargo)

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids  
Remarks : Transport according to 3.3.3.1.1 IATA.

### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

### IATA (Passenger)

Environmentally hazardous : yes

### IATA (Cargo)

Environmentally hazardous : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Country IE 000000123613

13 / 17

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025

Version 3.0

Print Date 01.07.2025

Date of last issue: 11.10.2024

### Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 57: cyclohexane

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

E1 ENVIRONMENTAL HAZARDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025  
Date of last issue: 11.10.2024

Version 3.0

Print Date 01.07.2025

### II

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 63,4% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 63,4% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT SE : Specific target organ toxicity - single exposure  
2006/15/EC : Europe. Indicative occupational exposure limit values  
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025

Version 3.0

Print Date 01.07.2025

Date of last issue: 11.10.2024

IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
2006/15/EC / TWA	:	Limit Value - eight hours
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Primer-600



Revision Date: 01.07.2025

Version 3.0

Print Date 01.07.2025

Date of last issue: 11.10.2024

---



Changes as compared to previous version !

IE / EN