

Version 3.0

Print Date 08.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikalastic[®] Rapid-721 Thixo

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Special coating, Sealant/adhesive, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Ireland Ltd Sika House Ballymun Industrial Estate
Telephone	Dublin 11 : +353 1862 0709
E-mail address of person	: EHS@UK.Sika.com
responsible for the SDS	

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic[®] Rapid-721 Thixo



Revision Date: 08.05.2025 Version 3.0 Print Date 08.05.2025 Date of last issue: 14.03.2024 Hazard pictograms 2 Signal word Warning Flammable liquid and vapour. Hazard statements H226 Causes skin irritation. H315 H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. Prevention: Precautionary statements : P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. Wash skin thoroughly after handling. P264 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

2-ethylhexyl acrylate methyl methacrylate Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4methylphenyl)amino]-ethanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-
tion (EU) 2020/878
Sikalastic [®] Rapid-721 Thixo



Version 3.0

Print Date 08.05.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
2-ethylhexyl acrylate	103-11-7	Skin Irrit. 2; H315	>= 10 - < 20
	203-080-7	Skin Sens. 1B; H317	
	01-2119453158-37-	STOT SE 3; H335	
	XXXX	(Respiratory system)	
		Aquatic Chronic 3;	
		H412	
methyl methacrylate	80-62-6	Flam. Liq. 2; H225	>= 10 - < 20
	201-297-1	Skin Irrit. 2; H315	
	01-2119452498-28-	Skin Sens. 1; H317	
	XXXX	STOT SE 3; H335	
		(Respiratory system)	
Reaction mass of 2,2'-[(4-	103671-44-9	Acute Tox. 4; H302	>= 0,1 - < 0,25
methylphenyl)imino]bisethanol	911-490-9	Skin Irrit. 2; H315	
and 2-[[2-(2-	01-2119979579-10-	Eye Dam. 1; H318	
hydroxyethoxy)ethyl](4-	XXXX	Skin Sens. 1; H317	
methylphenyl)amino]-ethanol		Aquatic Chronic 3;	
		H412	
		Acute toxicity esti- mate	
		male	
		Acute oral toxicity:	
		619 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing.

Sikalastic[®] Rapid-721 Thixo



Revision Date: 08.05.2025 Date of last issue: 14.03.2024	Version 3.0	Print Date 08.05.2025
	If eye irritation persists, consult a specialist.	
If swallowed	 Do not induce vomiting without medical advice Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscion 	
4.2 Most important symptoms and	d effects, both acute and delayed	
Symptoms	: Cough Respiratory disorder Allergic reactions Erythema Dermatitis See Section 11 for more detailed information of and symptoms.	on health effects
Risks	: irritant effects sensitising effects	
	Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.	
-	edical attention and special treatment needed	
Treatment	: Treat symptomatically.	

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media :	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Sand Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing : media	Water High volume water jet
5.2 Special hazards arising from th	e substance or mixture
Specific hazards during fire- : fighting	Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion prod- : ucts	No hazardous combustion products are known

Jika®

Print Date 08.05.2025

5.3 Advice for firefighters Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.
Further information	: Use water spray to cool unopened containers.
SECTION 6: Accidental release	e measures
6.1 Personal precautions, protect	ive equipment and emergency procedures
Personal precautions	 Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions	
Environmental precautions	 Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for cont	ainment and cleaning up
	· Soak up with inert absorbent material (e.g. sand silica gel

Version 3.0

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

Revision Date: 08.05.2025

Date of last issue: 14.03.2024

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth-
	ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the ap- plication area.
	Take precautionary measures against static discharge.
	Open drum carefully as content may be under pressure.
	Take necessary action to avoid static electricity discharge
	(which might cause ignition of organic vapours).
	Follow standard hygiene measures when handling chemical products

Sikalastic[®] Rapid-721 Thixo



Revision Date: 08.05.2025 Date of last issue: 14.03.2024	Version 3.0	Print Date 08.05.2025
Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep away fro open flames/ hot surfaces. No smoking. Take measures against electrostatic discharges.	•
Hygiene measures :	Handle in accordance with good industrial hyg practice. When using do not eat or drink. Whe smoke. Wash hands before breaks and at the	n using do not
7.2 Conditions for safe storage, inc	luding any incompatibilities	
Requirements for storage : areas and containers	Keep container tightly closed in a dry and well place. Store in accordance with local regulatio	
Further information on stor- : age stability	No decomposition if stored and applied as dire	ected.

7.3 Specific end use(s)

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
	Further informa	ation: Indicative		
		STEL	100 ppm	2009/161/EU
		OELV - 8 hrs	50 ppm	IE OEL
		(TWA)		
	Further information: Chemical agents which following exposure			
	may cause sensitisation of the respiratory tract and lead to asth-			
	ma, rhinitis or extrinsic allergic alveolitis			
		OELV - 15 min	100 ppm	IE OEL
		(STEL)		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

:

Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water

Sikalastic[®] Rapid-721 Thixo



Revision Date: 08.05.2025 Version 3.0 Print Date 08.05.2025 Date of last issue: 14.03.2024 Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345. long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work. Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. **Environmental exposure controls** General advice : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste various
Odour	:	ester-like
Melting point/ range / Freez- ing point	:	No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic[®] Rapid-721 Thixo



Revision Date: 08.05.2025 Date of last issue: 14.03.2024		Version 3.0	Print Date 08.05.2025
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or e	-		
Upper explosion limit / Up- per flammability limit	:	12,5 %(V)	
Lower explosion limit / Lower flammability limit	:	1,7 %(V)	
Flash point	:	ca. 24 °C Method: closed cup	
Auto-ignition temperature	:	252 °C	
Decomposition temperature	:	No data available	
рН	:	substance/mixture is non-polar/aprotic	
Viscosity			
Viscosity, dynamic	:	ca. 26.000 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	log Pow: 4,29 (25 °C) Method: OECD Test Guideline 107	
Vapour pressure	:	40 hPa	
Density	:	ca. 1,21 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	



Revision Date: 08.05.2025 Date of last issue: 14.03.2024	Version 3.0	Print Date 08.05.2025
9.2 Other information		
No data available		
SECTION 10: Stability and react	vity	
10.1 Reactivity		
No dangerous reaction known u	ler conditions of normal use.	
10.2 Chemical stability		
The product is chemically stable		
10.3 Possibility of hazardous react	ns	
Hazardous reactions	Stable under recommended storage conditions	
	Vapours may form explosive mixture with air.	
10.4 Conditions to avoid		
Conditions to avoid	Heat, flames and sparks.	
10.5 Incompatible materials		
Materials to avoid	No data available	
10.6 Hazardous decomposition pro	ucts	
	No hazardous decomposition products are kno	wn.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified due to lack of d	lata.	
Components:		
2-ethylhexyl acrylate: Acute oral toxicity	:	LD50 Oral (Rat): 4.435 mg/kg
methyl methacrylate: Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 29,8 mg/l Exposure time: 4 h Test atmosphere: vapour

Sikalastic[®] Rapid-721 Thixo



evision Date: 08.05.2025 Pate of last issue: 14.03.2024	Version 3.0	Print Date 08.05.202
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 mg/kg	
Reaction mass of 2,2'-[(4-m methylphenyl)amino]-ethan	ethylphenyl)imino]bisethanol and 2-[[2-(2-hyd ol:	roxyethoxy)ethyl](4-
Acute oral toxicity	: LD50 Oral (Rat): 619 mg/kg	
	Acute toxicity estimate: 619 mg/kg Method: Calculation method	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg	
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye irri Not classified due to lack of d		
Respiratory or skin sensitis	ation	
Skin sensitisation May cause an allergic skin rea	action.	
Respiratory sensitisation Not classified due to lack of d	ata.	
Germ cell mutagenicity Not classified due to lack of d	ata.	
Carcinogenicity Not classified due to lack of d	ata.	
Reproductive toxicity Not classified due to lack of d	ata.	
STOT - single exposure May cause respiratory irritatio	n.	
STOT - repeated exposure Not classified due to lack of d	ata.	
Aspiration toxicity Not classified due to lack of d	ata.	
11.2 Information on other hazard	ds	
Endocrine disrupting prope Not classified due to lack of d		
Product:		
Assessment	: The substance/mixture does not contain cor ered to have endocrine disrupting properties REACH Article 57(f) or Commission Delega (EU) 2017/2100 or Commission Regulation	s according to ted regulation
	levels of 0.1% or higher.	10/17



Version 3.0

Print Date 08.05.2025

SECTION 12: Ecological information

12.1 Toxicity

	Components:		
	2-ethylhexyl acrylate:		
	Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 1,81 mg/l Exposure time: 96 h
	Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,3 mg/l Exposure time: 48 h
	Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): 1,71 mg/l Exposure time: 72 h
	methyl methacrylate:		
	Toxicity to fish	:	NOEC (Danio rerio (zebra fish)): 9,4 mg/l
	Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
			NOEC : 37 mg/l Exposure time: 21 d Method: OECD Test Guideline 202
	Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 37 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)
12.2	2 Persistence and degradabili No data available	ity	
12 3	Bioaccumulative potential		
12.5	No data available		
12.4	Hobility in soil No data available		
12.5	5 Results of PBT and vPvB as	se	ssment

12.5 Results of PBT and vPvB assessment

Product:

Assessment	: This substance/mixture contains no components considered	
	to be either persistent, bioaccumulative and toxic (PBT), or	
	very persistent and very bioaccumulative (vPvB) at levels of	
	0.1% or higher	
	0.178 of higher.	



Version 3.0

Print Date 08.05.2025

12.6 Endocrine disrupting properties

Product:

Assessment

essment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
		0

12.7 Other adverse effects

Product:

Additional ecological infor-	:	There is no data available for this product.
mation		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADR	:	PAINT RELATED MATERIAL
IMDG	:	PAINT RELATED MATERIAL
ΙΑΤΑ	:	Paint related material
14.3 Transport hazard class(es)		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic[®] Rapid-721 Thixo



Revision Date: 08.05.2025 Date of last issue: 14.03.2024		Version 3.0	Print Date 08.05.2025	
		Class Subsidiary risks		
ADR		3		
IMDG	:			
	:	3		
	:	3		
14.4 Packing group				
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks		III F1 30 3 (D/E) Exempted according to 2.2.3.1.5 (Viscou tion)	us substance exemp-	
IMDG				
Packing group Labels	:	 3		
EmS Code	÷	5 F-E, <u>S-E</u>		
Remarks	:	Transport in accordance with 2.3.2.5 of	the IMDG-Code	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group	:	366 Y344 III		
Labels	:	Flammable Liquids		
IATA (Passenger) Packing instruction (passen- ger aircraft)	:	355		
Packing instruction (LQ) Packing group	:	Y344 III		
Labels	:	Flammable Liquids		
14.5 Environmental hazards				
ADR Environmentally hazardous	:	no		
IMDG Marine pollutant	:	no		
IATA (Passenger) Environmentally hazardous	:	no		
IATA (Cargo) Environmentally hazardous	:	no		
14.6 Special precautions for use	r			

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Sikalastic[®] Rapid-721 Thixo

Revision Date: 08.05.2025	Version 3.0	Print Date 08.05.2025
Date of last issue: 14.03.2024		

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors					
REACH Information: - registered by our up - registered by us, and - excluded from the re - exempted from the re			m suppliers, and/or tion, and/or		
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)			Conditions of restriction for the fol- lowing entries should be considered: Number on list 3		
			Number on list 75		
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			None of the components are listed (=> 0.1 %).		
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable		
Regulation (EU) No 2024/590 on plete the ozone layer	substances that de-	:	Not applicable		
Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu-	:	Not applicable		
Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable		

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic[®] Rapid-721 Thixo



Revision Date: 08.05.2025 Date of last issue: 14.03.2024	Version 3.0	Print Date 08.05.2025		
P5c	FLAMMABLE LIQUIDS			
Volatile organic compounds	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: <= 3% w/w no VOC duties			
	Directive 2010/75/EU of 24 November 24 livestock rearing emissions (integrated p and control) Volatile organic compounds (VOC) conte	ollution prevention		

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	:	Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation		Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or mixture:		Control of Substances Hazardous to Health Regulations (COSHH)
		May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full	text of	H-Statements
------	---------	---------------------

H225 H302 H315 H317 H318 H335 H412	:	Highly flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.		
Full text of other abbreviations				
Acute Tox. Aquatic Chronic Eye Dam. Flam. Liq. Skin Irrit. Skin Sens. STOT SE 2009/161/EU		Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Flammable liquids Skin irritation Skin sensitisation Specific target organ toxicity - single exposure Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC		
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occu-		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic[®] Rapid-721 Thixo



Revision Date: 08.05.2025 Date of last issue: 14.03.2024 Version 3.0

Print Date 08.05.2025

2009/161/EU / TWA 2009/161/EU / STEL IE OEL / OELV - 8 hrs (TWA) IE OEL / OELV - 15 min (STEL) ADR CAS DNEL EC50 GHS IATA IMDG LD50		pational Exposure Limit Values - Code of Practice, Schedule 1 and 2 Limit Value - eight hours Short term exposure limit Occupational exposure limit value (8-hour reference period) Occupational exposure limit value (15-minute reference peri- od) European Agreement concerning the International Carriage of Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC vPvB	:	Substances of Very High Concern Very persistent and very bioaccumulative

Further information

Classification of the	mixture:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikalastic[®] Rapid-721 Thixo

Revision Date: 08.05.2025 Date of last issue: 14.03.2024

IE / EN

Version 3.0



Print Date 08.05.2025