

Revision Date: 12.05.2025
Date of last issue: 18.10.2024

Version 6.1

Print Date 12.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] Primer MB Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd
		Sika House
		Ballymun Industrial Estate
		Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person	:	EHS@UK.Sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Primer MB Part B



Revision Date: 12.05.2025 Version 6.1 Print Date 12.05.2025 Date of last issue: 18.10.2024 Hazard pictograms 2 Signal word Danger 1 H302 + H332 Harmful if swallowed or if inhaled. Hazard statements Causes severe skin burns and eye damage. H314 H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects. Supplemental Hazard EUH071 Corrosive to the respiratory tract. 5 Statements Precautionary statements Prevention: · P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) Amines, polyethylenepoly-, tetraethylenepentamine fraction 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sika[®] Primer MB Part B

Revision Date: 12.05.2025 Date of last issue: 18.10.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti- mate	>= 40 - < 60
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32-	Acute oral toxicity: 1.200 mg/kg Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318	>= 10 - < 20
	XXXX	Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A; H317	
		>= 0,001 % Acute toxicity estimate	
		Acute oral toxicity: 1.030 mg/kg	

Version 6.1



Print Date 12.05.2025

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Primer MB Part B

Jika®

Revision Date: 12.05.2025 Date of last issue: 18.10.2024 Version 6.1

of last issue: 18.10.2024			
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity esti- mate Acute oral toxicity: 930 mg/kg Acute inhalation tox- icity (dust/mist): 1,34 mg/l	>= 10 - < 20
Amines, polyethylenepoly-, tetra- ethylenepentamine fraction	90640-66-7 292-587-7 01-2119487290-37- XXXX	mg/l Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 2; H411 Acute toxicity esti- mate Acute oral toxicity: 1.716 mg/kg Acute dermal toxicity: 1.465 mg/kg	>= 5 - < 10
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg	>= 5 - < 10
2-Propenenitrile, reaction prod- ucts with 2,2,4(or 2,4,4)-trimethyl- 1,6-hexanediamine	90530-20-4 292-059-6 01-2120773937-35- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 3 - < 5

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika[®] Primer MB Part B

evision Date: 12.05.2025 ate of last issue: 18.10.2024	Version 6	Print Date 12.05.2025	
2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine	25513-64-8 247-063-2 01-2119560598-25- XXXX	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Acute toxicity esti- mate Acute oral toxicity: 910 mg/kg	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measu	ires
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms an	d effects, both acute and delayed
Symptoms	: Gastrointestinal discomfort Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed information on health effects and symptoms.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Primer MB Part B



Revision Date: 12.05.2025 Date of last issue: 18.10.2024		Version 6.1	Print Date 12.05.202
Risks	:	Health injuries may be delayed. corrosive effects sensitising effects	
		Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage.	
		Causes severe burns. Corrosive to the respiratory tract.	
	neo	dical attention and special treatment needed	
Treatment		Treat symptomatically.	
SECTION 5: Firefighting meas	ur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/c ide/sand/foam/alcohol resistant foam/chemical p extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathin	g apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental release	e r	neasures	
6.1 Personal precautions, protect	tiv	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary sewe If the product contaminates rivers and lakes or or respective authorities.	
6.3 Methods and material for con	tai	nment and cleaning up	
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand	l, silica gel,



Version 6.1

Print Date 12.05.2025

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.



Version 6.1

Print Date 12.05.2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
m-phenylenebis(methylamine)	1477-55-0	OELV - 8 hrs (TWA)	0,1 mg/m3	IE OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sika® Primer MB Part B



Revision Date: 12.05.2025
Date of last issue: 18.10.2024

Version 6.1

Print Date 12.05.2025

Environmental exposure controls General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

: ca. 12 mPa.s (20 °C)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

information on basic physical	an	d chemical properties
Physical state Colour	:	liquid light yellow
Odour	:	amine-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	ca. 420 °C
Decomposition temperature	:	No data available
рН	:	> 11 Concentration: 100 %
Viscosity		
$\Lambda P = 1 + 1 + 1 + 2 + 1 + 2$		10 · · · · · · · · · · · · · · · · · · ·

Viscosity, dynamic

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Primer MB Part B



Revision Date: 12.05.2025 Date of last issue: 18.10.2024		Version 6.1	Print Date 12.05.2025
Viscosity, kinematic	: >7-<	< 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	: insolu	ble	
Partition coefficient: n- octanol/water	: No da	ta available	
Vapour pressure	: 0,07 h	ıPa	
Density	: ca. 1,0	018 g/cm3 (20 °C)	
Relative vapour density	: No da	ta available	
Particle characteristics	: No da	ta available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



Version 6.1

Print Date 12.05.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed or if inhaled. **Components:**

benzyl alcohol:		
Acute oral toxicity	:	Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
		LD50 Oral (Rat): 1.200 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist
3-aminomethyl-3,5,5-trimet	hylc	cyclohexylamine:
Acute oral toxicity	:	Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
		LD50 Oral (Rat): 1.030 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
		LD50 (Rabbit): > 2.000 - 5.000 mg/kg
m-phenylenebis(methylami	ine):	
Acute oral toxicity	:	LD50 Oral (Rat): 930 mg/kg
		Acute toxicity estimate: 930 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Primer MB Part B



Acute dermal toxicity:LD50 Dermal (Rat): > 3.100 mg/kgAmines, polyethylenepoly., tetraethylenepentamine fraction:Acute oral toxicity:LD50 Oral (Rat): 1.716 mg/kg Method: Calculation methodAcute dermal toxicity:LD50 Dermal (Rat): 1.426 mg/kg Method: Calculation methodAcute dermal toxicity:LD50 Dermal (Rat): 1.465 mg/kg Method: Calculation methodAcute oral toxicity:LD50 (Rat): 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/20082,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:Acute toxicity estimate: 910 mg/kg Method: Calculation methodAcute oral toxicity:LD50 Oral (Rat): 910 mg/kg Method: Calculation method2,4,6-tris(dimethylaminomethyl)benol: SigneideSource CorrosiveAcute oral toxicity:D50 Oral (Rat): 910 mg/kg Method: Calculation methodSkin corrosion/irritation Causes severe burms.Corrosive MethodComponentsi:Source Corrosive2,4,6-tris(dimethylaminomethyl)benol: Signeide:Species::Adues severe burms.Corrosive Causes serious eye damage/eye irritation ReGULATION (EC) No 1272/2008Serious eye damage/eye irritation Causes serious eye damage/eye irritation Causes serious eye damage/eye irritation Causes serious eye damage.2,4,6-tris(dimethylaminomethylphenol: Species:Componentsi:2,4,6-tris(dimethylaminomethylphenol: Causes serious eye damage.Species:Causes serious eye damage.Caus	sion Date: 12.05.2025 of last issue: 18.10.2024	Version 6.1	Print Date 12.05.2025
Acute oral toxicity LD50 Oral (Rat): 1.716 mg/kg Acute toxicity estimate: 1.716 mg/kg Method: Calculation method Acute dermal toxicity LD50 Dermal (Rat): 1.465 mg/kg Acute toxicity estimate: 1.465 mg/kg Acute toxicity estimate: 1.465 mg/kg Acute oral toxicity LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008 Recute toxicity estimate: 910 mg/kg Acute oral toxicity LD50 Oral (Rat): 910 mg/kg Acute toxicity estimate: 910 mg/kg Acute toxicity estimate: 910 mg/kg Acute toxicity estimate: 910 mg/kg Acute toxicity estimate: 910 mg/kg Species Rabbit Assessment CORSUM Assessment CORSUM Remarks Annex VI - Harmonised Regulation (EC) No 1272/2008 Species Annex VI - Harmonised Regulation (EC) No 1272/2008 Sessesment Corseive Remarks Annex VI - Harmonised	Acute dermal toxicity	: LD50 Dermal (Rat): > 3.100 mg/kg	
Acute toxicity estimate: 1.716 mg/kg Method: Calculation method Acute dermal toxicity : LD50 Dermal (Rat): 1.465 mg/kg Acute toxicity estimate: 1.465 mg/kg Method: Calculation method 2.4,6-tris(dimethylaminomethyl)phenol: Acute oral toxicity : Acute toxicity estimate: 910 mg/kg Method: Calculation method Skin corrosion/irritation Causes servere burns. Components: 2.4,6-tris(dimethylaminomethyl)phenol: Syspecies : Reigul ATION (EC) No 1272/2008 Serious eye damage/eye irritation <t< td=""><td>Amines, polyethylenepoly</td><td>-, tetraethylenepentamine fraction:</td><td></td></t<>	Amines, polyethylenepoly	-, tetraethylenepentamine fraction:	
Method: Calculation method Acute dermal toxicity : LD50 Dermal (Rat): 1.465 mg/kg Acute toxicity estimate: 1.465 mg/kg Method: Calculation method 2.4.6-tris(dimethylaminomethyl)phenol: Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008 2.2.4(or 2.4.4)-trimethylhexane-1.6-diamine: Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Method: Calculation method : Calculation method Skin corrosion/irritation : Calculation method Causes severe burns. : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks Remarks : irritating REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation : irritating REGULATION (EC) No 1272/2008 Causes serious eye damage. : Rabbit Assessment 24,6-tris(dimethylaminomethyl)phenol: : Species Species	Acute oral toxicity	: LD50 Oral (Rat): 1.716 mg/kg	
Acute toxicity estimate: 1.465 mg/kg Method: Calculation method 2.4,6-tris(dimethylaminomethyl)phenol: Acute oral toxicity LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008 2.2,4(or 2,4,4)-trimethylhexane-1,6-diamine: Acute oral toxicity it LD50 Oral (Rat): 910 mg/kg Acute toxicity estimate: 910 mg/kg Method: Calculation method 2.2,4(or 2,4,4)-trimethylhexane-1,6-diamine: Acute oral toxicity it LD50 Oral (Rat): 910 mg/kg Method: Calculation method Skin corrosion/irritation Causes severe burns. Components: 2.4,6-tris(dimethylaminomethyl)phenol: Species Rabbit Assessment Assessment it Orrosive Method Method COED Test Guideline 404 Assessment it Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: 2.4,6-tris(dimethylaminomethyl)phenol: Causes serious eye damage. Components: 2.4,6-tris(dimethylaminomethyl)phenol: Causes serious eye damage. Components: 2.4,6-tris(dimethylaminomethyl)phenol: Causes serious eye damage.			
Acute oral toxicity LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine: Acute oral toxicity : Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Method: Calculation method 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine: Acute oral toxicity : Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Method: Calculation method Skin corrosion/irritation Causes severe burns. : . Components: : . 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment Assessment : : Method : OECD Test Guideline 404 Assessment : : REGULATION (EC) No 1272/2008 : Serious eye damage/eye irritation Causes serious eye damage. : Components: : : 2,4,6-tris(dimethylaminomethyl)phenol: : Species : : Causes serious eye damage. : Components: : : 2,4,6-tris(dimethylaminomethyl)phenol: : Species :	Acute dermal toxicity	: LD50 Dermal (Rat): 1.465 mg/kg	
Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine: Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Acute toxicity estimate: 910 mg/kg Method: Calculation method Skin corrosion/irritation Causes severe burns. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : OCT Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008			
Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine: Acute oral toxicity : Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Acute toxicity estimate: 910 mg/kg Method: Calculation method Skin corrosion/irritation Causes severe burns.	2,4,6-tris(dimethylaminor	ethyl)phenol:	
Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg Acute toxicity estimate: 910 mg/kg Acute toxicity estimate: 910 mg/kg Skin corrosion/irritation Calculation method Causes severe burns. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Secies Species : Rabbit Assessment : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. 2,4,6-tris(dimethylaminomethyl)phenol: Species Species : Rabbit Assessment : Causes serious eye damage.	Acute oral toxicity	Remarks: Harmful if swallowed. Annex VI - Harmonised	
Acute toxicity estimate: 910 mg/kg Method: Calculation method Skin corrosion/irritation Causes severe burns. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : irritation REGULATION (EC) No 1272/2008 Serious eye damage. : Components: : 2,4,6-tris(dimethylaminomethyl)phenol: : Species : Rabbit Assessment : Causes serious eye damage.	2,2,4(or 2,4,4)-trimethylhe	xane-1,6-diamine:	
Method: Calculation method Skin corrosion/irritation Causes severe burns. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.	Acute oral toxicity	: LD50 Oral (Rat): 910 mg/kg	
Causes severe burns. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.			
Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.	Skin corrosion/irritation		
2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: : 2,4,6-tris(dimethylaminomethyl)phenol: Species Species : Rabbit Assessment Assessment : Causes serious eye damage.			
Species : Rabbit Assessment : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised Remarks : Annex VI - Harmonised Regulation : REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: : . 2,4,6-tris(dimethylaminomethyl)phenol: . Species : Rabbit Assessment : Causes serious eye damage.	Components:		
Assessment : Corrosive Method : OECD Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.			
Method : OECD Test Guideline 404 Assessment : irritating Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.			
Remarks : Annex VI - Harmonised REGULATION (EC) No 1272/2008 Serious eye damage/eye irritation Causes serious eye damage. Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.			
Causes serious eye damage. <u>Components:</u> 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.		: Annex VI - Harmonised	
Components: 2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.	Serious eye damage/eye i	rritation	
2,4,6-tris(dimethylaminomethyl)phenol: Species : Rabbit Assessment : Causes serious eye damage.	Causes serious eye damag	e.	
Species:RabbitAssessment:Causes serious eye damage.	Components:		
Assessment : Causes serious eye damage.	2,4,6-tris(dimethylaminom	ethyl)phenol:	
Assessment : irritating	•		
	Assessment	: irritating	

Sika[®] Primer MB Part B



Revision Date: 12.05.2025 Date of last issue: 18.10.2024

Version 6.1

Print Date 12.05.2025

Remarks

: Annex VI - Harmonised REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:		
benzyl alcohol:		
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Country IE 00000023916		

Sika[®] Primer MB Part B



Revision Date: 12.05.2025 Date of last issue: 18.10.2024		Version 6.1	Print Date 12.05.2025
3-aminomethyl-3,5,5-trimethy	vlo	velehovulamino	
Toxicity to algae/aquatic plants	ую :	ErC50 (Desmodesmus subspicatus (gree mg/l Exposure time: 72 h	•
		NOEC (Desmodesmus subspicatus (gree Exposure time: 72 h	en algae)): 1,5 mg/l
m-phenylenebis(methylamin	e):		
Toxicity to fish	:	LC50 (Oryzias latipes (Japanese medaka Exposure time: 96 h	a)): > 10 - 100 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10 Exposure time: 48 h	0 - 100 mg/l
2,2,4(or 2,4,4)-trimethylhexar	ne	1,6-diamine:	
Toxicity to algae/aquatic plants	:	EC50 (Scenedesmus capricornutum (fres mg/l Exposure time: 72 h	sh water algae)): 29,5
Toxicity to fish (Chronic tox- icity)	:	LC50: 174 mg/l Exposure time: 48 h Species: Leuciscus idus (Golden orfe)	
12.2 Persistence and degradabili No data available	ty		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	se	ssment	
Product:			
Assessment	:	This substance/mixture contains no comp to be either persistent, bioaccumulative a very persistent and very bioaccumulative 0.1% or higher	nd toxic (PBT), or
12.6 Endocrine disrupting proper	rtie	s	
Product:			
Assessment	:	The substance/mixture does not contain	

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

Sika[®] Primer MB Part B



Revision Date: 12.05.2025 Date of last issue: 18.10.2024	Version 6.1	Print Date 12.05.2025
	levels of 0.1% or higher.	
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	: An environmental hazard cannot be ex unprofessional handling or disposal. Harmful to aquatic life with long lasting	
SECTION 13: Disposal conside	erations	
13.1 Waste treatment methods		
Product	: The generation of waste should be avo wherever possible.	pided or minimized

Product		 wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	: UN 1760	
IMDG	: UN 1760	
ΙΑΤΑ	: UN 1760	
14.2 UN proper shipping name		
ADR	: CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine))	
IMDG	: CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Primer MB Part B



Revision Date: 12.05.2025 Date of last issue: 18.10.2024		Version 6.1	Print Date 12.05.202
		phenylenebis(methylamine))	
ΙΑΤΑ	:	Corrosive liquid, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohex phenylenebis(methylamine))	ylamine, m-
14.3 Transport hazard class(es)			
		Class Subsidiary risks	
ADR	:	8	
IMDG	:	8	
ΙΑΤΑ	:	8	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	II C9 80 8 (E)	
IMDG Packing group Labels EmS Code	:	II 8 F-A, S-B	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	855 Y840 II Corrosive	
IATA (Passenger)	:	851 Y840 II Corrosive	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	no	
IMDG Marine pollutant	:	no	
IATA (Passenger) Environmentally hazardous	:	no	
IATA (Cargo) Environmentally hazardous	:	no	



Version 6.1

Print Date 12.05.2025

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products are
	registered by our upstrages suppliers and/or

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 75
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
Regulation (EU) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable

Sika[®] Primer MB Part B



Revision Date: 12.05.2025Version 6.1Print Date 12.05.2025Date of last issue: 18.10.2024

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. Not applicable					
Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 48% w/w				
	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 48% w/w				
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.					
Health, safety and environ- :	Environmental Protection Act 1990 & Subsidiary Regulations				

Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	:	Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH) May be subject to the Control of Major Accident Hazards
		Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 H312 H314 H315 H317 H318 H319 H332 H411 H412		Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
Full text of other abbreviati Acute Tox. Aquatic Chronic Eye Dam. Eye Irrit. Skin Corr. Skin Irrit. Skin Sens.	:	Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Skin corrosion Skin irritation Skin sensitisation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Primer MB Part B



Revision Date: 12.05.2025 Date of last issue: 18.10.2024		Version 6.1	Print Date 12.05.2025
IE OEL	:	Ireland. List of Chemical Agents and Carcinoger pational Exposure Limit Values - Code of Practi and 2	
IE OEL / OELV - 8 hrs (TWA) ADR	:	Occupational exposure limit value (8-hour refere European Agreement concerning the Internation Dangerous Goods by Road	
CAS	:	Chemical Abstracts Service	
DNEL	:	Derived no-effect level	
EC50	:	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
ΙΑΤΑ	:	International Air Transport Association	
IMDG	:	International Maritime Code for Dangerous Goo	
LD50	:	Median lethal dosis (the amount of a material, g once, which causes the death of 50% (one half) test animals)	
LC50	:	Median lethal concentration (concentrations of t air that kills 50% of the test animals during the c period)	
MARPOL	:	International Convention for the Prevention of P Ships, 1973 as modified by the Protocol of 1978	
OEL	:	Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
REACH	:	Regulation (EC) No 1907/2006 of the European and of the Council of 18 December 2006 concer- istration, Evaluation, Authorisation and Restricti- cals (REACH), establishing a European Chemic	rning the Reg- on of Chemi-
SVHC	:	Substances of Very High Concern	
vPvB	:	Very persistent and very bioaccumulative	

Further information

Classification of the	Classification procedure:	
Acute Tox. 4	H302	Calculation method
Acute Tox. 4	H332	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sika® Primer MB Part B

Version 6.1

Revision Date: 12.05.2025 Date of last issue: 18.10.2024

IE / EN

Jika®

Print Date 12.05.2025