

Revision Date: 24.04.2025 Date of last issue: 27.10.2023 Version 2.1

Print Date 24.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikagard[®]-850 Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd
		Sika House
		Ballymun Industrial Estate
		Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person	:	EHS@UK.Sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023			Ve	ersion 2.1	Print Date 24.04.2025
Signal word	:	Warning			
Hazard statements	:	H226 H317 H336	Мау	nmable liquid and vapour. cause an allergic skin reaction. cause drowsiness or dizziness.	
Supplemental Hazard Statements	:	EUH066		Repeated exposure may cause or cracking.	skin dryness
Precautionary statements	:	P101		If medical advice is needed, hav container or label at hand.	e product
		P102		Keep out of reach of children.	
		Prevention			
		P210		Keep away from heat, hot surface open flames and other ignition s smoking.	
		P271		Use only outdoors or in a well-ve	entilated ar-
		P280		Wear protective gloves/ protective gloves/ protection.	ve clothing/
		Response:			
		P370 + P37	8	In case of fire: Use dry sand, dry alcohol-resistant foam to exting	
		Disposal:			
		P501		Dispose of contents/container in with local regulation.	accordance

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics N,N-Dibutylaminomethyl-triethoxysilane N-(3-(trimethoxysilyl)propyl)ethylenediamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023 Version 2.1

Print Date 24.04.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned 919-857-5 01-2119463258-33- XXXX [corresponding group CAS 64742-48- 9]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 EUH066	>= 40 - < 60
silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis prod- ucts with silica	68909-20-6 272-697-1 01-2119379499-16- XXXX	STOT RE 2; H373 (Lungs) EUH066	>= 2,5 - < 5
Hydrocarbons, C12-C15, n- alkanes, isoalkanes < 2% aromat- ics	Not Assigned 920-107-4 01-2119453414-43- XXXX	Asp. Tox. 1; H304 EUH066	>= 2,5 - < 5
N,N-Dibutylaminomethyl- triethoxysilane	35501-23-6 Not Assigned 01-2120096609-40- XXXX	Skin Sens. 1B; H317	>= 1 - < 2,5
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned 918-481-9 01-2119457273-39- XXXX	Asp. Tox. 1; H304 EUH066	>= 1 - < 2,5
N-(3- (trimethoxysi- lyl)propyl)ethylenediamine Contains: N,N'-bis[3- (trimethoxysi- lyl)propyl]ethylenediamine <= 3 % 1-(2-Aminoethyl)-2,2-dimethoxy-1- aza-2-silacyclopertane <= 3 %	1760-24-3 217-164-6 01-2119970215-39- XXXX	Eye Dam. 1; H318 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 0,1 - < 0,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023		Version 2.1	Print Date 24.04.2025
		Consult a physician after significant exposure.	
In case of skin contact	:	Take off contaminated clothing and shoes imm Wash off with soap and plenty of water. If symptoms persist, call a physician.	ediately.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconsciou	
4.2 Most important symptoms a	nd	effects, both acute and delayed	
Symptoms	:	Allergic reactions Erythema Loss of balance Vertigo See Section 11 for more detailed information of and symptoms.	n health effects
Risks	:	sensitising effects	
		May cause an allergic skin reaction. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or	[·] cracking.
4.3 Indication of any immediate Treatment	me :	dical attention and special treatment needed Treat symptomatically.	

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025	Version 2.1	Print Date 24.04.2025
Date of last issue: 27.10.2023		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
----------------------	---	--

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical
-------------------------	---	---

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023	Version 2.1	Print Date 24.04.2025
	products	
Advice on protection against fire and explosion	: Use explosion-proof equipment. Keep a open flames/ hot surfaces. No smoking measures against electrostatic discharge	. Take precautionary
Hygiene measures	 Handle in accordance with good indust practice. When using do not eat or drin smoke. Wash hands before breaks and 	k. When using do not
7.2 Conditions for safe storage, in	cluding any incompatibilities	
Requirements for storage areas and containers	: Keep container tightly closed in a dry a place. Store in accordance with local re	
Further information on stor- age stability	: No decomposition if stored and applied	l as directed.
7.3 Specific end use(s)		
Specific use(s)	: Consult most current local Product Dat use.	a Sheet prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
		ation: Indicative, Ide rough the skin	entifies the possibi	ility of signifi-
		OELV - 8 hrs (TWA)	200 ppm 260 mg/m3	IE OEL
		ation: Substances v n when they come i e body		
ethanol	64-17-5	OELV - 15 min (STEL)	1.000 ppm	IE OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023 Version 2.1

Print Date 24.04.2025

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment					
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water				
Hand protection :	 Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. 				
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.				
Respiratory protection	No special measures required.				
Environmental exposure controls					
General advice	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform				

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste clear
Odour	:	mild
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023	Version 2.1	Print Date 24.04.2025				
Upper/lower flammability or explosive limits						
Upper explosion limit / Upper flammability limit						
Lower explosion limit / Lower flammability limit	0,7 %(V)					
Flash point	ca. 40 °C Method: closed cup					
Auto-ignition temperature	255 °C					
Decomposition temperature	No data available					
рН	Not applicable substance/mixture is non-sc	luble (in water)				
Viscosity						
Viscosity, kinematic	> 20,5 mm2/s (40 °C)					
Solubility(ies)						
Water solubility	insoluble					
Partition coefficient: n- octanol/water	No data available					
Vapour pressure	4 hPa					
Density	ca. 0,87 g/cm3 (20 °C)					
Relative vapour density	No data available					
Particle characteristics	No data available					

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023	Version 2.1	Print Date 24.04.202
10.2 Chemical stability		
The product is chemically stable		
10.3 Possibility of hazardous react	ions	
Hazardous reactions	Stable under recommended storage conditions.	
	Vapours may form explosive mixture with air.	
10.4 Conditions to avoid		
Conditions to avoid	Heat, flames and sparks.	
10.5 Incompatible materials		
Materials to avoid	No data available	
10.6 Hazardous decomposition pro	ducts	
Hazardous decomposition products	methanol, ethanol	
SECTION 11: Toxicological info	rmation	
11.1 Information on boyord alassas	as defined in Regulation (EC) No 1272/2008	
	as defined in Regulation (EC) No 12/2/2006	
Acute toxicity		
Not classified due to lack of data		

Components:

Hydrocarbons, C9-C11, n-a Acute oral toxicity	alkanes, isoalkanes, cyclics, <2% aromatics: : LD50 Oral (Rat): > 5.000 mg/kg				
Acute dermal toxicity	: LD50 Dermal (Rabbit): 3.160 mg/kg				
N-(3-(trimethoxysilyl)propy Acute oral toxicity	/I)ethylenediamine: : LD50 Oral (Rat): 2.995 mg/kg				
Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.					
<u>Components:</u>					
Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics:					
Result	: Repeated exposure may cause skin dryness or cracking.				

Serious eye damage/eye irritation

Not classified due to lack of data.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023 Version 2.1

Print Date 24.04.2025

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

2

Toxicity to daphnia and other	:	EC50 (Daphnia magna (Water flea)): > 1.000 mg/l
aquatic invertebrates		Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available Country IE 100000030714

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Date of last issue: 27.10.2023 Version 2.1

Print Date 24.04.2025

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

mation

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:		
Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor-	:	There is no data available for this product.

SECTION	13: C	Disposal	consideratio	ns

-

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.
 Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
 Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
 European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances



Revision Date: 24.04.2025 Date of last issue: 27.10.2023 Version 2.1

Print Date 24.04.2025

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	UN 1993	
	IMDG	:	UN 1993	
	ΙΑΤΑ	:	UN 1993	
14.2	UN proper shipping name			
	ADR	:	FLAMMABLE LIQUID (naphtha (petroleum))	
	IMDG	:	FLAMMABLE LIQUID (naphtha (petroleum))	
	ΙΑΤΑ	:	Flammable liquid, n.o. (naphtha (petroleum))	
14.3	Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	3	
	IMDG	:	3	
	ΙΑΤΑ	:	3	
14.4	Packing group			
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III F1 30 3 (D/E)	
	IMDG Packing group Labels EmS Code	:	III 3 F-E, S-E	
	IATA (Cargo) Packing instruction (cargo aircraft)	:	366	
	Packing instruction (LQ) Packing group Labels	: : :	Y344 III Flammable Liquids	
	IATA (Passenger) Packing group Labels	:	III Flammable Liquids	
115	Environmental hazards			

14.5 Environmental hazards

ADR

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



 Revision Date: 24.04.2025
 Version 2.1
 Print Date 24.04.2025

 Date of last issue: 27.10.2023
 Environmentally hazardous
 :
 no

 IMDG Marine pollutant
 :
 no
 Implementally hazardous
 :
 no

 IATA (Passenger) Environmentally hazardous
 :
 no
 ino
 ino

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu-	:	Not applicable

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 Version 2.1 Print Date 24.04.2025 Date of last issue: 27.10.2023 tants (recast) Regulation (EU) No 649/2012 of the European Parlia-: Not applicable ment and the Council concerning the export and import of dangerous chemicals Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. FLAMMABLE LIQUIDS P5c 34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d) Volatile organic compounds ÷ Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 55,95% w/w Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 55,95% w/w If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 :	Flammable liquid and vapour.
H304 :	May be fatal if swallowed and enters airways.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



sion Date: 24.04.2025 of last issue: 27.10.2023	Version 2.1	Print Date 24.04.2
11225	May aguag rearizatory irritation	
H335	: May cause respiratory irritation.	
H336	: May cause drowsiness or dizziness.	
H373	: May cause damage to organs through p exposure if inhaled.	prolonged or repeated
Full text of other abbreviatio	IS	
Asp. Tox.	: Aspiration hazard	
Eye Dam.	: Serious eye damage	
Flam. Liq.	: Flammable liquids	
Skin Sens.	: Skin sensitisation	
STOT RE	: Specific target organ toxicity - repeated	exposure
STOT SE	: Specific target organ toxicity - single ex	posure
2006/15/EC	: Europe. Indicative occupational exposu	re limit values
IE OEL	: Ireland. List of Chemical Agents and Ca	rcinogens with Occu-
	pational Exposure Limit Values - Code	
	and 2	
2006/15/EC / TWA	: Limit Value - eight hours	
IE OEL / OELV - 8 hrs (TWA)	: Occupational exposure limit value (8-ho	our reference period)
IE OEL / OELV - 15 min	: Occupational exposure limit value (15-n	
(STEL)	od)	
ADR	: European Agreement concerning the In	ternational Carriage of
	Dangerous Goods by Road	5
CAS	: Chemical Abstracts Service	
DNEL	: Derived no-effect level	
EC50	: Half maximal effective concentration	
GHS	: Globally Harmonized System	
IATA	: International Air Transport Association	
IMDG	: International Maritime Code for Danger	ous Goods
LD50	: Median lethal dosis (the amount of a ma	
	once, which causes the death of 50% (c	
	test animals)	
LC50	: Median lethal concentration (concentrat	ions of the chemical in
2000	air that kills 50% of the test animals dur	
	period)	
MARPOL	: International Convention for the Preven	tion of Pollution from
	Ships, 1973 as modified by the Protoco	
OEL	: Occupational Exposure Limit	
PBT	: Persistent, bioaccumulative and toxic	
PNEC	: Predicted no effect concentration	
REACH	: Regulation (EC) No 1907/2006 of the E	uropean Parliament
REAGI	and of the Council of 18 December 200	
	istration, Evaluation, Authorisation and	
	cals (REACH), establishing a European	
SVHC		Chemicals Agency
vPvB	 Substances of Very High Concern Very persistent and very bioaccumulativ 	10
VEVO	. very persistent and very bloaccumulativ	/e

Classification of the mixture:

Classification procedure:

Flam. Liq. 3	H226
--------------	------

Based on product data or assessment

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-850 Primer



Revision Date: 24.04.2025 _Date of last issue: 27.10.2023	3	Version 2.1	Print Date 24.04.2025
Skin Sens. 1	H317	Calculation method	
STOT SE 3	H336	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN