

PRODUCT DATA SHEET

EVERBUILD® ALL PURPOSE READY MIXED FILLER

FILLER FOR MULTIPLE PURPOSES

PRODUCT DESCRIPTION

EVERBUILD® ALL PURPOSE READY MIXED FILLER is an easy-to-use ready-mixed filler which is suitable for both interior and exterior use. Dries to a smooth but tough crack-resistant, sandable finish which may be painted, papered or stained. The product is designed for indoor or outdoor repairs to plaster, plasterboard, brick, render, wood, stone and most other building materials.

USES

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

CHARACTERISTICS / ADVANTAGES

- Heavy-duty tough filler – interior or exterior use.
- Ready-mixed formula – apply straight from tub or Easi-squeeze tube.
- Overpaintable with most solvent-based and emulsion paints.
- Overstainable
- Dries white.

Movement Accommodation Low – dries hard

Maximum Fill 9mm in one coat - further layers may be built up

Maximum Width 25mm

pH 8.5-9.9

PRODUCT INFORMATION

Packaging	600g & 1kg tubs, and 330g Easi-squeeze tubes.
Appearance / Colour	White
Shelf Life	24 months from date of manufacture when stored according to manufacturers instructions.
Storage Conditions	Store at temperatures between 5°C - 25°C and protect from frost.
Density	S.G. at 20°C ca. 1.8g / cm ³
Ambient Air Temperature	5°C to 30°C.
Drying time	1-8 hours depending on depth and temperature

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry, free from dust, grease and other contamination. Provide a key to gloss-painted surfaces. Cover nail or screw heads with oil-based paint and allow to dry.

APPLICATION

Tubs: Stir well and apply directly from the tub with spatula/spreader. Press the filler into the repair to a maximum depth of 9mm. For deeper cavities, apply in layers and allow each to dry (1 hour).

Easi-squeeze tubes: Remove cap and cut nozzle to required aperture. Squeeze directly into hole or crack and level with a filling knife. Note: do not exceed 5mm depth in one application. For greater depth, build up in individual layers.

Fill hole proud to allow for sanding and finish with a wet knife. Once dry, sand to a smooth finish. When used outdoors, seal repair with an oil based paint when fully dry.

CLEANING OF TOOLS

Clean tools immediately after use with warm water.

LIMITATIONS

- Do not use to fill plastic or metals.
- Do not apply externally when rain is imminent (within 5 hours of application)
- Do not apply in temperatures (ambient and surface) below 5°C.
- Not suitable for repairs to permanently wet areas.
- Do not apply in layers more than 9mm deep. If deeper holes need filling, build up in layers allowing each layer to dry (about 1 hour) before applying further layer. Alternatively use ONE STRIKE® LIGHTWEIGHT FILLER which may be applied in one application to a 75mm maximum depth.
- As the manufacturer cannot know all the uses their products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED
Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
EVERBUILD® ALL PURPOSE READY MIXED FILLER
May 2019, Version 02.01
020406010020000035

EVERBUILDALLPURPOSEREADYMIXEDFILLER-en-IE-(05-2019)-2-1.pdf

