

PRODUCT DATA SHEET

Sika® Retarder-50

Set retarding admixture for concrete

PRODUCT DESCRIPTION

Sika® Retarder-50 is a liquid admixture developed for the control of cement hydration. Sika® Retarder-50 retards and stabilises concrete mixes without negatively influencing their final strength.

USES

Sika® Retarder-50 retards the initial set in concrete to allow an extended period of workability.

CHARACTERISTICS / ADVANTAGES

Sika® Retarder-50 retards the hydration of cement.

- Strong retardation to facilitate long haulage duration
- High resistance to segregation with reduced bleed
- Extended workability

APPROVALS / STANDARDS

Conforms to the requirements of BS EN 934-2 Table 8 DoC 90726371, certified by Factory Production Control Body 0120 and provided with the UKCA mark DoP 76238927, certified by Factory Production Control Body 1029 and provided with the CE mark

PRODUCT INFORMATION

Chemical Base	Hydrocarboxylate and carbohydrate blend
Packaging	18 L drum, 200 L drum, 1000 L IBC
Shelf Life	12 months from date of production if stored properly in undamaged unopened, original sealed packaging.
Storage Conditions	Store in dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight and frost.
Appearance / Colour	Pale Straw Liquid
Specific gravity	1.21 kg/L
Total Chloride Ion Content	<0.1% w/w (chloride free)
Equivalent Sodium Oxide	<10.0 % w/w (alkali content)

APPLICATION INFORMATION

Recommended Dosage	0.2–2.0 % by weight of cement
Dispensing	Sika® Retarder-50 should be dispensed through suitably calibrated dosing equipment

Compatibility

Sika® Retarder-50 should not be mixed directly with the following admixtures prior to dispensing as solids can form in the mixture. This can cause increased viscosity and pump / pipe blockages:

Sika® Plastiment®-190

SikaRapid®-1

SikaRapid®-800 ECO

Sika® Viscoflow®-1000

Sika® Viscoflow®-2000

Important: Always conduct trials before combining products in specific mixes and contact our Technical Service Department for information and advice about any specific combinations.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

APPLICATION

- The standard rules of good concreting practice, concerning production and placing, are to be followed.
- Laboratory trials shall be carried out before concreting on site, especially when using a new mix design or producing new concrete components.
- Fresh concrete must be cured properly and curing applied as early as possible.
- Sika® Retarder-50 shall not be added to dry cement
- Overdosing will result in an increase in setting time

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet

Sika® Retarder-50

April 2024, Version 03.02

02140601100000030

SikaRetarder-50-en-IE-(04-2024)-3-2.pdf