according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikagard®-850 Clear

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Ireland Ltd

Sika House

Ballymun Industrial Estate

Dublin 11

Telephone : +353 1862 0709 E-mail address of person : EHS@UK.Sika.com

responsible for the SDS

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166

(available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear

Revision Date: 24.04.2025 Version 2.1 Print Date 24.04.2025

Date of last issue: 27.10.2023

Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

> H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

Supplemental Hazard

Statements

EUH066 Repeated exposure may cause skin dryness

or cracking.

If medical advice is needed, have product P101 Precautionary statements

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated ar-

P280 Wear protective gloves/ protective clothing/

eve protection/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics N.N-Dibutylaminomethyl-triethoxysilane trimethoxyvinylsilane

N-(3-(trimethoxysilyl)propyl)ethylenediamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikagard®-850 Clear

Revision Date: 24.04.2025 Version 2.1 Print Date 24.04.2025

Date of last issue: 27.10.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		(70 11,11)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned 919-857-5 01-2119463258-33- XXXX [corresponding group CAS 64742-48- 9]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 EUH066	>= 25 - < 40
silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis prod- ucts with silica	68909-20-6 272-697-1 01-2119379499-16- XXXX	STOT RE 2; H373 (Lungs) EUH066	>= 5 - < 10
Hydrocarbons, C12-C15, n- alkanes, isoalkanes < 2% aromat- ics	Not Assigned 920-107-4 01-2119453414-43- XXXX	Asp. Tox. 1; H304 EUH066	>= 2,5 - < 5
N,N-Dibutylaminomethyl- triethoxysilane	35501-23-6 Not Assigned 01-2120096609-40- XXXX	Skin Sens. 1B; H317	>= 2,5 - < 5
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned 918-481-9 01-2119457273-39- XXXX	Asp. Tox. 1; H304 EUH066	>= 1 - < 2,5
ethanol	64-17-5 200-578-6 01-2119457610-43-	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 1 - < 2,5
	XXXX	specific concentration limit Eye Dam. 2; H319 >= 50 %	
trimethoxyvinylsilane Contains: tetramethyl orthosilicate <= 0,2 %	2768-02-7 220-449-8 01-2119513215-52- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Sens. 1B; H317	>= 0,5 - < 1
		Acute toxicity esti- mate	
		Acute inhalation tox- icity (vapour): 16,8 mg/l	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

Revision Date: 24.04.2025

N-(3-	1760-24-3	Eye Dam. 1; H318	>= 0,5 - < 1
(trimethoxysi-	217-164-6	Skin Sens. 1B; H317	
lyl)propyl)ethylenediamine	01-2119970215-39-	STOT SE 3; H335	
Contains:	XXXX	(Respiratory system)	
N,N'-bis[3-			
(trimethoxysi-			
lyl)propyl]ethylenediamine <= 3 %			
1-(2-Aminoethyl)-2,2-dimethoxy-1-			
aza-2-silacyclopentane <= 3 %			

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Erythema Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks : sensitising effects

May cause an allergic skin reaction. May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

Revision Date: 24.04.2025

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing Water

media High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear

Revision Date: 24.04.2025 Version 2.1 Print Date 24.04.2025

Date of last issue: 27.10.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
ethanol	64-17-5	OELV - 15 min (STEL)	1.000 ppm	IE OEL

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of signifi-			
	cant uptake through the skin			
		OELV - 8 hrs	200 ppm	IE OEL
		(TWA)	260 mg/m3	
	Further information: Substances which have the capacity to pene- trate intact skin when they come in contact with it, and be ab- sorbed into the body			
ethanol	64-17-5	OELV - 15 min (STEL)	1.000 ppm	IE OEL

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

: Chemical-resistant, impervious gloves complying with an ap-Hand protection

> proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons

and protective boots are additionally recommended for mixing

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

Revision Date: 24.04.2025

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Appearance : paste
Colour : clear

Odour : mild

Melting point/ range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : 6 %(V)

per flammability limit

. 0 /o(v)

Lower explosion limit /

: 0,7 %(V)

Lower flammability limit

: ca. 40 °C

Flash point

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

Revision Date: 24.04.2025

Method: closed cup

Auto-ignition temperature : 255 °C

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 4 hPa

Density : ca. 0,95 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

Stable under recommended storage conditions.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition

products

: methanol, ethanol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity LD50 Dermal (Rabbit): 3.160 mg/kg

trimethoxyvinylsilane:

Acute oral toxicity : LD50 Oral (Rat): ca. 7.120 mg/kg

Acute inhalation toxicity : LC50: ca. 16,8 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute toxicity estimate: 16,8 mg/l Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity LD50: 3.540 mg/kg

N-(3-(trimethoxysilyl)propyl)ethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 2.995 mg/kg

Skin corrosion/irritation


Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

Revision Date: 24.04.2025

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l

aquatic invertebrates Exposure time: 48 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

Revision Date: 24.04.2025

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Revision Date: 24.04.2025 Version 2.1 Print Date 24.04.2025

Date of last issue: 27.10.2023

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1993 IMDG : UN 1993 IATA : UN 1993

14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, N.O.S.

(naphtha (petroleum))

IMDG : FLAMMABLE LIQUID, N.O.S.

(naphtha (petroleum))

IATA : Flammable liquid, n.o.s.

(naphtha (petroleum))

14.3 Transport hazard class(es)

Class Subsidiary risks

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

Revision Date: 24.04.2025

IATA (Passenger)

Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

Remarks : Not classified as supporting combustion according to the

transport regulations.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



Date of last issue: 27.10.2023

Revision Date: 24.04.2025

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Regulation (EU) No 2024/590 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Petroleum products: (a) gasolines and naphthas, (b) kerosenes

(including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards

as the products referred to in points (a) to (d)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 36,22% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 36,22% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard®-850 Clear



SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure 2006/15/EC : Europe. Indicative occupational exposure limit values

IE OEL : Ireland. List of Chemical Agents and Carcinogens with Occu-

pational Exposure Limit Values - Code of Practice, Schedule 1

and 2

2006/15/EC / TWA : Limit Value - eight hours

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period) IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference peri-

.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Ser DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation


period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic



(STEL)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sikagard®-850 Clear

Revision Date: 24.04.2025 Version 2.1 Print Date 24.04.2025

Date of last issue: 27.10.2023

PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

Skin Sens. 1 H317 Calculation method STOT SE 3 H336 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

IE / EN