

Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EVERBUILD B1 Gungrade Fire Foam

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Fire protection system

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd Sika House Ballymun Industrial Estate Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person responsible for the SDS	:	EHS@UK.Sika.com

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Effects on or via lactation	H362: May cause harm to breast-fed children.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.

EVERBUILD B1 Gungrade Fire Foam



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Extremely flammable aerosol.

Signal word

Danger

H222

1

÷

	•		
		H229	Pressurised container: May burst if heated.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H334	May cause allergy or asthma symptoms or breath- ing difficulties if inhaled.
		H335	May cause respiratory irritation.
		H351	Suspected of causing cancer.
		H362	May cause harm to breast-fed children.
		H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
		H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	:	P101	If medical advice is needed, have product container or label at hand.
		P102	Keep out of reach of children.
		Prevention	:
		P201	Obtain special instructions before use.
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P211	Do not spray on an open flame or other igni- tion source.
		P251	Do not pierce or burn, even after use.
		P260	Do not breathe dust/ fume/ gas/ mist/ va- pours/ spray.
		P263	Avoid contact during pregnancy and while nursing.
		P271	Use only outdoors or in a well-ventilated ar-

ea.

Wear protective gloves/ protective clothing/

eye protection/ face protection.

P280



Revision Date: 01.05.2024 Date of last issue: 06.10.2023

Version 1.2

P304 + P340 + F	P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical ad- vice/ attention.
Storage:	
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to tem- peratures exceeding 50 °C/ 122 °F.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

Formaldehyde, oligomeric reaction products with aniline and phosgene alkanes, C14-17, chloro

Additional Labelling

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
tris(2-chloro-1-methylethyl) phos-	13674-84-5	Acute Tox. 4; H302	>= 20 - < 25
phate	237-158-7	Aquatic Chronic 3;	
	01-2119486772-26-	H412	
	XXXX (covered by EC		
	807-935-0)		

Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2



Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 10 - < 20
Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 \longrightarrow specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5	
Flam. Gas 1A; H220	>= 10 - < 20
Lact.H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH066 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	>= 1 - < 2,5
Flam. Gas 1A; H220	>= 10 - < 20
Flam. Gas 1A; H220	>= 10 - < 20
	STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l Flam. Gas 1A; H220 Lact.H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH066 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10

For explanation of abbreviations see section 16.

Print Date 28.03.2025

Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

SECTION 4: First aid measures

4.1 Description of first aid measures General advice Move out of dangerous area. 1 Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled Move to fresh air. In case of skin contact Take off contaminated clothing and shoes immediately. ÷ Wash off with soap and plenty of water. If symptoms persist, call a physician. Immediately flush eye(s) with plenty of water. In case of eye contact Remove contact lenses. Keep eve wide open while rinsing. If eye irritation persists, consult a specialist. Do not induce vomiting without medical advice. If swallowed ٠ Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Symptoms Asthmatic appearance • Cough Respiratory disorder Allergic reactions **Excessive lachrymation** Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms. Risks irritant effects · sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause harm to breast-fed children. May cause damage to organs through prolonged or repeated exposure if inhaled.



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	Water
5.2 Special hazards arising from	the	e substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8.
		For personal protection see section 8.

EVERBUILD B1 Gungrade Fire Foam



Revision Date: 01.05.2024				
Date of last issue: 06.10.2023				

	 Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products 		
Advice on protection against fire and explosion	: Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.		
7.2 Conditions for safe storage, including any incompatibilities			

Requirements for storage areas and containers BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations. Further information on storage stability

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
	Further inform	ation: Indicative		
		OELV - 8 hrs (TWA)	1.000 ppm 1.920 mg/m3	IE OEL
Formaldehyde, oligomeric reaction products with aniline and phosgene	32055-14-4	OELV - 8 hrs (TWA)	0,02 mg/m3 (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asth-			



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

ma, rhinitis or ex	trinsic allergic alve	eolitis	
	OELV - 15 min (STEL)	0,07 mg/m3 (NCO)	IE OEL

8.2 Exposure controls

t
Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	aerosol pink
Odour	:	slight
Melting point/range / Freezing point	:	No data available

EVERBUILD B1 Gungrade Fire Foam



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	-	
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	-4 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable
Viscosity		
Viscosity, kinematic	:	No data available
Solubility(ies)		
Solubility(ies) Water solubility	:	insoluble
	:	
Water solubility Partition coefficient: n-	-	
Water solubility Partition coefficient: n- octanol/water	-	No data available
Water solubility Partition coefficient: n- octanol/water Vapour pressure	-	No data available 8300 hPa ca. 1 g/cm3



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Formaldehyde, oligomeric reaction products with aniline and phosgene:

Acute inhalation toxicity	 LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method
Skin corrosion/irritation	
Causes skin irritation.	
Components:	
alkanes, C14-17, chloro:	

: Repeated exposure may cause skin dryness or cracking.

EVERBUILD B1 Gungrade Fire Foam



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

May cause harm to breast-fed children.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

Components:

alkanes, C14-17, chloro:

M-Factor (Acute aquatic tox- : 1 icity)

M-Factor (Chronic aquatic : 10 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2



12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-		An environmental hazard cannot be excluded in the event of
Additional ecological intol-	•	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : ·

The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues.
This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number				
ADR	:	UN 1950		
IMDG	:	UN 1950		
ΙΑΤΑ	:	UN 1950		
14.2 UN proper shipping name				
ADR	:	AEROSOLS		
IMDG	:	AEROSOLS		

Print Date



Revision Date: 01.05.2024 Version 1.2 Date of last issue: 06.10.2023 ΙΑΤΑ Aerosols, flammable 14.3 Transport hazard class(es) Subsidiary risks Class ADR 2 2.1 ÷ IMDG 2.1 2 ΙΑΤΑ · 2.1 14.4 Packing group ADR Packing group ÷ Not assigned by regulation **Classification Code** ÷ 5F Labels ÷ 2.1 Tunnel restriction code (D) : IMDG Packing group : Not assigned by regulation Labels 2.1 1 EmS Code : F-D, S-U IATA (Cargo) Packing instruction (cargo : 203 aircraft) Packing instruction (LQ) 1 Y203 Packing group Not assigned by regulation 1 Labels : Flammable Gas IATA (Passenger) Packing instruction (passen-: 203 ger aircraft) Packing instruction (LQ) 1 Y203 Packing group Not assigned by regulation : Labels Flammable Gas 14.5 Environmental hazards ADR Environmentally hazardous : no IMDG Marine pollutant no IATA (Passenger) Environmentally hazardous : no IATA (Cargo) Environmentally hazardous : no 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15. ⁻	I Safety, health and environmen International Chemical Weapons Schedules of Toxic Chemicals ar		or mixture
	REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.	
	REACH - Candidate List of Subst Concern for Authorisation (Article		
	REACH - List of substances subj (Annex XIV)	ect to authorisation : Not applicable	
	Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de- : Not applicable	
	Regulation (EU) 2019/1021 on pe tants (recast)	ersistent organic pollu- : Not applicable	
	Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		
	Seveso III: Directive 2012/18/EU jor-accident hazards involving da P3a	of the European Parliament and of the Council on the co ngerous substances. FLAMMABLE AEROSOLS	ntrol of ma-
	Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 35% w/w	i
		Directive 2010/75/EU of 24 November 2010 on industria emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 35% w/w, 350 g/l VOC content excluding water	al

EVERBUILD B1 Gungrade Fire Foam



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	: Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH)
	May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

75/324/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H220 H302 H315 H317 H319 H332	:	Extremely flammable gas. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled.
H334	÷	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335 H351 H362	:	May cause respiratory irritation. Suspected of causing cancer. May cause harm to breast-fed children.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviatio	ns	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Lact.	:	Effects on or via lactation
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation



rision Date: 01.05.2024 e of last issue: 06.10.2023		Version 1.2	Print Date 28.03.2	
STOT RE		Specific target organ toxicity - repeated exp	osure	
STOT SE	:	Specific target organ toxicity - single exposu		
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first		
2000/39/20	•	list of indicative occupational exposure limit values		
IE OEL		Ireland. List of Chemical Agents and Carcino		
0	•	pational Exposure Limit Values - Code of Pr		
		and 2		
2000/39/EC / TWA	•	Limit Value - eight hours		
IE OEL / OELV - 8 hrs (TWA)	÷	Occupational exposure limit value (8-hour re	eference period)	
IE OEL / OELV - 15 min		Occupational exposure limit value (15-minute reference peri-		
(STEL)	-	od)		
ADR		European Agreement concerning the Interna	ational Carriage of	
		Dangerous Goods by Road		
CAS	:	Chemical Abstracts Service		
DNEL	:	Derived no-effect level		
EC50	:	Half maximal effective concentration		
GHS	:	Globally Harmonized System		
ΙΑΤΑ	:	International Air Transport Association		
IMDG	:	International Maritime Code for Dangerous	Goods	
LD50	:	Median lethal dosis (the amount of a materia	al, given all at	
		once, which causes the death of 50% (one h	nalf) of a group of	
		test animals)	,	
LC50	:	Median lethal concentration (concentrations		
		air that kills 50% of the test animals during t	he observation	
		period)		
MARPOL	:	International Convention for the Prevention		
		Ships, 1973 as modified by the Protocol of 1	978	
OEL	:	Occupational Exposure Limit		
PBT	:	Persistent, bioaccumulative and toxic		
PNEC	:	Predicted no effect concentration		
REACH	:	Regulation (EC) No 1907/2006 of the Europ		
		and of the Council of 18 December 2006 co		
		istration, Evaluation, Authorisation and Rest		
		cals (REACH), establishing a European Che	emicals Agency	
SVHC	:	Substances of Very High Concern		
vPvB	:	Very persistent and very bioaccumulative		

Further information

Classification of the mixtu	Classification procedure:	
Aerosol 1	H222, H229	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
Lact.	H362	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method



Revision Date: 01.05.2024 Date of last issue: 06.10.2023 Version 1.2

Aquatic Chronic 3

H412

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN