

ETAG 005

13

0836

DECLARATION OF PERFORMANCE

Sikalastic[®]-625

02 09 15 20 600 0 000016 1148

	1	
Product Type: Unique identification code of the product-type:	Sikalastic [®] -625	
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Sikalastic®-625 (Batch no. see packaging)	
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Sikalastic [®] -625 is for use as a liquid-applied roof waterproofing kit to resist the passage of water to the building's internal structure, where Essential Requirements 2 Safety in case of fire, 3 Hygiene, health and the environment and 4 Safety in use of Directive 89/106/EEC, including the aspect of durability.	
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikalastic [®] -625 Sika Limited Sika Liquid Plastics Sika House Miller Street Preston PR1 1EA United Kingdom	
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)	
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 3	
7. Notified body (hEN): In case of the declaration of performance (DoP)concerning a construction product covered by a harmonised standard:	Not Relevant (see 8)	



Roofing Declaration of Performance Edition 04.2013 Identification no. 02 09 15 20 600 0 000016 Version no. 01

8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Approval body British Board of Agrèment (no.0836) issued an ETA-13/0788 on the basis of ETAG 005-6:2000.

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
External fire performance Part 1 – 4	B _{Roof} (t1) ⁽¹⁾ B _{Roof} (t4) ⁽²⁾	ENV 1187 EN 13501-5	
Reaction to fire	Euroclass E	EN 13501-1	
Categorization by working life:	W3	According to ETAG - 005-6:2000, 4.3.3	ETAG 005-6:2000
Categorization by climatic zones:	м		
Categorization by imposed loads:	P3		
Categorization by roof slope:	S1 to S4		
Categorization by surface Temperature			
Lowest: Highest:	TL3 TH4		
Statement on dangerous substances	None contained		
Slipperiness	NPD	EN 13893	

⁽¹⁾ The tests were carried out on a non-combustible, calcium silicate board substrate. The result is applicable between pitches of 0°to 20°



⁽²⁾ The tests were carried out on a non-combustible, calcium silicate board substrate at zero pitch on a self-adhesive modified bitumen membrane over an 80mm polyurethane insulation board at zero pitch

Roofing Declaration of Performance Edition 04.2013 Identification no. 02 09 15 20 600 0 000016 Version no. 01

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

R&D Manager

Technical Manager

04, 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

Further Information

Contact: Sika Liquid Plastics

Tel: 01772 259781 Fax: 01772 255670

Email: liquidplastics@uk.sika.com

www.liquidplastics.co.uk

Legal note:


This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited (Registered Office) Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Phone +44 1707 394444 Telefax +44 1707 329129







Certificate No. FM 588020