

Version 2.3

Print Date 25.04.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikasil<sup>®</sup> SG-500 Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Catalyst for 2 Comp. sealants/adhesives.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd Sika House Ballymun Industrial Estate Dublin 11
Telephone E-mail address of person responsible for the SDS	:	+353 1862 0709 EHS@UK.Sika.com

#### **1.4 Emergency telephone number**

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikasil<sup>®</sup> SG-500 Part B



Revision Date: 25.04.2025 Date of last issue: 19.01.2024	V	ersion 2.3	Print Date 25.04.2025
Hazard pictograms :		!	
Signal word :	Danger	·	
Hazard statements :	H317 Ma H318 Ca	uses skin irritation. y cause an allergic skin reaction. uses serious eye damage. y cause respiratory irritation.	
Precautionary statements :	<b>Prevention:</b> P261 P264 P280	Avoid breathing mist or vapours Wash skin thoroughly after hand Wear protective gloves/ eye pro protection.	dling.
	Response:		
	P304 + P340 +	P312 IF INHALED: Remove pe air and keep comfortable for bre POISON CENTER/ doctor if you	eathing. Call a
	P305 + P351 +		e cautiously Remove con- to do. Con-
	P333 + P313	If skin irritation or rash occurs: 0 advice/ attention.	Get medical

#### Hazardous components which must be listed on the label:

tetraethyl silicate N-[3-(triethoxysilyl)propyl]ethylenediamine

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# Sikasil<sup>®</sup> SG-500 Part B

Revision Date: 25.04.2025 Date of last issue: 19.01.2024 Version 2.3

Print Date 25.04.2025

# SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
tetraethyl silicate	78-10-4 201-083-8 01-2119496195-28- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335	>= 20 - < 25
N-[3- (triethoxysi- lyl)propyl]ethylenediamine Contains: N,N'-bis[3- (triethoxysi- lyl)propyl]ethylenediamine >= 3 - <= 5 % N1,N1-Bis[3-(triethoxysilyl)propyl]- 1,2-ethanediamine >= 3 - <= 5 % di- aminoethylaminopropyltetraethox- ydisiloxane >= 3 - <= 5 %	5089-72-5 225-806-1 01-2120767929-30- XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 10 - < 20
trimethoxyoctylsilane Contains: methanol <= 0,2 %	3069-40-7 221-338-7 01-2119948401-42- XXXX	Skin Irrit. 2; H315	>= 5 - < 10



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikasil<sup>®</sup> SG-500 Part B



Revision Date: 25.04.2025 Date of last issue: 19.01.2024

Version 2.3

Print Date 25.04.2025

Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane	93925-42-9 300-344-4 01-2119560586-30- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Dam. 1; H318 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 Aquatic Chronic 3; H412 	>= 0,25 - < 0,3
		specific concentration limit Muta. 2; H341 >= 2 %	
		specific concentration limit STOT SE 1; H370 >= 20 %	
		specific concentration limit STOT SE 2; H371 >= 2 %	
		specific concentration limit STOT RE 1; H372 >= 20 %	
		specific concentration limit STOT RE 2; H373 >= 2 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 1.000 mg/kg	



Version 2.3

Print Date 25.04.2025

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

4.1 Description of first aid measures				
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.			
If inhaled	: Move to fresh air. Consult a physician after significant exposure.			
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>			
In case of eye contact	<ul> <li>Small amounts splashed into eyes can cause irreversible tissue damage and blindness.</li> <li>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</li> <li>Continue rinsing eyes during transport to hospital.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> </ul>			
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>			
4.2 Most important symptoms a	nd effects, both acute and delayed			
Symptoms	: Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.			
Risks	: irritant effects sensitising effects			
	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.			

# Sikasil<sup>®</sup> SG-500 Part B



Revision Date: 25.04.2025 Date of last issue: 19.01.2024		Version 2.3	Print Date 25.04.20
4.3 Indication of any immediate r	ne	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/ ide/sand/foam/alcohol resistant foam/chemical extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathi	ng apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas	e I	neasures	
6.1 Personal precautions, protec	tiv	e equipment and emergency procedures	
Personal precautions	:		
6.2 Environmental precautions		Do not flush into surface water or sanitary sew	orcyctom
Environmental precautions	•		er system.
6.3 Methods and material for con	Itai	nment and cleaning up	
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. san acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposa	-
6.4 Reference to other sections			
For personal protection see se	ecti	on 8.	
SECTION 7: Handling and sto			

Advice on safe handling: Avoid exceeding the given occupational exposure limits (see<br/>section 8).<br/>Do not get in eyes, on skin, or on clothing.

### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikasil<sup>®</sup> SG-500 Part B



Revision Date: 25.04.2025 Version 2.3 Print Date 25.04.2025 Date of last issue: 19.01.2024 For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products Advice on protection against Normal measures for preventive fire protection. 1 fire and explosion Handle in accordance with good industrial hygiene and safety Hygiene measures 2 practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage Keep container tightly closed in a dry and well-ventilated areas and containers place. Store in accordance with local regulations. Further information on stor-: No decomposition if stored and applied as directed. age stability 7.3 Specific end use(s) Specific use(s) Consult most current local Product Data Sheet prior to any use.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
tetraethyl silicate	78-10-4	TWA	5 ppm 44 mg/m3	2017/164/EU
	Further inform	ation: Indicative		
		OELV - 8 hrs (TWA)	5 ppm 44 mg/m3	IE OEL
Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane	93925-42-9	OELV - 8 hrs (TWA)	0,1 mg/m3 (Tin)	IE OEL
		OELV - 15 min (STEL)	0,2 mg/m3 (Tin)	IE OEL

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikasil® SG-500 Part B



Revision Date: 25.04.2025 Date of last issue: 19.01.2024 Version 2.3

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
ethanol	64-17-5	OELV - 15 min (STEL)	1.000 ppm	IE OEL
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of signifi-			
	cant uptake through the skin			
		OELV - 8 hrs (TWA)	200 ppm 260 mg/m3	IE OEL
	Further information: Substances which have the capacity to pene- trate intact skin when they come in contact with it, and be ab- sorbed into the body			

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth-



Revision Date: 25.04.2025 Date of last issue: 19.01.2024	Version 2.3	Print Date 25.04.2025
	ods for determining inhalation exposure ticular to the mixing / stirring area. In ca to keep the concentrations under the o limits then respiration protection measu	ase this is not sufficent ccupational exposure
Environmental exposure	controls	
General advice	: Do not flush into surface water or sanit	ary sewer system.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Information on basic physical	an	• •
Physical state Appearance	÷	solid
Colour	:	paste black
Colodi	•	DIGCK
Odour	:	very faint
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	ca. 8 - 10 Concentration: 100 %

#### Viscosity

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikasil<sup>®</sup> SG-500 Part B



Revision Date: 25.04.2025 Date of last issue: 19.01.2024	Version 2.3	Print Date 25.04.2025
Viscosity, dynamic	: ca. 250.000 mPa.s (20 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
<b>Solubility(ies)</b> Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,01 hPa	
Density	: ca. 1,07 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
<b>9.2 Other information</b> Flammable solids Burning rate	: > 120 s Method: UN-Test N1	

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

## 10.5 Incompatible materials

Materials to avoid	: No data available



Version 2.3

Print Date 25.04.2025

#### 10.6 Hazardous decomposition products

Hazardous decomposition : ethanol, methanol products

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Components:

#### Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane:

Acute oral	toxicity
------------	----------

: LD50 Oral (Rat): 1.000 mg/kg

Acute toxicity estimate: 1.000 mg/kg Method: Calculation method

#### Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified due to lack of data.

#### STOT - single exposure

May cause respiratory irritation.

#### STOT - repeated exposure

Not classified due to lack of data.

## Aspiration toxicity

Not classified due to lack of data.



Version 2.3

Print Date 25.04.2025

#### 11.2 Information on other hazards

#### Endocrine disrupting properties

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

#### N-[3-(triethoxysilyl)propyl]ethylenediamine:

Toxicity to fish (Chronic tox-	:	LC50: 597 mg/l
icity)		Exposure time: 96 h
		Species: Danio rerio (zebra fish)

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### **12.6 Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# Sikasil<sup>®</sup> SG-500 Part B



Revision Date: 25.04.2025Version 2.3Print Date 25.04.2025Date of last issue: 19.01.2024

#### 12.7 Other adverse effects

#### Product:

Additional ecological infor- : There is no data available for this product. mation

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.2	UN proper shipping name		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.3	Transport hazard class(es)		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikasil<sup>®</sup> SG-500 Part B

Revision Date: 25.04.2025



Print Date 25.04.2025

Date of last issue: 19.01.2024		
ΙΑΤΑ	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA (Passenger)	: Not regulated as a dangerous good	
14.5 Environmental hazards		
Not regulated as a danger	bus good	
<b>14.6 Special precautions for</b> Not applicable	ıser	
14.7 Maritime transport in bu	k according to IMO instruments	
Not applicable for product	as supplied.	
	onmental regulations/legislation specific for apons Convention (CWC) : Not applic	
REACH Information:	All substances contained in our Prode - registered by our upstream supplier - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.	s, and/or
	ain dangerous substances, lowing en	s of restriction for the fol- tries should be considered: n list 3
	Number o	n list 75
REACH - Candidate List c Concern for Authorisation	, ,	ne components are listed ).
REACH - List of substance	es subject to authorisation : Not applic	able

Version 2.3

(Annex XIV)

Regulation (EU) No 2024/590 on substances that de- : Not applicable plete the ozone layer

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikasil<sup>®</sup> SG-500 Part B



Revision Date: 25.04.2025 Date of last issue: 19.01.2024	Version 2.3	Print Date 25.04.2025		
Regulation (EU) 2019/1021 on petants (recast)	ersistent organic pollu- : Not applicable			
Regulation (EU) No 649/2012 of the European Parlia- : Not applicable ment and the Council concerning the export and import of dangerous chemicals				
Seveso III: Directive 2012/18/EU jor-accident hazards involving da	of the European Parliament and of the Counc ngerous substances. Not applicable	il on the control of ma-		
Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: < 0,01% w/w no VOC duties			
	Directive 2010/75/EU of 24 November 2010 livestock rearing emissions (integrated pollu and control) Volatile organic compounds (VOC) content:	tion prevention		

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	<ul> <li>Environmental Protection Act 1990 &amp; Subsidiary Regulations</li></ul>
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH) <li>May be subject to the Control of Major Accident Hazards</li> <li>Bagulations (COMAH) and amondmenta</li>
	Regulations (COMAH), and amendments.

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

## **Full text of H-Statements**

H315: Causes skin irritation.H317: May cause an allergic skin reaction.H318: Causes serious eye damage.H319: Causes serious eye irritation.H332: Harmful if inhaled.H335: May cause respiratory irritation.
---

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikasil<sup>®</sup> SG-500 Part B



Revision Date: 25.04.2025 Version 2.3 Print Date 25.04.2025 Date of last issue: 19.01.2024 H341 Suspected of causing genetic defects. : H360FD May damage fertility. May damage the unborn child. Causes damage to organs. H370 Causes damage to organs through prolonged or repeated H372 exposure if swallowed. H412 • Harmful to aquatic life with long lasting effects. Full text of other abbreviations Acute Tox. Acute toxicity Aquatic Chronic Long-term (chronic) aquatic hazard Eve Dam. Serious eye damage Eye Irrit. Eye irritation Flam. Liq. Flammable liquids Germ cell mutagenicity Muta. : Reproductive toxicity Repr. : Skin irritation Skin Irrit. Skin Sens. Skin sensitisation STOT RE Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure STOT SE : Europe. Indicative occupational exposure limit values 2006/15/EC : Europe. Commission Directive 2017/164/EU establishing a 2017/164/EU fourth list of indicative occupational exposure limit values IE OEL Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2 2006/15/EC / TWA Limit Value - eight hours Limit Value - eight hours 2017/164/EU / TWA Occupational exposure limit value (8-hour reference period) IE OEL / OELV - 8 hrs (TWA) : IE OEL / OELV - 15 min Occupational exposure limit value (15-minute reference peri-(STEL) od) ADR European Agreement concerning the International Carriage of : Dangerous Goods by Road CAS **Chemical Abstracts Service** DNEL Derived no-effect level Half maximal effective concentration **EC50** GHS **Globally Harmonized System** International Air Transport Association IATA International Maritime Code for Dangerous Goods IMDG LD50 Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) LC50 Median lethal concentration (concentrations of the chemical in : air that kills 50% of the test animals during the observation period) MARPOL International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 OEL Occupational Exposure Limit : Persistent, bioaccumulative and toxic PBT Predicted no effect concentration PNEC REACH Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikasil® SG-500 Part B



Revision Date: 25.04.2025
Date of last issue: 19.01.2024

Version 2.3

Print Date 25.04.2025

SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

#### Further information

cture:	Classification procedure:
H315	Calculation method
H318	Calculation method
H317	Calculation method
H335	Calculation method
	H318 H317

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN