

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Bituminous coating

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Ireland Ltd  
Sika House  
Ballymun Industrial Estate  
Dublin 11  
Telephone : +353 1862 0709  
E-mail address of person : EHS@UK.Sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166  
(available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|  |   |
|--|---|
| Flammable liquids, Category 3  | H226: Flammable liquid and vapour.                                    |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.                              |
| Specific target organ toxicity - repeated exposure, Category 1                       | H372: Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard, Category 1  | H304: May be fatal if swallowed and enters airways.                   |
| Long-term (chronic) aquatic hazard, Category 2                                       | H411: Toxic to aquatic life with long lasting effects.                |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements :  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name   | CAS-No.<br>EC-No.<br>Registration number   | Classification   | Concentration<br>(% w/w) |
|---|--|--|--------------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | Not Assigned<br>919-446-0<br>265-185-4<br>01-2119458049-33-XXXX [corresponding group CAS 64742-82-1] | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT RE 1; H372<br>(Central nervous system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2; H411<br>EUH066 | $\geq 25$ - $< 50$       |
| Substances with a workplace exposure limit :                            |  |  |                          |
| Asphalt   | 8052-42-4<br>232-490-9<br>01-2119480172-44-XXXX  |  | $\geq 50$ - $\leq 100$   |

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.  
Erythema  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.

Risks : Risk of serious damage to the lungs (by aspiration).  
  
May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.  
Causes damage to organs through prolonged or repeated exposure.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components | CAS-No.   | Value type (Form of exposure)                 | Control parameters *  | Basis * |
|------------|-----------|---|-----------------------|---------|
| Asphalt    | 8052-42-4 | OELV - 8 hrs (TWA) (fume, inhalable fraction) | 0,5 mg/m <sup>3</sup> | IE OEL  |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

ing limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : black

Odour : characteristic

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : Upper flammability limit  
per flammability limit 8 %(V)

Lower explosion limit / Lower flammability limit : Lower flammability limit  
0,6 %(V)

Flash point : 38 °C  
Method: closed cup

Auto-ignition temperature : 230 °C

Decomposition temperature : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

pH : Not applicable

### Viscosity

Viscosity, kinematic : > 7 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 3,9997 hPa

Density : 0,91 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

Country IE 000000602420



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

:  
No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### **Acute toxicity**

Not classified based on available information.

##### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

##### **Components:**

##### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Assessment : Repeated exposure may cause skin dryness or cracking.

Result : Repeated exposure may cause skin dryness or cracking.

##### **Serious eye damage/eye irritation**

Not classified based on available information.

##### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

Not classified based on available information.

##### **Respiratory sensitisation**

Not classified based on available information.

##### **Germ cell mutagenicity**

Not classified based on available information.

##### **Carcinogenicity**

Not classified based on available information.

##### **Reproductive toxicity**

Not classified based on available information.

##### **STOT - single exposure**

May cause drowsiness or dizziness.

##### **STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

##### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

##### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

##### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

#### 14.2 UN proper shipping name

ADR : PAINT

IMDG : PAINT  
(naphtha (petroleum))

IATA : Paint

#### 14.3 Transport hazard class(es)

|      | Class | Subsidiary risks |
|------|-------|------------------|
| ADR  | : 3   |                  |
| IMDG | : 3   |                  |
| IATA | : 3   |                  |

#### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

#### 14.5 Environmental hazards

ADR

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

### IATA (Passenger)

Environmentally hazardous : yes

### IATA (Cargo)

Environmentally hazardous : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c

FLAMMABLE LIQUIDS

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

|                            |  |
|----------------------------|--|
| E2                         | ENVIRONMENTAL HAZARDS  |
| 34                         | Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d) |
| Volatile organic compounds | : Law on the incentive tax for volatile organic compounds (VOCV)<br>Volatile organic compounds (VOC) content: 40% w/w<br><br>Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)<br>Volatile organic compounds (VOC) content:<br>40% w/w, 364 g/l<br>VOC content excluding water                                    |

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

|  |  |
|--|--|
| Health, safety and environmental regulation/legislation specific for the substance or mixture: | : Environmental Protection Act 1990 & Subsidiary Regulations<br>Health and Safety at Work Act 1974 & Subsidiary Regulations<br>Control of Substances Hazardous to Health Regulations (COSHH)<br>May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments. |
|--|--|

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

|      |  |
|------|--|
| H226 | : Flammable liquid and vapour.   |
| H304 | : May be fatal if swallowed and enters airways.                              |
| H336 | : May cause drowsiness or dizziness.   |
| H372 | : Causes damage to organs through prolonged or repeated exposure if inhaled. |
| H411 | : Toxic to aquatic life with long lasting effects.                           |

### Full text of other abbreviations

|                 |   |
|-----------------|---|
| Aquatic Chronic | : Long-term (chronic) aquatic hazard                          |
| Asp. Tox.       | : Aspiration hazard   |
| Flam. Liq.      | : Flammable liquids   |
| STOT RE         | : Specific target organ toxicity - repeated exposure          |
| STOT SE         | : Specific target organ toxicity - single exposure            |
| IE OEL          | : Ireland. List of Chemical Agents and Carcinogens with Occu- |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

|                             |  |
|-----------------------------|--|
|                             | patational Exposure Limit Values - Code of Practice, Schedule 1 and 2  |
| IE OEL / OELV - 8 hrs (TWA) | : Occupational exposure limit value (8-hour reference period)  |
| ADR                         | : European Agreement concerning the International Carriage of Dangerous Goods by Road  |
| CAS                         | : Chemical Abstracts Service   |
| DNEL                        | : Derived no-effect level  |
| EC50                        | : Half maximal effective concentration   |
| GHS                         | : Globally Harmonized System   |
| IATA                        | : International Air Transport Association  |
| IMDG                        | : International Maritime Code for Dangerous Goods  |
| LD50                        | : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)   |
| LC50                        | : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)   |
| MARPOL                      | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL                         | : Occupational Exposure Limit  |
| PBT                         | : Persistent, bioaccumulative and toxic  |
| PNEC                        | : Predicted no effect concentration  |
| REACH                       | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC                        | : Substances of Very High Concern  |
| vPvB                        | : Very persistent and very bioaccumulative   |

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| STOT SE 3         | H336 |
| STOT RE 1         | H372 |
| Asp. Tox. 1       | H304 |
| Aquatic Chronic 2 | H411 |

#### Classification procedure:

|                        |
|------------------------|
| On basis of test data. |
| Calculation method     |
| Calculation method     |
| On basis of test data. |
| Calculation method     |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD BLACK JACK 901 BLACK BITUMEN PAINT



Revision Date: 26.04.2024

Version 2.1

Print Date 28.03.2025

Date of last issue: 07.02.2023

---