according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Revision Date: 08.01.2025 Version 3.0 Print Date 28.03.2025

Date of last issue: 30.04.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name SikaGard®-6220

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika Ireland Ltd

Sika House

Ballymun Industrial Estate

Dublin 11

+353 1862 0709 Telephone E-mail address of person EHS@UK.Sika.com

responsible for the SDS

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166

(available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

Hazard pictograms

Revision Date: 08.01.2025





Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dryness

or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P261 Avoid breathing mist or vapours. P273 Avoid release to the environment.

Response:

P370 + P378

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

### Hazardous components which must be listed on the label:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned 919-857-5 01-2119463258-33- XXXX [corresponding group CAS 64742-48- 9]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 EUH066	>= 25 - < 40
Aromatic hydrocarbons, C9; Al- kylbenzenes; C9-aromatics	128601-23-0 918-668-5 01-2119455851-35- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 5 - < 10
Sulfonic acids, petroleum, sodium salts	68608-26-4 271-781-5 01-2119527859-22- XXXX	Eye Irrit. 2; H319	>= 5 - < 10
ethylene glycol monobutyl ether	111-76-2 203-905-0 01-2119475108-36- XXXX	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate	>= 0,5 - < 1
		Acute oral toxicity: 1.200 mg/kg Acute inhalation tox- icity (vapour): 3 mg/l	

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Revision Date: 08.01.2025 Version 3.0 Print Date 28.03.2025

Date of last issue: 30.04.2024

Consult a physician after significant exposure.

Take off contaminated clothing and shoes immediately. In case of skin contact

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** Erythema

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks No known significant effects or hazards.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing Water

media High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

Do not use a solid water stream as it may scatter and spread

fighting

fire.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

Country IE 10000001474

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

Revision Date: 08.01.2025

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

> Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

**Environmental precautions** Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against Use explosion-proof equipment. Keep away from heat/ sparks/

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Revision Date: 08.01.2025 Version 3.0 Print Date 28.03.2025

Date of last issue: 30.04.2024

fire and explosion open flames/ hot surfaces. No smoking. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
ethylene glycol monobutyl ether	111-76-2	TWA	20 ppm 98 mg/m3	2000/39/EC	
	Further information: Identifies the possibility of significant uptake				
	through the skin, Indicative				
		STEL	50 ppm 246 mg/m3	2000/39/EC	
		OELV - 8 hrs (TWA)	20 ppm 98 mg/m3	IE OEL	
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be ab-				
	sorbed into the body				
		OELV - 15 min (STEL)	50 ppm 246 mg/m3	IE OEL	

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid Colour : various

Odour : solvent-like

Melting point/ range / Freez-

ing point

: No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

Revision Date: 08.01.2025

Boiling point/boiling range : ca. 165 - 181 °C

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : Upper flammability limit

per flammability limit 10,0 %(V)

Lower explosion limit / : Lower flammability limit

Lower flammability limit 0,6 %(V)

Flash point : ca. 38 °C

Method: closed cup

Auto-ignition temperature : 255 °C

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-polar/aprotic

**Viscosity** 

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : ca. 1 hPa (20 °C)

Density : ca. 0,87 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

Revision Date: 08.01.2025

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

## 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified due to lack of data.

### Components:

## Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3.160 mg/kg

#### ethylene glycol monobutyl ether:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Revision Date: 08.01.2025 Version 3.0 Print Date 28.03.2025

Date of last issue: 30.04.2024

LD50 Oral: 1.200 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Test atmosphere: vapour

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Not classified due to lack of data.

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

### Respiratory sensitisation

Not classified due to lack of data.

## Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

#### STOT - single exposure

May cause drowsiness or dizziness.

#### STOT - repeated exposure

Not classified due to lack of data.

### **Aspiration toxicity**

Not classified due to lack of data.

### 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Revision Date: 08.01.2025 Date of last issue: 30.04.2024 Version 3.0 Print Date 28.03.2025

## **SECTION 12: Ecological information**

### 12.1 Toxicity

### Components:

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to daphnia and other aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

Revision Date: 08.01.2025

This material and its container must be disposed of in a safe way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR : UN 1139 IMDG : UN 1139 IATA : UN 1139

### 14.2 UN proper shipping name

ADR : COATING SOLUTION : COATING SOLUTION

IATA : Coating solution

### 14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 3

 IMDG
 : 3

 IATA
 : 3

#### 14.4 Packing group

#### **ADR**

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

Remarks : Transport according to chapter 3.4 (LQ) possible

### **IMDG**

Packing group : III
Labels : 3
EmS Code : F-E, S-E
Remarks : None.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

Revision Date: 08.01.2025

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/or
exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Date of last issue: 30.04.2024

Number on list 40: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cy-

clics, <2% aromatics

Number on list 75:

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 44,5% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 44,5% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaGard®-6220



Revision Date: 08.01.2025 Version 3.0 Print Date 28.03.2025

Date of last issue: 30.04.2024

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Irrit. : Eye irritation Flam. Liq. : Flammable liquids Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

IE OEL : Ireland. List of Chemical Agents and Carcinogens with Occu-

pational Exposure Limit Values - Code of Practice, Schedule 1

and 2

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference peri-

(STEL) o

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaGard®-6220



Revision Date: 08.01.2025 Version 3.0 Print Date 28.03.2025

Date of last issue: 30.04.2024

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

### Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

STOT SE 3 H336 Calculation method Aquatic Chronic 3 H412 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

IE / EN