

Revision Date: 24.04.2025 Date of last issue: 28.11.2023 Version 4.0

Print Date 24.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®]-262 AS N Thixo Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd
		Sika House
		Ballymun Industrial Estate
		Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person	:	EHS@UK.Sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)Skin irritation, Category 2H315: Causes skin irritation.Eye irritation, Category 2H319: Causes serious eye irritation.Skin sensitisation, Category 1H317: May cause an allergic skin reaction.Long-term (chronic) aquatic hazard, Cat-H411: Toxic to aquatic life with long lasting effects.

Long-term (chronic) aquatic hazard, Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

tion (EU) 2020/878

Sikafloor[®]-262 AS N Thixo Part A



Revision Date: 24.04.2025 Version 4.0 Print Date 24.04.2025 Date of last issue: 28.11.2023 Hazard pictograms Signal word Warning 1 Causes skin irritation. Hazard statements H315 May cause an allergic skin reaction. H317 H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. Prevention: Precautionary statements • P261 Avoid breathing mist or vapours. Wash skin thoroughly after handling. P264 Avoid release to the environment. P273 Wear protective gloves/ eye protection/ face P280 protection. Response: P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P391 Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane Reaction mass of isomers of epoxy resin BFDGE p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 24.04.2025 Date of last issue: 28.11.2023 Version 4.0

Print Date 24.04.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)	
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319	>= 20 - < 25	
		>= 5 % specific concentration limit Skin Irrit. 2; H315 >= 5 %		
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 5 - < 10	
p-tert-butylphenyl 1-(2,3- epoxy)propyl ether	3101-60-8 221-453-2 01-2119959496-20- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 5 - < 10	
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti- mate Acute oral toxicity: 1.200 mg/kg	>= 1 - < 2,5	
Substances with a workplace expo	osure limit :	1.200 mg/kg		
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 2,5 - < 5	

For explanation of abbreviations see section 16.



Sikafloor®-262 AS N Thixo Part A

Revision Date: 24.04.2025 Date of last issue: 28.11.2023 Version 4.0

Print Date 24.04.2025

SECTION 4: First aid measures

4.1 Description of first aid measures General advice Move out of dangerous area. : Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled : Move to fresh air. Consult a physician after significant exposure. In case of skin contact Take off contaminated clothing and shoes immediately. 2 Wash off with soap and plenty of water. If symptoms persist, call a physician. Immediately flush eye(s) with plenty of water. In case of eye contact Remove contact lenses. Keep eye wide open while rinsing. If eve irritation persists, consult a specialist. If swallowed Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed **Symptoms** : Allergic reactions **Excessive lachrymation** Ervthema Dermatitis See Section 11 for more detailed information on health effects and symptoms. Risks irritant effects • sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.	
			4 / 4

Jika®

Sikafloor[®]-262 AS N Thixo Part A

Revision Date: 24.04.2025 Date of last issue: 28.11.2023		Version 4.0	Print Date 24.04.2025
5.2 Special hazards arising from			
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter a courses.	drains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	٦
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breath	ing apparatus.
Further information	:	Collect contaminated fire extinguishing water s must not be discharged into drains. Fire residues and contaminated fire extinguish be disposed of in accordance with local regula	ning water must

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for co	ontai	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections		

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should
	ma, anorgios, onionio or recurrent respiratory disease should

Sikafloor[®]-262 AS N Thixo Part A



Revision Date: 24.04.2025 Date of last issue: 28.11.2023	Version 4.0	Print Date 24.04.2025
	not be employed in any process in which this m used. Smoking, eating and drinking should be prohibi plication area. Follow standard hygiene measures when handl products	ted in the ap-
Advice on protection against : fire and explosion	Normal measures for preventive fire protection.	
Hygiene measures :	Handle in accordance with good industrial hygic practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the e	using do not
7.2 Conditions for safe storage, inc	luding any incompatibilities	
Requirements for storage : areas and containers	Keep container tightly closed in a dry and well- place. Containers which are opened must be ca sealed and kept upright to prevent leakage. Sto ance with local regulations.	arefully re-
Further information on stor- : age stability	No decomposition if stored and applied as direc	sted.
7.3 Specific end use(s) Specific use(s) :	Consult most current local Product Data Sheet use.	prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	OELV - 8 hrs (TWA) (Respira- ble dust)	4 mg/m3	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment



Revision Date: 24.04.2025 Date of last issue: 28.11.2023	Version 4.0	Print Date 24.04.2025
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water	
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.	
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.	

Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid various
Odour	:	epoxy-like
Melting point/ range / Freez- ing point	:	No data available

Sikafloor[®]-262 AS N Thixo Part A



Revision Date: 24.04.2025 Date of last issue: 28.11.2023		Version 4.0	Print Date 24.04.2025
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	plosive limits	
Upper explosion limit / Upper flammability limit	-		
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	ca. 96 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
		No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, dynamic	:	ca. 5.300 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,5 g/cm3 (20 °C)	
Relative vapour density	:	No data available	



Print Date 24.04.2025

Sikafloor[®]-262 AS N Thixo Part A

Revision Date: 24.04.2025

Date of last issue: 28.11.2023		
Particle characteristics	: No data available	
9.2 Other information		
No data available		
SECTION 10: Stability and	reactivity	
10.1 Reactivity		
No dangerous reaction kno	wn under conditions of normal use.	
10.2 Chemical stability		
The product is chemically s	table.	
10.3 Possibility of hazardous	reactions	
Hazardous reactions	: Stable under recommended storage con	ditions.
10.4 Conditions to avoid		
Conditions to avoid	: No data available	
10.5 Incompatible materials		

Version 4.0

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicityNot classified due to lack of data.Components:bis-[4-(2,3-epoxipropoxi)phenyl]propane:Acute oral toxicity: LD50 Oral (Rat): > 5.000 mg/kgAcute dermal toxicity: LD50 Dermal (Rabbit): > 5.000 mg/kgp-tert-butylphenyl 1-(2,3-epoxy)propyl ether:Acute oral toxicity: LD50 Oral (Rat): > 5.000 mg/kgAcute oral toxicity: LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity: LC50 (Rat): 3.466 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-262 AS N Thixo Part A



evision Date: 24.04.2025 ate of last issue: 28.11.2023		Version 4.0	Print Date 24.04.202
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 6.000 mg/kg	
benzyl alcohol:			
Acute oral toxicity	:	Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according No. 1272/2008	g to Regulation (EC)
		LD50 Oral (Rat): 1.200 mg/kg	
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Skin corrosion/irritation Causes skin irritation.			
Serious eye damage/eye in Causes serious eye irritation		on	
Respiratory or skin sensiti	satio	n	
Skin sensitisation May cause an allergic skin re	acti	on.	
Respiratory sensitisation Not classified due to lack of c	data		
Germ cell mutagenicity Not classified due to lack of o	data.		
Carcinogenicity Not classified due to lack of c	data.		
Reproductive toxicity Not classified due to lack of o	data.		
STOT - single exposure Not classified due to lack of o	data.		
STOT - repeated exposure Not classified due to lack of c	data.		
Aspiration toxicity Not classified due to lack of o	data.		
1.2 Information on other hazar			
Endocrine disrupting prop	ertie	S	
Product:			
Assessment	:	The substance/mixture does not contain ered to have endocrine disrupting proper	



Revision Date: 24.04.2025 Date of last issue: 28.11.2023 Version 4.0

Print Date 24.04.2025

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h

Reaction mass of isomers of epoxy resin BFDGE:

Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (algae): 1,8 mg/l Exposure time: 72 h

benzyl alcohol:

Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h

Toxicity to daphnia and other:EC50 (Daphnia magna (Water flea)): > 100 mg/laquatic invertebratesExposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

Sikafloor[®]-262 AS N Thixo Part A



Revision Date: 24.04.2025 Date of last issue: 28.11.2023	Version 4.0	Print Date 24.04.2025
	0.1% or higher	
12.6 Endocrine disrupting prope	rties	
Product:		
Assessment	: The substance/mixture does not con ered to have endocrine disrupting p REACH Article 57(f) or Commission (EU) 2017/2100 or Commission Reg levels of 0.1% or higher.	roperties according to Delegated regulation
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	: An environmental hazard cannot be unprofessional handling or disposal Toxic to aquatic life with long lasting	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues.
	This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	UN 3082
IMDG	:	UN 3082
ΙΑΤΑ	:	UN 3082
14.2 UN proper shipping name		
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
O		40/47

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-262 AS N Thixo Part A



Revision Date: 24.04.2025 Date of last issue: 28.11.2023		Version 4.0	Print Date 24.04.2025
		(epoxy resin)	
IMDG	:	ENVIRONMENTALLY HAZARDOUS S N.O.S. (epoxy resin)	SUBSTANCE, LIQUID,
ΙΑΤΑ	:	Environmentally hazardous substance (epoxy resin)	, liquid, n.o.s.
14.3 Transport hazard class(es)			
		Class Subsidiary risks	;
ADR	:	9	
IMDG	:	9	
ΙΑΤΑ	:	9	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III M6 90 9 (-)	
IMDG Packing group Labels EmS Code	:	III 9 F-A, S-F	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	yes	
IMDG Marine pollutant	:	yes	
IATA (Passenger) Environmentally hazardous	:	yes	
IATA (Cargo) Environmentally hazardous	:	yes	



Revision Date: 24.04.2025 Date of last issue: 28.11.2023 Version 4.0

Print Date 24.04.2025

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products are
	 registered by our upstream suppliers, and/or
	 registered by us, and/or

- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 75
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
Regulation (EU) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable

Sikafloor®-262 AS N Thixo Part A

_



Revision Date: 24.04.2025	Version 4.0	Print Date 24.04.2025
Date of last issue: 28.11.2023		

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS			
Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 3,16% w/w		
	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3,16% w/w		
If other regulatory information applies that is not already provided elsewhere in the Safety Data			

Sheet, then it is described in this subsection.

Health, safety and environ-	: Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH)
	May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 H315 H317 H319 H411	-	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.	
Full text of other abbreviations			
Acute Tox. Aquatic Chronic Eye Irrit. Skin Irrit. Skin Sens. IE OEL	:	Acute toxicity Long-term (chronic) aquatic hazard Eye irritation Skin irritation Skin sensitisation Ireland. List of Chemical Agents and Carcinogens with Occu-	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-262 AS N Thixo Part A



Revision Date: 24.04.2025 Date of last issue: 28.11.2023		Version 4.0	Print Date 24.04.2025
		pational Exposure Limit Values - Code of Practice and 2	e, Schedule 1
IE OEL / OELV - 8 hrs (TWA)		Occupational exposure limit value (8-hour referen	ace period)
	:		
ABR	•		
CAS			
	÷		
EC50	÷	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
IATA	:	International Air Transport Association	
IMDG	:	International Maritime Code for Dangerous Good	S
LD50	:	Median lethal dosis (the amount of a material, giv	en all at
			of a group of
		/	
LC50	:		
		-	servation
MARDOL			llution from
MARPOL	•		
OFI			
-	:	• •	
	:	,	
	÷		Parliament
	•		
		istration, Evaluation, Authorisation and Restriction	
		cals (REACH), establishing a European Chemica	
SVHC	:	Substances of Very High Concern	-
vPvB	:	Very persistent and very bioaccumulative	
GHS IATA IMDG LD50 LC50 MARPOL OEL PBT PNEC REACH SVHC		Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Good Median lethal dosis (the amount of a material, giv once, which causes the death of 50% (one half) of test animals) Median lethal concentration (concentrations of the air that kills 50% of the test animals during the ob period) International Convention for the Prevention of Pol Ships, 1973 as modified by the Protocol of 1978 Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European F and of the Council of 18 December 2006 concern istration, Evaluation, Authorisation and Restriction cals (REACH), establishing a European Chemical Substances of Very High Concern	s ven all at of a group of e chemical in oservation Ilution from Parliament ing the Reg- n of Chemi-

Further information

Classification of the mixture:		Classification procedure:
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN



Revision Date: 24.04.2025 Date of last issue: 28.11.2023 Version 4.0

Print Date 24.04.2025