

PRODUCT DATA SHEET

EVERBUILD® FLOOR PAINT

HEAVY DUTY, POLYURETHANE BASED FLOOR PAINT

PRODUCT DESCRIPTION

EVERBUILD® FLOOR PAINT is a solvent-based polyurethane floor paint designed to provide a clean hard wearing finish to concrete, stone and wooden floors subject to light to medium traffic. Ideal for use on garage floors, workshops, storerooms, walkways etc. EVERBUILD® FLOOR PAINT gives enhanced durability, abrasion resistance and a good resistance to dilute acids/alkalis and oils.

USES

Concrete, stone and wooden floors in:

- Garages
- Workshops
- Storerooms
- Cloakrooms and many more.

PRODUCT INFORMATION

Chemical Base	Polyurethane
Packaging	5ltr tins
Appearance / Colour	Grey, Red
Shelf Life	24 months from date of manufacture when stored correctly in unopened container.
Storage Conditions	Store in cool, dry conditions, between 5 and 25°C. PROTECT FROM FROST.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry (to touch) and free from grease and other contaminants. Remove all loose and flaking material with a scraper and a stiff brush back to a sound surface. Remove all organic growth with EVERBUILD PATIO WIZARD. Chemically or mech-

CHARACTERISTICS / ADVANTAGES

- Hard wearing polyurethane formula.
 - Low viscosity for easy application over large areas.
 - One component solvent based system.
- | | |
|--------------------------|---------------|
| MFFT | >5°C |
| Film Thickness (dry) | 25 - 40 µm |
| Dry Time (touch dry) | 2 - 4 hours |
| Dry Time (between coats) | 16 - 24 hours |

anically hardened floor may need abrasion prior to use. If in doubt test a small area prior to full application.

APPLICATION

Concrete must be a minimum of 6 months old before paint can be applied. Priming is not normally required, however the first coat on concrete or porous surfaces should first be thinned with up to 10% white spirit and

allowed to dry. EVERBUILD® FLOOR PAINT is touch dry in 2-4 hours depending on ambient temperatures.

NOTE low temperatures can significantly extend drying time. Apply using a brush or roller to give an even coating. 2 coats are normally required allowing 16-24 hours between coats.

CLEANING OF TOOLS

Clean tools and brushes with white spirits/turps subs immediately after use. Cured product can only be removed mechanically.

LIMITATIONS

- Do not use on concrete floors with a moisture level of above 18%, which do not have a waterproof membrane or concrete floors containing a dust suppressing additive.
- New concrete must be a minimum of 6 months old before painting.
- Suitable for light to medium traffic only, for areas subject to heavy traffic or constant use, an epoxy-based product is recommended.
- Do not use on bitumen or asphalt.
- Mechanically or chemically hardened floors may need abrasion prior to application.
- As the company cannot be aware of all applications and materials the product can be used on, it is the users responsibility to determine suitability for use. If in doubt contact technical services for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling.

Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
EVERBUILD® FLOOR PAINT
June 2019, Version 01.01
020813020010000016

EVERBUILDFLOORPAINT-en-IE-(06-2019)-1-1.pdf