Sika[®] Concrete Primer Part A



Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0

Print Date 13.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] Concrete Primer Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Primer, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd
		Sika House
		Ballymun Industrial Estate
		Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person	:	EHS@UK.Sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Concrete Primer Part A



 Revision Date: 13.05.2025
 Version 3.0
 Print Date 13.05.2025

 Date of last issue: 22.04.2024
 H335: May cause respiratory irritation.

 Specific target organ toxicity - single exposure, Category 3, Respiratory system
 H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Labelling (REGULATION (EC)	No 1272/2008)	
Hazard pictograms :		
Signal word :	Danger	
Hazard statements :	H315 Ca H317 Ma H319 Ca H334 Ma ing H335 Ma H336 Ma	Immable liquid and vapour. uses skin irritation. by cause an allergic skin reaction. uses serious eye irritation. by cause allergy or asthma symptoms or breath- difficulties if inhaled. by cause respiratory irritation. by cause drowsiness or dizziness. spected of causing cancer.
Precautionary statements :	Prevention:	
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P261 P280	Avoid breathing mist or vapours. Wear protective gloves/ protective clothing/ eye protection/ face protection.
	Response:	
	P304 + P340 +	P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
	P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

2-methoxy-1-methylethyl acetate 4,4'-methylenediphenyl diisocyanate o-(p-isocyanatobenzyl)phenyl isocyanate Diphenylmethanediisocyanate, isomeres and homologues 2,2'-methylenediphenyl diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."



Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0

Print Date 13.05.2025

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226	>= 25 - < 40
Contains:	203-603-9	STOT SE 3; H336	
2-methoxypropyl acetate <= 1 %	01-2119475791-29-		
	XXXX		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0



Print Date 13.05.2025

te of last issue: 22.04.2024			
4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 %	>= 5 - < 10
		specific concentration limit STOT SE 3; H335 >= 5 % specific concentration limit Skin Irrit. 2; H315	
		>= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti-	
		mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0



Print Date 13.05.2025

of last issue: 22.04.2024			
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1 227-534-9 01-2119480143-45- XXXX	Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H317 Carc. 2; H351 STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 %	>= 5 - < 10
		specific concentration limit STOT SE 3; H335 >= 5 %	
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
		specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	
propyl acetate	109-60-4 203-686-1 01-2119484620-39- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - < 10

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0



Print Date 13.05.2025

te of last issue: 22.04.2024			
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 % specific concentration limit Skin Irrit. 2; H315 >= 5 % specific concentration limit StoT SE 3; H335 >= 5 %	>= 1 - < 2,5

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0

Print Date 13.05.2025

2,2'-methylenediphenyl diisocya- nate	2536-05-2 219-799-4 01-2119927323-43- XXXX	Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319	>= 0,5 - < 1
		>= 5 % specific concentration limit STOT SE 3; H335 >= 5 %	
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
		specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Immediately flush eye(s) with plenty of water.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Concrete Primer Part A



Revision Date: 13.05.2025 Date of last issue: 22.04.2024	Version 3.0	Print Date 13.05.2025
	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a speciali	ist.
If swallowed	: Do not induce vomiting without medical a Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unco	
4.2 Most important symptoms ar	nd effects, both acute and delayed	
Symptoms	 Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis Loss of balance Vertigo See Section 11 for more detailed informa and symptoms. 	tion on health effects
Risks	 irritant effects sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms of ties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. 	or breathing difficul-

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika[®] Concrete Primer Part A

Revision Date: 13.05.2025 Date of last issue: 22.04.2024		Version 3.0	Print Date 13.05.2025
5.2 Special hazards arising from	the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter fire.	and spread
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	apparatus.
Further information	:	Use water spray to cool unopened containers.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions		
Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for co	ntai	nment and cleaning up
Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid formation of aerosol.
	Avoid exceeding the given occupational exposure limits (see
	section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Date of last issue: 22.04.2024		Version 3.0	Print Date 13.05.2025	
		 ma, allergies, chronic or recurrent respiratory di not be employed in any process in which this m used. Smoking, eating and drinking should be prohibit plication area. Take precautionary measures against static dis Open drum carefully as content may be under p Take necessary action to avoid static electricity (which might cause ignition of organic vapours). Follow standard hygiene measures when handl products 	ixture is being ted in the ap- charge. oressure. discharge	
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from open flames/ hot surfaces. No smoking. Take p measures against electrostatic discharges.		
Hygiene measures	:	Handle in accordance with good industrial hygic practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the e	using do not	
7.2 Conditions for safe storage,	inc	luding any incompatibilities		
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-well-well-well-well-well-well-well	arefully re-	
Further information on stor- age stability	:	No decomposition if stored and applied as direc	ted.	
7.3 Specific end use(s)				
Specific use(s)	:	Cleaning with aprotic polar solvents must be ave Consult most current local Product Data Sheet puse.		

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC
		mation: Identifies the skin, Indicative	e possibility of signi	ificant uptake
		TWA	50 ppm 275 mg/m3	2000/39/EC
		OELV - 8 hrs (TWA)	50 ppm 275 mg/m3	IE OEL

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0

Print Date 13.05.2025

	Further inforr	nation: Substances	which have the c	apacity to per
	trate intact sk	in when they come		
	sorbed into the			
		OELV - 15 min (STEL)	100 ppm 550 mg/m3	IE OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	OELV - 8 hrs (TWA)	0,005 ppm (NCO)	IE OEL
		nation: Chemical ag		
	may cause se	ensitisation of the re	espiratory tract ar	d lead to asth
		r extrinsic allergic al		
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	OELV - 8 hrs (TWA)	0,02 mg/m3 (NCO)	IE OEL
	Further inforr	nation: Chemical ag	ents which follow	ing exposure
		ensitisation of the re		d lead to asth
	ma, rhinitis o	r extrinsic allergic al		
		OELV - 15 min (STEL)	0,07 mg/m3 (NCO)	IE OEL
propyl acetate	109-60-4	OELV - 8 hrs (TWA)	100 ppm	IE OEL
		OELV - 15 min	150 ppm	IE OEL
		(STEL)		
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	OELV - 8 hrs (TWA)	0,02 mg/m3 (NCO)	IE OEL
Diphenylmethanediisocyanate, isomeres and homologues		OELV - 8 hrs (TWA)	(NCO)	
Diphenylmethanediisocyanate, isomeres and homologues	Further inform	OELV - 8 hrs	(NCO) gents which follow	/ing exposure
Diphenylmethanediisocyanate, isomeres and homologues	Further inform	OELV - 8 hrs (TWA) nation: Chemical ag	(NCO) gents which follow espiratory tract ar	/ing exposure
Diphenylmethanediisocyanate, isomeres and homologues	Further inform	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3	/ing exposure
Diphenylmethanediisocyanate, isomeres and homologues	Further inform	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic a OELV - 15 min (STEL)	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO)	ving exposure d lead to asth
and homologues	Further inforr may cause so ma, rhinitis o	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL) OELV - 8 hrs (TWA)	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,005 ppm (NCO)	ving exposure vid lead to asth IE OEL IE OEL
and homologues	Further inform may cause so ma, rhinitis o 2536-05-2	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL) OELV - 8 hrs (TWA) OELV - 8 hrs (TWA)	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,005 ppm (NCO) 0,02 mg/m3 (NCO)	ving exposure vid lead to asth IE OEL IE OEL IE OEL
and homologues	Further inform may cause so ma, rhinitis o 2536-05-2	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL) OELV - 8 hrs (TWA) OELV - 8 hrs	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,005 ppm (NCO) 0,02 mg/m3 (NCO)	ving exposure vid lead to asth IE OEL IE OEL IE OEL
and homologues	Further inform may cause so ma, rhinitis o 2536-05-2 Further inform may cause so	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL) OELV - 8 hrs (TWA) OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,005 ppm (NCO) 0,02 mg/m3 (NCO) gents which follow espiratory tract an	ving exposure vid lead to asth IE OEL IE OEL IE OEL ving exposure
and homologues	Further inform may cause so ma, rhinitis o 2536-05-2 Further inform may cause so	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL) OELV - 8 hrs (TWA) OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,005 ppm (NCO) 0,02 mg/m3 (NCO) gents which follow espiratory tract an	ving exposure vid lead to asth IE OEL IE OEL IE OEL ving exposure
and homologues	Further inform may cause so ma, rhinitis o 2536-05-2 Further inform may cause so	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL) OELV - 8 hrs (TWA) OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,005 ppm (NCO) 0,02 mg/m3 (NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO)	ving exposure vid lead to asth IE OEL IE OEL IE OEL ving exposure
and homologues	Further inform may cause so ma, rhinitis o 2536-05-2 Further inform may cause so	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL) OELV - 8 hrs (TWA) OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,005 ppm (NCO) 0,02 mg/m3 (NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3	ving exposure d lead to asth IE OEL IE OEL Ving exposure d lead to asth
Diphenylmethanediisocyanate, isomeres and homologues 2,2'-methylenediphenyl diisocyanate	Further inform may cause so ma, rhinitis o 2536-05-2 Further inform may cause so ma, rhinitis o	OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL) OELV - 8 hrs (TWA) OELV - 8 hrs (TWA) nation: Chemical ag ensitisation of the re r extrinsic allergic al OELV - 15 min (STEL)	(NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,005 ppm (NCO) 0,02 mg/m3 (NCO) gents which follow espiratory tract an veolitis 0,07 mg/m3 (NCO) 0,01 mg/m3 (NCO)	ving exposure d lead to asth IE OEL IE OEL Ving exposure d lead to asth IE OEL 98/24/EC I

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166
		Eye wash bottle with pure water

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025 Date of last issue: 22.04.2024 Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345. long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work. Respiratory protection In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

ing point		
Melting point/ range / Freez-	:	No data available
Odour	:	characteristic
Physical state Colour	:	liquid light yellow

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Date of last issue: 22.04.2024		Version 3.0	Print Date 13.05.2025
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	losive limits	
Upper explosion limit / Up- per flammability limit	:	10,8 %(V)	
Lower explosion limit / Lower flammability limit	:	1,5 %(V)	
Flash point	:	40 °C Method: closed cup	
Auto-ignition temperature	:	333 °C	
Decomposition temperature	:	No data available	
рН	:	substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, kinematic	:	> 7 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	33 hPa	
Density	:	ca. 1,1 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika[®] Concrete Primer Part A

Revision Date: 13.05.2025 Date of last issue: 22.04.2024	Version 3.0	Print Date 13.05.2025
9.2 Other information		
No data available		
SECTION 10: Stability and reac	ivity	
10.1 Reactivity		
No dangerous reaction known u	der conditions of normal use.	
10.2 Chemical stability		
The product is chemically stable		
10.3 Possibility of hazardous react	ons	
Hazardous reactions	Stable under recommended storage conditions.	
	Vapours may form explosive mixture with air.	
10.4 Conditions to avoid		
Conditions to avoid	Heat, flames and sparks.	
10.5 Incompatible materials		
Materials to avoid	No data available	
10.6 Hazardous decomposition pro	ducts	
	No hazardous decomposition products are know	vn.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified due to lack of	data.	
Components:		
2-methoxy-1-methylethyl a	iceta	te:
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg
4,4'-methylenediphenyl dii	socy	vanate:
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1,5 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A



evision Date: 13.05.2025 ate of last issue: 22.04.2024		Version 3.0	Print Date 13.05.20
		Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement	
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method	
Diphenylmethanediisocya	nate,	isomeres and homologues:	
Acute oral toxicity	:	LD50 Oral (Rat): > 10.000 mg/kg	
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is r short term inhalation.	noderately toxic after
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9.400 mg/kg	
Skin corrosion/irritation Causes skin irritation.	., ,.		
Serious eye damage/eye in Causes serious eye irritation		on	
Respiratory or skin sensit	isatic	n	
Skin sensitisation May cause an allergic skin r	eactio	on.	
Respiratory sensitisation May cause allergy or asthm	a sym	ptoms or breathing difficulties if inhaled.	
Germ cell mutagenicity Not classified due to lack of	data.		
Carcinogenicity Suspected of causing cance	er.		
Reproductive toxicity			
Not classified due to lack of	data.		
STOT - single exposure			
May cause respiratory irritat May cause drowsiness or di		SS.	
STOT - repeated exposure			
Not classified due to lack of	data.		

Sika[®] Concrete Primer Part A



Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0

Print Date 13.05.2025

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid-
	ered to have endocrine disrupting properties according to
	REACH Article 57(f) or Commission Delegated regulation
	(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at
	levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Date of last issue: 22.04.2024 Version 3.0

Print Date 13.05.2025

12.7 Other adverse effects

Product:

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	The generation of waste should be avoided or m wherever possible. Empty containers or liners may retain some proo This material and its container must be disposed way. Dispose of surplus and non-recyclable products waste disposal contractor. Disposal of this product, solutions and any by-pr at all times comply with the requirements of env protection and waste disposal legislation and an local authority requirements. Avoid dispersal of spilled material and runoff and soil, waterways, drains and sewers.	duct residues. d of in a safe via a licensed oducts should ironmental y regional
European Waste Catalogue	08 01 11* waste paint and varnish containing or vents or other dangerous substances	ganic sol-
Contaminated packaging	15 01 10* packaging containing residues of or c by dangerous substances	ontaminated

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADR	:	PAINT RELATED MATERIAL
IMDG	:	PAINT RELATED MATERIAL
ΙΑΤΑ	:	Paint related material
14.3 Transport bazard class(os)		

14.3 Transport hazard class(es)

Subsidiary risks

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Date of last issue: 22.04.2024		Version 3.0	Print Date 13.05.202
ADR	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADR			
Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks	· · · · · · · · · · · · · · · · · · ·	III F1 30 3 (D/E) Transport according to chapter 3.4 (LO) possible	
Remarks	·	Transport according to chapter 3.4 (LQ) possible	
IMDG Packing group Labels EmS Code	:	III 3 F-E, <u>S-E</u>	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	366 Y344 III Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	355 Y344 III Flammable Liquids	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	no	
IMDG Marine pollutant	:	no	
IATA (Passenger) Environmentally hazardous	:	no	
IATA (Cargo) Environmentally hazardous	:	no	
14.6 Special precautions for use	r		

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Concrete Primer Part A

Jika®

Print Date 13.05.2025

Revision Date: 13.05.2025Version 3.0Date of last issue: 22.04.2024Version 3.0

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 56:

4,4'-methylenediphenyl diisocyanate, o-(p-isocyanatobenzyl)phenyl isocyanate, Diphenylmethanediisocyanate, isomeres and homologues, 2,2'-methylenediphenyl diisocyanate

Number on list 74:

4,4'-methylenediphenyl diisocyanate, o-(p-isocyanatobenzyl)phenyl isocyanate, Diphenylmethanediisocyanate, isomeres and homologues, 2,2'-methylenediphenyl diisocyanate

Number on list 75

REACH - Candidate List of Substances of Very High: None of the components are listedConcern for Authorisation (Article 59).(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV)

: Not applicable

: Not applicable

Regulation (EU) No 2024/590 on substances that de-

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-

tion (EU) 2020/878

Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Date of last issue: 22.04.2024	Version 3.0	Print Date 13.05.2025
plete the ozone layer		
Regulation (EU) 2019/1021 on po tants (recast)	ersistent organic pollu- : Not applicable	
Regulation (EU) No 649/2012 of ment and the Council concerning of dangerous chemicals		
Seveso III: Directive 2012/18/EU jor-accident hazards involving da	of the European Parliament and of the Cour ngerous substances. FLAMMABLE LIQUIDS	icil on the control of ma-
Volatile organic compounds :	Law on the incentive tax for volatile organic (VOCV) Volatile organic compounds (VOC) content	
	Directive 2010/75/EU of 24 November 201 livestock rearing emissions (integrated poll and control) Volatile organic compounds (VOC) content	ution prevention
If other regulatory information ap Sheet, then it is described in this	plies that is not already provided elsewhere i subsection.	n the Safety Data
Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	Environmental Protection Act 1990 & Subs Health and Safety at Work Act 1974 & Sub Control of Substances Hazardous to Health (COSHH) May be subject to the Control of Major Acc Regulations (COMAH), and amendments.	sidiary Regulations n Regulations

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225

: Highly flammable liquid and vapour.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Concrete Primer Part A

Revision Date: 13.05.2025 Da



evision Date: 13.05.2025 ate of last issue: 22.04.2024	Version 3.0	Print Date 13.05.2025
H226	: Flammable liquid and vapour.	
H315	: Causes skin irritation.	
H317	: May cause an allergic skin reaction.	
H319	: Causes serious eye irritation.	
H332	: Harmful if inhaled.	
H334		or broothing difficul
П334	: May cause allergy or asthma symptoms ties if inhaled.	or breatning difficul-
H335	: May cause respiratory irritation.	
H336	: May cause drowsiness or dizziness.	
H351	: Suspected of causing cancer.	
H373	: May cause damage to organs through p	violonged or repeated
1075	exposure.	solonged of repeated
H373	: May cause damage to organs through p exposure if inhaled.	prolonged or repeated
Full text of other abbreviatio	ns	
Acute Tox.	: Acute toxicity	
Carc.	: Carcinogenicity	
Eye Irrit.	: Eye irritation	
Flam. Liq.	: Flammable liquids	
Resp. Sens.	: Respiratory sensitisation	
Skin Irrit.	: Skin irritation	
Skin Sens.	: Skin sensitisation	
STOT RE	: Specific target organ toxicity - repeated	
STOT SE	: Specific target organ toxicity - single ex	
2000/39/EC	: Europe. Commission Directive 2000/39/	
	list of indicative occupational exposure	
98/24/EC I	: Europe. Chemical Agents Directive - Ar	inex I: Binding occupa-
IE OEL	tional exposure limit valuesIreland. List of Chemical Agents and Ca	arcinogens with Occu-
	pational Exposure Limit Values - Code	
	and 2	or Fractice, Schedule 1
2000/39/EC / TWA	: Limit Value - eight hours	
2000/39/EC / STEL	: Short term exposure limit	
98/24/EC I / STEL	: Limit values Short-term	
98/24/EC I / TWA	: Limit values 8 hours	
IE OEL / OELV - 8 hrs (TWA)	: Occupational exposure limit value (8-ho	
IE OEL / OELV - 15 min	: Occupational exposure limit value (15-n	ninute reference peri-
(STEL)	od)	
ADR	: European Agreement concerning the In	ternational Carriage of
	Dangerous Goods by Road	
CAS	: Chemical Abstracts Service	
DNEL	: Derived no-effect level	
EC50	: Half maximal effective concentration	
GHS	: Globally Harmonized System	
IATA	: International Air Transport Association	
IMDG		ous Goods
	: International Maritime Code for Dangero	
LD50	: Median lethal dosis (the amount of a ma	
	once, which causes the death of 50% (c	one nail) of a group of
1.050	test animals)	
LC50	: Median lethal concentration (concentrat	
	air that kills 50% of the test animals dur	ing the observation
	period)	
		21/22

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Date of last issue: 22.04.2024		Version 3.0	Print Date 13.05.2025
MARPOL	:	International Convention for the Prevention of Ships, 1973 as modified by the Protocol of 19	
OEL	:	Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
REACH	:	Regulation (EC) No 1907/2006 of the Europea and of the Council of 18 December 2006 cond istration, Evaluation, Authorisation and Restric cals (REACH), establishing a European Chem	erning the Reg- tion of Chemi-
SVHC vPvB	:	Substances of Very High Concern Very persistent and very bioaccumulative	
	•	very persistent and very bloaccumulative	

Further information

Classification of the mixture:		Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN