according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Revision Date: 26.04.2024 Version 3.0 Print Date 28.03.2025

Date of last issue: 20.07.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikadur®-31 DW Rapid Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive, Cement / Mortar, Product is not intended for con-

sumer use

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Ireland Ltd

Sika House

Ballymun Industrial Estate

Dublin 11

Telephone : +353 1862 0709 E-mail address of person : EHS@UK.Sika.com

responsible for the SDS

#### 1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Reproductive toxicity, Category 2 H361d: Suspected of damaging the unborn child.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Date of last issue: 20.07.2022

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

Supplemental Hazard

Statements

EUH071 Corrosive to the respiratory tract.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P261 Avoid breathing mist or vapours.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

#### Hazardous components which must be listed on the label:

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine m-phenylenebis(methylamine) salicylic acid

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Date of last issue: 20.07.2022

# Version 3.0 Find Date 28.0

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Components			
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine	25513-64-8 247-063-2 01-2119560598-25- XXXX	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Acute toxicity estimate  Acute oral toxicity: 910 mg/kg	>= 5 - < 10
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 ————————————————————————————————————	>= 5 - < 10
salicylic acid	69-72-7 200-712-3 01-2119486984-17- XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d  Acute toxicity estimate  Acute oral toxicity: 891 mg/kg	>= 3 - < 5

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Revision Date: 26.04.2024 Version 3.0 Print Date 28.03.2025

Date of last issue: 20.07.2022

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Health injuries may be delayed.

corrosive effects sensitising effects

May cause an allergic skin reaction.

Causes serious eye damage.

Suspected of damaging the unborn child.

Corrosive to the respiratory tract.

Causes severe burns.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Revision Date: 26.04.2024 Version 3.0 Print Date 28.03.2025

Date of last issue: 20.07.2022

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

### 6.2 Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B



Date of last issue: 20.07.2022

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Handle in accordance with good industrial hygiene and safety Hygiene measures

> practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) Consult most current local Product Data Sheet prior to any

use.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
m-phenylenebis(methylamine)	1477-55-0	OELV - 8 hrs (TWA)	0,1 mg/m3	IE OEL

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Safety glasses with side-shields conforming to EN166 Eye/face protection

> Eye wash bottle with pure water Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

> proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Revision Date: 26.04.2024 Version 3.0 Print Date 28.03.2025

Date of last issue: 20.07.2022

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing

and stirring work.

Respiratory protection In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

**Environmental exposure controls** 

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state liquid

Appearance viscous liquid Colour dark grey

Odour amine-like

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

per flammability limit

Upper explosion limit / Up- : No data available

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Lower explosion limit / Lower flammability limit

: No data available

Flash point : > 101 °C

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : ca. 11 (20 °C)

Concentration: 100 %

**Viscosity** 

Viscosity, kinematic : > 20,5 mm2/s

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0,04 hPa

Density : ca. 1,96 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Revision Date: 26.04.2024 Version 3.0 Print Date 28.03.2025

Date of last issue: 20.07.2022

Hazardous reactions Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid No data available

10.5 Incompatible materials

Materials to avoid No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified based on available information.

#### **Components:**

### 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg

> Acute toxicity estimate: 910 mg/kg Method: Calculation method

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

> Acute toxicity estimate: 930 mg/kg Method: Calculation method

Acute inhalation toxicity LC50 (Rat): 1,34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method

LD50 Dermal (Rat): > 3.100 mg/kg Acute dermal toxicity

salicylic acid:

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute toxicity estimate: 891 mg/kg

Method: Calculation method

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Date of last issue: 20.07.2022

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

#### Skin corrosion/irritation

Causes severe burns.

### Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Suspected of damaging the unborn child.

### STOT - single exposure

Corrosive to the respiratory tract.

### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

### 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Revision Date: 26.04.2024 Version 3.0 Print Date 28.03.2025

Date of last issue: 20.07.2022

Toxicity to algae/aquatic

plants

: EC50 (Scenedesmus capricornutum (fresh water algae)): 29,5

mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

: LC50: 174 mg/l

Exposure time: 48 h

Species: Leuciscus idus (Golden orfe)

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.

**SECTION 13: Disposal considerations** 

13.1 Waste treatment methods

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Date of last issue: 20.07.2022

Sika<sup>®</sup>

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR : UN 2735 IMDG : UN 2735 IATA : UN 2735

### 14.2 UN proper shipping name

ADR : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine, m-

phenylenebis(methylamine))

**IMDG** : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine, m-

phenylenebis(methylamine))

**IATA** : Polyamines, liquid, corrosive, n.o.s.

(2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine, m-

phenylenebis(methylamine))

### 14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 8

 IMDG
 : 8

 IATA
 : 8

### 14.4 Packing group

**ADR** 

Packing group : II
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Date of last issue: 20.07.2022

**IMDG** 

Packing group : II Labels : 8

EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo : 855

aircraft)

Packing instruction (LQ) : Y840 Packing group : II

Labels : Corrosive

IATA (Passenger)

Packing instruction (passen: 851

ger aircraft)

Packing instruction (LQ) : Y840 Packing group : II

Labels : Corrosive

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Date of last issue: 20.07.2022

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Revision Date: 26.04.2024 Version 3.0 Print Date 28.03.2025

Date of last issue: 20.07.2022

### **SECTION 16: Other information**

**Full text of H-Statements** 

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H361d : Suspected of damaging the unborn child.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Repr. : Reproductive toxicity Skin Corr. : Skin corrosion Skin Sens. : Skin sensitisation

IE OEL : Ireland. List of Chemical Agents and Carcinogens with Occu-

pational Exposure Limit Values - Code of Practice, Schedule 1

and 2

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Ser
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

according to Regulation (EC) No. 1907/2006

## Sikadur®-31 DW Rapid Part B

Date of last issue: 20.07.2022



Classification of the mixture:		Classification procedure:
Skin Corr. 1A	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 2	H361d	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

IE / EN