

Revision Date: 29.04.2025 Date of last issue: 24.04.2025 Version 5.3

Print Date 29.04.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifier**

Trade name

: Sikafloor<sup>®</sup>-150 Part B

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Epoxy coating, Product is not intended for consumer use

# 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd
		Sika House
		Ballymun Industrial Estate
		Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person	:	EHS@UK.Sika.com
responsible for the SDS		

## **1.4 Emergency telephone number**

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

## 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Part B



Revision Date: 29.04.2025 Version 5.3 Print Date 29.04.2025 Date of last issue: 24.04.2025 Hazard pictograms 2 Signal word Danger 1 H302 Harmful if swallowed. Hazard statements Causes severe skin burns and eye damage. H314 May cause an allergic skin reaction. H317 H412 Harmful to aquatic life with long lasting effects. Prevention: Precautionary statements · P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF ON SKIN (or hair): Take off immedi-P303 + P361 + P353 ately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

#### Hazardous components which must be listed on the label:

benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine Amines, polyethylenepoly-, tetraethylenepentamine fraction

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

CAS-No.

100-51-6

Registration number

EC-No.

**SECTION 3: Composition/information on ingredients** 

# Sikafloor<sup>®</sup>-150 Part B

Revision Date: 29.04.2025	
Date of last issue: 24.04.2025	

3.2 Mixtures

Components Chemical name

benzyl alcohol

Version 5.3

Classification

Acute Tox. 4; H302

Print Date 29.04.2025

Concentration

(% w/w)

>= 40 - < 60

#### 202-859-9 Eye Irrit. 2; H319 01-2119492630-38-Skin Sens. 1B; H317 XXXX Acute toxicity estimate Acute oral toxicity: 1.200 mg/kg 3-aminomethyl-3,5,5-2855-13-2 Acute Tox. 4; H302 >= 25 - < 40 Skin Corr. 1B; H314 trimethylcyclohexylamine 220-666-8 01-2119514687-32-Eye Dam. 1; H318 XXXX Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A: H317 >= 0,001 % Acute toxicity estimate Acute oral toxicity: 1.030 mg/kg Acute Tox. 4; H302 Amines, polyethylenepoly-, tetra-90640-66-7 >= 10 - < 20 ethylenepentamine fraction Acute Tox. 4; H312 292-587-7 01-2119487290-37-Skin Corr. 1B; H314 Eye Dam. 1; H318 XXXX Skin Sens. 1B; H317 Aquatic Chronic 2; H411 Acute toxicity estimate Acute oral toxicity: 1.716 mg/kg Acute dermal toxicity: 1.465 mg/kg

3/17



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# Sikafloor®-150 Part B

vision Date: 29.04.2025 te of last issue: 24.04.2025	Version 5.3		Print Date 29.04.2025	
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg	>= 5 - < 10	

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	<ul> <li>Small amounts splashed into eyes can cause irreversible tissue damage and blindness.</li> <li>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</li> <li>Continue rinsing eyes during transport to hospital.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> </ul>
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	<ul> <li>Gastrointestinal discomfort Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms.</li> </ul>
Risks	: Health injuries may be delayed. corrosive effects



Revision Date: 29.04.2025 Date of last issue: 24.04.2025	Version 5.3	Print Date 29.04.2025	
	sensitising effects		
	Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns.		
<b>4.3 Indication of any immediate m</b> Treatment	edical attention and special treatment nee : Treat symptomatically.	eded	
SECTION 5: Firefighting measure	ures		
5.1 Extinguishing media			
Suitable extinguishing media	: In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/cherextinction.		
5.2 Special hazards arising from t	he substance or mixture		
Hazardous combustion prod- ucts	: No hazardous combustion products are k	nown	
5.3 Advice for firefighters			
-	: In the event of fire, wear self-contained bi	reathing apparatus.	
Further information	: Standard procedure for chemical fires.		
SECTION 6: Accidental release	e measures		
6.1 Personal precautions, protect	ive equipment and emergency procedures	5	
Personal precautions	: Use personal protective equipment. Deny access to unprotected persons.		
6.2 Environmental precautions			
Environmental precautions	: Do not flush into surface water or sanitary If the product contaminates rivers and lak respective authorities.		

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

# Sikafloor®-150 Part B



Revision Date: 29.04.2025 Version 5.3 Date of last issue: 24.04.2025

Print Date 29.04.2025

# 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

	Advice on safe handling :	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
	Advice on protection against : fire and explosion	Normal measures for preventive fire protection.
	Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, inc	luding any incompatibilities
	Requirements for storage : areas and containers	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- : age stability	No decomposition if stored and applied as directed.
7.3	Specific end use(s)	
	Specific use(s) :	Consult most current local Product Data Sheet prior to any use.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# **Occupational Exposure Limits**

Contains no substances with occupational exposure limit values.

# Sikafloor®-150 Part B



Revision Date: 29.04.2025 Date of last issue: 24.04.2025 Version 5.3

Print Date 29.04.2025

#### 8.2 Exposure controls

# Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment	t
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	No special measures required.
Environmental exposure contr	ols
General advice :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid light yellow
Odour	:	amine-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-150 Part B



Revision Date: 29.04.2025 Date of last issue: 24.04.2025	Version 5.3	Print Date 29.04.2025
Flammability (solid, gas)	: No data available	
<b>Upper/lower flammability or</b> Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	: No data available	
Flash point	: > 101 °C Method: closed cup	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
рН	: ca. 11 (20 °C) Concentration: 50 %	
Viscosity		
Viscosity, dynamic	: ca. 40 mPa.s (20 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,07 hPa	
Density	: ca. 0,99 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

No data available



Version 5.3

Print Date 29.04.2025

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### **10.2 Chemical stability**

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	: :	Stable under recommended storage conditions.
---------------------	-----	----------------------------------------------

#### 10.4 Conditions to avoid

Conditions to avoid	:	No data available
---------------------	---	-------------------

# 10.5 Incompatible materials

Materials to avoid : No	data available

## **10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed. <u>Components:</u>	
benzyl alcohol:	
Acute oral toxicity	: Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
	LD50 Oral (Rat): 1.200 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist
3-aminomethyl-3,5,5-trimeth	ylcyclohexylamine:
Acute oral toxicity	: Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

# Sikafloor®-150 Part B



ision Date: 29.04.2025 e of last issue: 24.04.2025		Version 5.3	Print Date 29.04.2025
		LD50 Oral (Rat): 1.030 mg/kg	
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg	
		LD50 (Rabbit): > 2.000 - 5.000 mg/kg	
Amines, polyethylenepoly	-, tet	raethylenepentamine fraction:	
Acute oral toxicity	:	LD50 Oral (Rat): 1.716 mg/kg	
		Acute toxicity estimate: 1.716 mg/kg Method: Calculation method	
Acute dermal toxicity	:	LD50 Dermal (Rat): 1.465 mg/kg	
		Acute toxicity estimate: 1.465 mg/kg Method: Calculation method	
2,4,6-tris(dimethylaminom	ethy	l)phenol:	
Acute oral toxicity	:	LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Skin corrosion/irritation			
Causes severe burns.			
Components:			
2,4,6-tris(dimethylaminom	ethy	l)phenol:	
Species Assessment Method	:	Rabbit Corrosive OECD Test Guideline 404	
Assessment Remarks	:	irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Serious eye damage/eye i	rritat	ion	
Causes serious eye damage	э.		
Components:			
2,4,6-tris(dimethylaminom	ethy	l)phenol:	
Species Assessment	:	Rabbit Causes serious eye damage.	



Revision Date: 29.04.2025 Date of last issue: 24.04.2025 Version 5.3

Print Date 29.04.2025

Assessment	:	irritating
Remarks	:	Annex VI - Harmonised
		REGULATION (EC) No 1272/2008

# Respiratory or skin sensitisation

## Skin sensitisation

May cause an allergic skin reaction.

## Respiratory sensitisation

Not classified due to lack of data.

## Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

Not classified due to lack of data.

## **Reproductive toxicity**

Not classified due to lack of data.

## STOT - single exposure

Not classified due to lack of data.

# STOT - repeated exposure

Not classified due to lack of data.

#### Aspiration toxicity

Not classified due to lack of data.

# 11.2 Information on other hazards

#### Endocrine disrupting properties

Not classified due to lack of data.

# Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

# Components:

# benzyl alcohol:

Toxicity to fish

LC50 (Fish): > 100 mg/l Exposure time: 96 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor<sup>®</sup>-150 Part B




Revision Date: 29.04.2025 Date of last issue: 24.04.2025		Version 5.3	Print Date 29.04.202
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 Exposure time: 48 h	mg/l
3-aminomethyl-3,5,5-trimetl	hylc	yclohexylamine:	
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green a mg/l Exposure time: 72 h	algae)): > 10 - 100
		NOEC (Desmodesmus subspicatus (green Exposure time: 72 h	algae)): 1,5 mg/l
<b>12.2 Persistence and degradabi</b> No data available	lity		
<b>12.3 Bioaccumulative potential</b> No data available			
<b>12.4 Mobility in soil</b> No data available			
12.5 Results of PBT and vPvB a	sse	ssment	
Product:			
Assessment	:	This substance/mixture contains no compor to be either persistent, bioaccumulative and very persistent and very bioaccumulative (v 0.1% or higher	l toxic (PBT), or
12.6 Endocrine disrupting prope	ertie	S	
Product:			
Assessment	:	The substance/mixture does not contain con ered to have endocrine disrupting properties REACH Article 57(f) or Commission Delega (EU) 2017/2100 or Commission Regulation levels of 0.1% or higher.	s according to ted regulation
12.7 Other adverse effects			
Droduct			
Product:	:	An environmental hazard cannot be exclude	ed in the event of

# SECTION 13: Disposal considerations

# 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized
---------	---	--------------------------------------------------------

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878





Revision Date: 29.04.2025 Date of last issue: 24.04.2025		Version 5.3	Print Date 29.04.2025
		<ul> <li>wherever possible.</li> <li>Empty containers or liners may retain some product residues.</li> <li>This material and its container must be disposed of in a safe way.</li> <li>Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.</li> <li>Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.</li> <li>Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.</li> </ul>	
European Waste Catalogue	:	08 01 11* waste paint and varnish containing or vents or other dangerous substances	ganic sol-
Contaminated packaging	:	15 01 10* packaging containing residues of or co by dangerous substances	ontaminated

# **SECTION 14: Transport information**

14.1 UN number or ID number				
ADR	:	UN 2735		
IMDG	:	UN 2735		
ΙΑΤΑ	:	UN 2735		
14.2 UN proper shipping name				
ADR	:		DRROSIVE, N.O.S. 5-trimethylcyclohexylamine, Amines, pol- ethylenepentamine fraction)	
IMDG	:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Amines, pol- yethylenepoly-, tetraethylenepentamine fraction)		
ΙΑΤΑ	:	Amines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Amines, pol- yethylenepoly-, tetraethylenepentamine fraction)		
14.3 Transport hazard class(es)				
		Class	Subsidiary risks	
ADR	:	8		
IMDG	:	8		
ΙΑΤΑ	:	8		
14.4 Packing group				

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-150 Part B

**Jika**®

Revision Date: 29.04.2025 Date of last issue: 24.04.2025 Version 5.3

Print Date 29.04.2025

# ADR

Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III C7 80 8 (E)
IMDG Packing group Labels EmS Code		III 8 F-A, S-B
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	856 Y841 III Corrosive
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ)	:	
Packing group	÷	

# 14.5 Environmental hazards

Labels

ADR Environmentally hazardous	:	no
IMDG Marine pollutant	:	no
IATA (Passenger) Environmentally hazardous	:	no
IATA (Cargo) Environmentally hazardous	:	no

# 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# 14.7 Maritime transport in bulk according to IMO instruments

•

Corrosive

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

: Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors



Revision Date: 29.04.2025 Date of last issue: 24.04.2025	Version	5.3		Print Date 29.04.2025		
REACH Information: All substances cont - registered by our of - registered by us, a - excluded from the - exempted from the			am suppliers, and/or ation, and/or			
REACH - Restrictions on the mathe market and use of certain da mixtures and articles (Annex XV	ingerous substances,	:	Conditions of restrict lowing entries should Number on list 3			
			Number on list 75			
REACH - Candidate List of Subs Concern for Authorisation (Articl		:	None of the compone (=> 0.1 %).	ents are listed		
REACH - List of substances subject to authorisation (Annex XIV)			Not applicable			
Regulation (EU) No 2024/590 or plete the ozone layer	n substances that de-	:	Not applicable			
Regulation (EU) 2019/1021 on p tants (recast)	ersistent organic pollu-	:	Not applicable			
Regulation (EU) No 649/2012 of ment and the Council concerning of dangerous chemicals		:	Not applicable			
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. Not applicable						
Volatile organic compounds :	Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 48% w/w					
	ndustrial and prevention 6 w/w					



Revision Date: 29.04.2025 Version 5.3 Date of last issue: 24.04.2025

Print Date 29.04.2025

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ- mental regulation/legislation	:	Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or mixture:		Control of Substances Hazardous to Health Regulations (COSHH)
		May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

# 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# **SECTION 16: Other information**

Full text of H-Statements		
H302	:	Harmful if swallowed.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbreviat	ions	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
·		

# Full text of H-Statements

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-150 Part B



Revision Date: 29.04.2025 Date of last issue: 24.04.2025	Version 5.3	Print Date 29.04.2025
PBT PNEC REACH	<ul> <li>Persistent, bioaccumulative and toxic</li> <li>Predicted no effect concentration</li> <li>Regulation (EC) No 1907/2006 of the and of the Council of 18 December 20 istration, Evaluation, Authorisation and cals (REACH), establishing a Europea</li> </ul>	European Parliament )06 concerning the Reg- d Restriction of Chemi-
SVHC vPvB	<ul><li>Substances of Very High Concern</li><li>Very persistent and very bioaccumula</li></ul>	tive

# **Further information**

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN