

PRODUCT DATA SHEET

Feb[®] Febond Blue Grit[®]

EXTRA GRIP PLASTER BONDING AGENT

PRODUCT DESCRIPTION

Feb[®] Febond Blue Grit[®] is a high performance plaster bonding agent specifically designed to provide an improved key to smooth surfaces. Containing a fine aggregate, Feb[®] Febond Blue Grit[®] provides a mechanical key to backgrounds such as plaster, concrete, painted surfaces and glazed tiles.

USES

- Bonding coat for walls prior to plastering.
- Bonding to difficult substrates - glass, ceramics, MR plasterboard, MDF, pre-cast concrete, and other particle boards etc.

CHARACTERISTICS / ADVANTAGES

- Provides mechanical key - enables plastering.
- Blue colour gives easy identification of area covered.
- Simple to apply by roller or brush.
- Ready to use straight from the tub.

APPROVALS / STANDARDS

Bond strength tested in accordance with EN13892-8.

PRODUCT INFORMATION

Chemical Base	A modified vinyl co-polymer emulsion with selected aggregates and additives.
Packaging	5L & 10L pails
Appearance / Colour	Blue
Shelf Life	24 months when stored in a sealed container and as recommended.
Storage Conditions	Store in cool (5 - 25°C) conditions. Protect from extremes of temperatures and frost.
Consumption	Approx. 4.5m ² per litre, depending on substrate porosity.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Ensure substrate is dust, release agent and frost free and is suitable to provide sufficient support.

APPLICATION

STIR WELL BEFORE USE. Ensure ambient and surface

temperature is above 5°C. Use 1 coat only. Apply using a short pile roller or brush to give an even coating. Feb[®] Febond Blue Grit[®] is coloured blue to help avoid missing any areas.

Protect adjacent surfaces from splashes and remove any Feb[®] Febond Blue Grit[®] before drying with warm soapy water.

Allow to dry thoroughly before applying plaster (usually 24 hours minimum). NOTE: drying time will be sig-

nificantly extended at low temperatures.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
Feb® Febond Blue Grit®
May 2019, Version 01.01
020406010050000011

FebFebondBlueGrit-en-IE-(05-2019)-1-1.pdf

