

PRODUCT DATA SHEET

EVERBUILD TECNIC® Sealant Primer NP2

SOLVENT BASED, POLYORGANOSILOXANE SEALANT PRIMER

PRODUCT DESCRIPTION

EVERBUILD SEALANT PRIMER NP2 is a solvent based, polyorganosiloxane primer for use on non porous surfaces prior to applying all common types of silicone.

USES

- Glass
- uPVC
- Aluminium
- Steel
- Ceramics

CHARACTERISTICS / ADVANTAGES

- Works on most common non porous building materials
- Works with all common silicone types.

PRODUCT INFORMATION

Packaging	1ltr Tin
Appearance / Colour	Yellow liquid
Shelf Life	12 months from date of manufacture. In original, unopened containers.
Storage Conditions	Store in cool, dry conditions between +5 and +25°C. Ensure good ventilation. Storage outside these parameters will dramatically reduce shelf life. Opened tins must be closed airtight and used up as soon as possible (within 1 month).
Density	0.7-0.8 g/cm ³
Flash Point	3°C
Service Temperature	Working Temperature 5 to 40°C

APPLICATION INFORMATION

Curing Time Drying Time @ 20°C - Approx 30 minutes

Product Data Sheet EVERBUILD TECNIC® Sealant Primer NP2 June 2019, Version 01.01 0205160100000000041

APPLICATION INSTRUCTIONS

Coverage will vary according to type and porosity of substrate. As a guide, a 1ltr bottle will cover approx 2.5m².

APPLICATION METHOD / TOOLS

Apply by brush in one coat and allow to dry.

LIMITATIONS

- Do not use against bitumen or substrates that bleed oil or plasticizers.
- Do not use below +5°C.
- Do not apply to damp or wet surfaces.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Data sheet available to professional user upon request.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate Ballymun Dublin 11, Ireland Tel: +353 1 862 0709 Web: www.sika.ie Twitter: @Sikalreland



Product Data Sheet EVERBUILD TECNIC® Sealant Primer NP2 June 2019, Version 01.01 020516010000000041

