

## PRODUCT DATA SHEET

# Cromar® Lead Free Plus

A high performance, self adhesive aluminium flashing.

### PRODUCT DESCRIPTION

Designed as a cost effective alternative to traditional lead flashing. It is suitable for use on flat and pitched roofs and provides a durable, waterproof solution without the handling, health and theft issues associated with lead.

### USES

- Chimneys and abutments.
- Dormers.
- Soakers and stepped flashings.
- Valleys.
- Windows and rooflights.
- Gutters.

### PRODUCT INFORMATION

<b>Packaging</b>	1 roll per cardboard box.
<b>Colour</b>	Grey, lead look.
<b>Shelf Life</b>	24 months
<b>Storage Conditions</b>	Store in a cool, dry place away from direct sunlight.
<b>Dimensions</b>	Rolls available in; 150 mm x 5 m 300 mm x 5 m 450 mm x 5 m

### VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH: This

### CHARACTERISTICS / ADVANTAGES

- Lead free alternative to traditional lead flashing.
- Self adhesive backing for quick and easy installation.
- Lightweight and malleable - easily shaped on site.
- Waterproof and weather resistant.
- Durable aluminium construction.
- Easily cut and repaired.
- As a lead free product, it avoids the H&S concerns associated with lead containing materials.
- No scrap value, reducing risk of theft.
- Low-cost solution with long-term performance.

product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very

high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

## APPLICATION INSTRUCTIONS

- Suitable for flat and pitched roof applications.
- Apply to clean, dry substrates.
- Peel off backing and press firmly into place.
- Dress and shape using hand pressure or a roller.
- Ensure full adhesion, especially at edges and overlaps.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @Sikalreland



**Product Data Sheet**  
Cromar® Lead Free Plus  
March 2026, Version 01.01  
020945201000246834

CromarLeadFreePlus-en-IE-(03-2026)-1-1.pdf

