

PRODUCT DATA SHEET

EVERBUILD® MAMMOTH® BUILDERS PVC TAPE

Strong PVC builders tape

PRODUCT DESCRIPTION

EVERBUILD® MAMMOTH® BUILDERS PVC TAPE is a strong, versatile, all-weather adhesive that is ideal for jointing all PVC and polythene sheets and membranes. This product can be used in cold weather applications, down to 0°C. It provides good resistance to abrasion, moisture, alkalis, acids, corrosion and resistance to varying weather conditions. EVERBUILD® MAMMOTH® BUILDERS PVC TAPE is perfect for contamination barrier fastening, dust sealing of sheets and many other uses in construction and industry.

USES

- Contamination barrier fastening
- Dust sealing of sheets
- For heavy duty sealing, repairing and waterproofing
- Suitable for insulating air ducts and underground pipes

PRODUCT INFORMATION

Packaging	50 mm x 33 m & 75 mm x 33 m rolls
Appearance / Colour	Black
Shelf Life	12 months from date of manufacture.
Storage Conditions	Store in cool dry conditions between 10 °C and 27 °C. Safe in normal use however as a precaution keep polythene outer packaging away from children.
Thickness	0.15 mm
Elongation at Break	150 % @ 23 °C
Resistance to fire	Class A fire retardant

CHARACTERISTICS / ADVANTAGES

- Will stick to most common surfaces, including polythene and PVC.
- Good resistance to abrasion, moisture, alkalis, acids, corrosion and varying weather conditions
- Removes easily - no adhesive residue
- Can be used in extensive temperature, moisture and humid conditions
- Flame retardant

Adhesion to Steel	3.5 N/25mm
Adhesion to Backing	3.5 N/25mm
Dielectric Strength	5 KV/Min

APPROVALS / STANDARDS

EN 60454 type 2 for electrical use

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Ensure surfaces to which tape is to be applied are clean sound and dry.

APPLICATION METHOD / TOOLS

Remove outer packaging from roll of tape. Peel required amount of tape from roll pressing firmly into place while unrolling. Cut with a knife when finished.

LIMITATIONS

- Do not use on surfaces that bleed oils or plasticiser.
- It is the users responsibility to determine suitability for use. If in doubt contact technical services for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
EVERBUILD® MAMMOTH® BUILDERS PVC TAPE
August 2020, Version 02.01
02051605000000034

EVERBUILDMAMMOTHBUILDERSPVC TAPE-en-IE-(08-2020)-2-1.pdf

