

## PRODUCT DATA SHEET

# SikaRoof® Adhesive Tape PVC

Double-sided pressure sensitive adhesive

### PRODUCT DESCRIPTION

SikaRoof® Adhesive Tape PVC is a double-sided pressure sensitive acrylic adhesive to bond waterproofing membranes to various substrates.

### USES

Approved Substrates

- Plywood, OSB
- Concrete
- Metal
- PIR/PUR Insulation
- Coverboards
- Sikaplan PVC Roofing Membranes

### PRODUCT INFORMATION

<b>Chemical Base</b>	Double-sided acrylic adhesive with removable polyolefin liner
<b>Packaging</b>	33 cm x 50 m roll, 7.5 kg per roll, 84 rolls per pallet 100 cm x 50 m roll, 23 kg per roll, 28 rolls per pallet
<b>Shelf Life</b>	12 months
<b>Storage Conditions</b>	Store rolls standing on end on pallets and fully protected from the weather. Store at temperatures between 5°C - 30°C. Limit exposure to direct sunlight. Do not expose to moisture and/or extreme humidity while stored.

### CHARACTERISTICS / ADVANTAGES

- VOC free and odor free
- Quick and easy to install
- Factory manufactured to ensure uniform coverage
- Can be installed down to 0°C
- Eliminates disposal of empty adhesive pails
- Polyolefin interliner protects the adhesive

### VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### USES

- The ambient and substrate temperature must be 0°C or above during application.
- SikaRoof® Adhesive Tape PVC will not provide a barrier from incompatible materials such as residual asphalt
- Adhered flashings that exceed 1.00 m in height shall receive additional securement

- A static electric charge may develop when removing the liner from the adhesive. Care should be used when removing and handling the liner to avoid ignition. Lids must be closed on any flammable products and a fire extinguisher should be readily available.

## ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH: This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

All surfaces must be clean, sound, dry, and free of loose materials and laitance, or contaminants such as water, frost, ice, oil and grease that would interfere with the adhesion of the product. Concrete block joints must be flush with the face of the concrete block.

### APPLICATION

#### Parapets >30cm

Use the 100 cm wide roll. Lay the roll on side at the base of the wall with the SikaRoof® Adhesive Tape PVC side toward the wall. Pull the SikaRoof® Adhesive Tape PVC up to the top of the wall. Press and smooth the SikaRoof® Adhesive Tape PVC into place by hand and create the continuous bond to the substrate. Butt all side laps (do not overlap). Cut the roll at the base of the wall. Remove the release liner, install the Sikaplan barebacked membrane into the adhesive without wrinkles. Press the flashing membrane onto the adhesive using pressure roller.

#### Upstands <30cm / Roof lights

Use the 33 cm wide roll. Apply the SikaRoof® Adhesive Tape PVC to the substrate by holding the roll and wrap the SikaRoof® Adhesive Tape PVC around all sides. Cut the roll to butt the adhesive with the beginning edge (do not overlap). Press and smooth the SikaRoof® Adhesive Tape PVC into place by hand and create the continuous bond to the substrate. Remove the release liner, install the Sikaplan barebacked membrane into the SikaRoof® Adhesive Tape PVC without wrinkles. Press the flashing membrane onto the adhesive using pressure roller.

#### Main Roof Application

Use the 100 cm wide roll and apply the SikaRoof® Adhesive Tape PVC on the existing substrate. Remove the release liner, install the Sikaplan SGK membrane into the adhesive without wrinkles. Press the membrane onto the SikaRoof® Adhesive Tape PVC using pressure roller.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @Sikalreland



Product Data Sheet  
SikaRoof® Adhesive Tape PVC  
March 2026, Version 01.01  
020945051200000025

SikaRoofAdhesiveTapePVC-en-IE-(03-2026)-1-1.pdf

