

PRODUCT DATA SHEET

SikaWall® All Purpose Ready Mixed Filler

Ready mixed filler for multiple uses.

PRODUCT DESCRIPTION

SikaWall® All Purpose Ready Mixed Filler is a ready-to-use, easy-to-apply filler suitable for both interior and exterior applications. It dries to a smooth, durable, crack-resistant and sandable finish, and can be painted, papered or stained once cured. SikaWall® All Purpose Ready Mixed Filler is designed for general repairs on plaster, plasterboard, brick, render, wood, stone and most common building substrates.

USES

Fills gaps and holes in plaster, brick, stone, wood and render.

CHARACTERISTICS / ADVANTAGES

- Ready mixed formula allows for quick and easy application - apply straight from the tub.
- Heavy-duty, tough filler for interior or exterior use.
- Dries white.
- Overpaintable with most solvent-based and emulsion paints.
- Overstainable.
- Quick drying.

PRODUCT INFORMATION

Packaging	600 g and 1 kg tubs
Appearance / Colour	White paste
Shelf Life	24 months from date of manufacture when stored according to manufacturers instructions.
Storage Conditions	Store between +5 °C and +25 °C. Protect from frost.
Density	approx. 1.8 g/cm ³ at +20 °C
pH-Value	8.5 - 9.9
Movement Capability	Low - dries hard
Layer Thickness	9 mm in one coat - further layers can be built up. Maximum width 25 mm.
Ambient Air Temperature	+5 °C to +30 °C

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Do not use to fill plastic or metal.
- Do not apply externally when rain is imminent (within five hours of application).
- Do not apply in temperatures (ambient and surface)

below +5 °C.

- Not suitable for repairs to permanently wet areas.
- Do not apply in layers more than 9 mm deep. If deeper holes need filling, build up in layers, allowing each layer to dry (approx. 1 hour) before applying further layers. Alternatively, use One Strike® Lightweight Filler or SikaWall® Deep Gap Filler which can be applied in 75 mm or 50 mm maximum depths respectively.
- As the manufacturer cannot know all the uses their products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services for advice.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry, free from dust, grease and other contamination. Provide a key to gloss painted surfaces. Cover nail and screw heads with oil-based paint and allow to dry.

APPLICATION

Stir well and apply directly from the tub with a spreader or filler knife. Press the filler into the repair to a maximum depth of 9 mm. For deeper cavities, apply in layers and allow each to dry for one hour. Fill hole proud to allow for sanding and finish with a wet knife. Once dry, sand to a smooth finish. When used outdoors, seal repair with an oil-based paint when dry.

CLEANING OF TOOLS

Clean tools immediately after use with warm, clean water.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet

SikaWall® All Purpose Ready Mixed Filler
July 2026, Version 01.01
021840303000263307

SikaWallAllPurposeReadyMixedFiller-en-IE-(07-2026)-1-1.pdf

