

PRODUCT DATA SHEET

SikaBond® Contractors PVA

General purpose primer, sealer, adhesive and admixture.

PRODUCT DESCRIPTION

SikaBond® Contractors PVA is a multi-purpose, water-based adhesive, primer, sealer, and mortar admixture. It adheres to most common building materials, excluding PVC and rubber, and is ideal for priming unsound surfaces before plastering or painting, enhancing cement mixtures and dust sealing on flaking paintwork and walls. SikaBond® Contractors PVA is an adhesive for use on wood, cork, textiles, plaster, concrete etc.

CHARACTERISTICS / ADVANTAGES

- Numerous applications in the building industry from one product.
- Improves adhesion to most common building surfaces.
- Improves flexibility of mortars and screeds.
- Economical and easy to use.
- Quick drying.

USES

- As a primer and sealer before plastering, painting or in tiling applications.
- As a bonding agent for screeds and renders to difficult substrates.
- As a general purpose adhesive for wood, cork, paper, textiles, concrete, ceramics, and most applications where at least one surface is porous.
- As an admixture for mortar, screeds and renders.
- As an internal filler when mixed with wood shavings, plaster etc.

PRODUCT INFORMATION

Packaging	5 L
Appearance / Colour	White liquid.
Shelf Life	12 months from date of manufacture when stored according to manufacturer's instructions in original, tightly closed containers.
Storage Conditions	Store in cool, dry conditions. Between +5 and +25 °C. Protect from frost. Storage outside these parameters will dramatically reduce shelf life.

Densityapprox. 1.04 g/cm³**Consumption**Neat 1 litre per 6-12 m².Diluted 1:4: 1 litre per 30-60 m².

The above figures will vary according to the degree of porosity and texture of the surface to which SikaBond® Contractors PVA is applied.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

Do not use in exterior applications or in areas subject to constant damp. In these areas use SikaBond® SBR. As the manufacturer cannot know all the uses their products may be put to, it is the user's responsibility to determine suitability of use. If in doubt, please contact Technical Services department for advice.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS**SUBSTRATE QUALITY / PRE-TREATMENT**

All surfaces must be clean, dry and free from grease and loosely adhering material.

APPLICATION METHOD / TOOLS

FOR GENERAL PRIMING – Dilute 4 parts water to 1 part SikaBond® Contractors PVA and apply by brush. Allow to dry.

FOR A BONDING COAT – Use neat and apply by brush, apply plaster or render while still tacky. Note: If a sealer coat is required, allow to fully dry before applying the bonding coat.

AS AN ADHESIVE – Use undiluted. Coat each face and press surfaces together. Large areas should be clamped for 24 hours.

AS A CEMENT ADMIXTURE – Add 10 to 15 litres SikaBond® Contractors PVA to 50 kg cement.

AS A FILLER/PLASTER ADMIXTURE – Dilute 1 to 1 with water and add to mix in place of water.

AS A DUST SEALER (Concrete, Composite and Terrazzo Flooring) – Dilute 1 part SikaBond® Contractors PVA with 5 parts water. Apply 1-2 coats. Leave to dry completely (usually 8 hours) before allowing foot traffic.

CLEANING OF TOOLS

Clean all tools and any excess SikaBond® Contractors PVA with cold, clean water immediately after use.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

**Product Data Sheet**

SikaBond® Contractors PVA
October 2025, Version 03.01
021405061000000045

SikaBondContractorsPVA-en-IE-(10-2025)-3-1.pdf

