

PRODUCT DATA SHEET

Parex[®] Render Bead Adhesive

Render Bead Adhesive

PRODUCT DESCRIPTION

Parex Render Bead Adhesive is based on new technology making it the first hybrid polymer grab adhesive especially created for render beads. This superior adhesive has the ability to bond virtually anything to everything in both wet and dry conditions. With incredible initial grab, high bonding strength, Parex Render Bead Adhesive is the number one choice for render bead application.

USES

Parex Render Bead Adhesive is capable of bonding of almost all materials, porous and non-porous, such as, bricks, blockwork, stone, render boards, plasterboard, concrete, stainless/aluminium beads, stonewool, EPS insulation.

CHARACTERISTICS / ADVANTAGES

- High initial Grab
- Excellent Bond Strength
- Can be applied to wet surfaces
- Designed for use with Parex Mineral Renders

PRODUCT INFORMATION

Packaging	350 ml cartridge
Shelf Life	Use within 12 months.
Storage Conditions	Store in cool, dry conditions between +5 and +25 °C. Storage outside these parameters will dramatically reduce shelf life.
Appearance / Colour	White thick paste

APPLICATION INFORMATION

Consumption	Approx. 12 linear meters for a 6 mm diameter bead.
--------------------	--

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

All surfaces to be bonded must be sound and clean. For a temporary fix prior to render application follow the procedure below. Cut the tip of the cartridge, taking care not to damage the thread. Apply nozzle and cut cleanly at a 45 degree angle with an opening of approximately 6–10 mm diameter. Apply using a standard sealant gun directly to back of one surface only. Immediately place the bead into position and secure with good, even pressure. Fix at maximum 300 mm centres. NOTE: Parex Render Bead Adhesive will skin over within approximately 30 minutes. Through cure will be approximately 1.5 mm in depth per 24 hours. This may be slower on non-porous surfaces.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
Parex® Render Bead Adhesive
October 2023, Version 01.01
021830908000000058

ParexRenderBeadAdhesive-en-IE-(10-2023)-1-1.pdf

