

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaRoof® Adhesive C-733

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Ireland Ltd
Sika House
Ballymun Industrial Estate
Dublin 11
Telephone : +353 1862 0709
E-mail address of person responsible for the SDS : EHS@UK.Sika.com

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166
(available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :  

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

	H336	May cause drowsiness or dizziness.
Supplemental Hazard Statements	: EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	: Prevention:	
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233	Keep container tightly closed.
	P261	Avoid breathing mist or vapours.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
	Response:	
	P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 40
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 40

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

Symptoms : Excessive lachrymation
Erythema
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.

Risks : irritant effects

Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025

Version 1.0

Print Date 12.03.2026

Date of last issue: -

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m ³	2017/164/EU
		Further information: Indicative		
		TWA	200 ppm 734 mg/m ³	2017/164/EU
		OELV - 8 hrs (TWA)	200 ppm 734 mg/m ³	IE OEL
		OELV - 15 min (STEL)	400 ppm 1.468 mg/m ³	IE OEL
butanone	78-93-3	TWA	200 ppm 600 mg/m ³	2000/39/EC
		Further information: Indicative		
		STEL	300 ppm 900 mg/m ³	2000/39/EC
		OELV - 8 hrs (TWA)	200 ppm 600 mg/m ³	IE OEL
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
		OELV - 15 min (STEL)	300 ppm 900 mg/m ³	IE OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : yellow
Odour : solvent-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : 77 - 78 °C

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : Upper explosion limit
13 %(V)

Lower explosion limit / Lower flammability limit : Lower explosion limit
2,1 %(V)

Flash point : ca. 1 °C
Method: closed cup

Auto-ignition temperature : 425 °C

Decomposition temperature : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025

Version 1.0

Print Date 12.03.2026

Date of last issue: -

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : ca. 1.500 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : partly soluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : ca. 105 hPa (20 °C)

Density : ca. 0,90 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

ethyl acetate:

- Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): ca. 1.600 mg/l
Exposure time: 4 h
Test atmosphere: vapour
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

butanone:

- Acute oral toxicity : LD50 Oral (Rat): 3.300 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 36 mg/l
Exposure time: 4 h
Test atmosphere: vapour
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

- ADR : UN 1133
IMDG : UN 1133
IATA : UN 1133

14.2 UN proper shipping name

- ADR : ADHESIVES
IMDG : ADHESIVES
IATA : Adhesives

14.3 Transport hazard class(es)

Class	Subsidiary risks
-------	------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Labels : 3
Tunnel restriction code : (E)
Remarks : Transport according to 2.2.3.1.4 ADR.

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Remarks : Transport according to 2.3.2.2 IMDG.

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids
Remarks : Transport according to 3.3.3.1.1 IATA.

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

IATA (Passenger)
Environmentally hazardous : no

IATA (Cargo)
Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 77% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

Volatile organic compounds (VOC) content: 77% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
IE OEL : Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL) : Occupational exposure limit value (15-minute reference period)
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaRoof® Adhesive C-733



Revision Date: 23.10.2025
Date of last issue: -

Version 1.0

Print Date 12.03.2026

	once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

IE / EN