

## PRODUCT DATA SHEET

# SikaSeal®-629 Fire Wrap+

### Fire resistant pipe wrap

#### PRODUCT DESCRIPTION

SikaSeal®-629 Fire Wrap+ is a fire resistant flexible pipe wrap available as pre-cut strips or on a roll for interior and exterior penetration sealing applications that pass through floor and wall service openings. It is ready to use and can be cut to suit varying pipe diameters. SikaSeal®-629 Fire Wrap+ is designed to provide a high volume expansion and pressure seal during a fire to combustible pipes.

#### USES

- Restores the fire resistance performance of a wall or a floor which incorporates combustible pipes, combustible pipe insulations or conduits.
- Can be combined with Sikacryl®-621 Fire+, SikaSeal®-626 Fire Board+ and Sikacrete®-630 Fire+.

#### PRODUCT INFORMATION

<b>Chemical Base</b>	Graphite based, intumescent wrap
<b>Packaging</b>	Wraps available in two types: as pre-cut strips in plastic pouch and as a 50 mm x 25 m roll (with adhesive). Refer to current price list for packaging variations.
<b>Appearance / Colour</b>	Anthracite
<b>Shelf Life</b>	6 years from the date of production.
<b>Storage Conditions</b>	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.
<b>Dimensions</b>	SikaSeal®-629 Fire Wrap+ is available in the following dimensions.

#### CHARACTERISTICS / ADVANTAGES

- Up to 4 hours fire resistance.
- Highly intumescent – Volume expansion 28 times original size.
- Invisible installation in walls and floors.
- Large pipe range covered.
- Tested for a large variety of relevant wall and floor types.

#### APPROVALS / STANDARDS

- CE Marking and Declaration of Performance to European Technical Assessment ETA 21/1032, based on EAD 350454-00-1104:2017 - Fire stopping and fire sealing products, penetration seals.
- Fire Resistance EN 13501-2, UL\_EU, Certificate No.UL-EU-01216-CPR.

Type: pre-cut strips	Type: roll
55 mm	50 mm x 25 m with adhesive
82 mm	
110 mm	
125 mm	
160 mm	
200 mm	

## TECHNICAL INFORMATION

<b>Resistance to fire</b>	Refer to 'Approvals / Certificates' or contact Sika Technical Services for specific information.
<b>Service Temperature</b>	-20 °C min. / +70 °C max.

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTS

- Sika Application Manual: SikaSeal®-629 Fire Wrap+.
- Brochure Sika Fire Protection Solutions.

## LIMITATIONS

- SikaSeal®-629 Fire Wrap+ may only be used for applications and in combination with products it was tested for.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

REGULATION (EC) NO 1907/2006 - REACH: This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

**SIKA IRELAND LIMITED**  
 Ballymun Industrial Estate  
 Ballymun  
 Dublin 11, Ireland  
 Tel: +353 1 862 0709  
 Web: www.sika.ie  
 Twitter: @Sikalreland



**Product Data Sheet**  
 SikaSeal®-629 Fire Wrap+  
 May 2022, Version 01.01  
 020517100010000005

## APPLICATION INSTRUCTIONS

### APPLICATION METHOD / TOOLS

Reference must be made to the relevant Sika Application Manual or contact Sika Technical Services for additional information.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SikaSeal-629FireWrap+-en-IE-(05-2022)-1-1.pdf

