

PRODUCT DATA SHEET

EVERBUILD® MULTI STICK

SUPERIOR HIGH STRENGTH GRAB ADHESIVE BASED ON HYBRID POLYMER TECHNOLOGY

PRODUCT DESCRIPTION

EVERBUILD® MULTI STICK, based on hybrid polymer technology, is the ultimate building adhesive, the first hybrid polymer grab adhesive especially created for the Trade, uniquely packed in a plastic 350ml cartridge. This superior adhesive has the ability to bond virtually anything to everything in both wet and dry conditions, and even underwater or in the rain. With incredible initial grab, high bonding strength, and almost limitless applications and other benefits, no tradesman should be without a tube of this next generation adhesive.

USES

- As a high quality nail replacement adhesive, even to damp surfaces
- Bonding mirrors to most common substrates
- Jointing cladding panels
- Bonding difficult materials
- Any application requiring high performance, durable bonding
- Applications where resistance to chemical spillage is required

CHARACTERISTICS / ADVANTAGES

- Primerless adhesion to all common building substrates, porous and non-porous
- Internal and External use
- Fast curing
- Virtually odourless
- Low dirt pick up
- Excellent break off and tooling
- Waterproof
- Weather resistant
- UV resistant
- Chemical resistant

PRODUCT INFORMATION

Packaging	350ml cartridge
Colour	White
Shelf Life	Use 12 months from date of manufacture.
Storage Conditions	Store in cool dry conditions away from direct sunlight between +5°C and +25°C. Storage outside these parameters will dramatically reduce the shelf life.
Density	1.63g/cm ³

TECHNICAL INFORMATION

Shore A Hardness	60 - 70
Service Temperature	-50°C to + 80°C

APPLICATION INFORMATION

Yield	Approx. 12 linear metres for a 6mm diameter bead.
Sagging	Nil
Ambient Air Temperature	+5°C to + 35°C
Curing Time	≥1mm per 24 hours
Skin Time	20 – 40 mins

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

- Surfaces must be clean, dry and free from dust, grease, loose material etc.
- Prime dusty surfaces with Everbuild 501 PVA Bond diluted 1:4 with water and allow to dry.
- Apply using a standard sealant gun, cut tip of cartridge, apply nozzle and cut an opening to suite the required bead size.

APPLICATION METHOD / TOOLS

- Cut the tip of the cartridge taking care not to damage the thread. Fix nozzle, cut aperture to required width and apply with a standard sealant gun.
- For bonding heavy items (plasterboard, worktops, wall panels etc) apply adhesive all the way around the edge of the item (30-50mm from edge) and cover back with beads of adhesive at 300mm intervals. Alternatively, apply adhesive direct to battens and press into place. With heavy items, always provide temporary support until the adhesive dries.
- For bonding lightweight items (covings, dado rails, skirting etc) apply adhesive to back of item in one or two continuous beads and press immediately into place.
- Where gap filling is required, mark the areas where there is a large gap and apply a thicker bead to these areas

CLEANING OF TOOLS

Clean up excess adhesive immediately with a cloth/white spirits

LIMITATIONS

- Use on overhead applications – Always use in conjunction with mechanical fixings.
- Use in conjunction with mechanical fixings for glass block fitting or large mirrors (>0.5m² total area).
- For heavy items, provide temporary support until adhesive has dried.
- In areas of high UV some darkening/discolouration may occur. This does not affect the performance.
- Overpaintability: check compatibility with specific paint first before overpainting large areas

- Do not use on polythene safety-backed mirrors, polypropylene or Teflon.
- Do not use on surfaces that bleed oils or plasticizers.
- It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for advice.
- Not for use as part of a glazing system.
- Not for use in aquarium manufacture.
- Not for use in conjunction with bitumen or asphalt.
- Yellowing can occur in the dark.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any

legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
EVERBUILD® MULTI STICK
May 2019, Version 01.01
02051302000000061

EVERBUILDMULTISTICK-en-IE-(05-2019)-1-1.pdf

