

Revision Date: 08.05.2025 Date of last issue: 15.03.2024 Version 4.0

Print Date 08.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikalastic[®]-641

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Polyurethane coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Ireland Ltd Sika House Ballymun Industrial Estate Dublin 11
Telephone	: +353 1862 0709
E-mail address of person responsible for the SDS	: EHS@UK.Sika.com

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)Eye irritation, Category 2H319: Causes serious eye irritation.					
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.				
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.				

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Sikalastic[®]-641

Revision Date: 08.05.2025 Date of last issue: 15.03.2024			Version 4.0	Print Date 08.05.2025
Signal word	:	Warning		
Hazard statements	:	H317 H319 H412	May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lastir	ng effects.
Precautionary statements	:	Prevention P261 P273 P280	Avoid breathing mist or vapours Avoid release to the environmer Wear protective gloves/ eye pro protection.	nt.
		Response:		
		P333 + P31	3 If skin irritation or rash occurs: C advice/ attention.	Get medical
		P337 + P31	3 If eye irritation persists: Get mer attention.	dical advice/
		P362 + P36	4 Take off contaminated clothing a before reuse.	and wash it

Hazardous components which must be listed on the label:

Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)) Hardener MI (Isophoronedi(morpholinoaldimine)) Isophorondiisocyanate homopolymer 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Pentamethyl piperidylsebacate

Additional Labelling

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikalastic[®]-641



Revision Date: 08.05.2025 Date of last issue: 15.03.2024 Version 4.0

Print Date 08.05.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenyl tolyl phosphate MCS	Not Assigned 945-730-9 01-2119511174-52- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 10 - < 20
Hardener MTJ (Polyoxypropylene- tri(morpholinoaldimine))	1379822-00-0 Not Assigned 01-2120039480-63- XXXX	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 5 - < 10
propylene carbonate	108-32-7 203-572-1 01-2119537232-48- XXXX	Eye Irrit. 2; H319	>= 5 - < 10
Hardener MI (Isopho- ronedi(morpholinoaldimine)) Contains: 2,2-Dimethyl-3-(4- morpholinyl)propanal <= 7 %	1217271-02-7 700-584-3 01-2119941782-33- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2,5 - < 5
Isophorondiisocyanate homopol- ymer Contains: 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate <= 0,09 %	53880-05-0 500-125-5 01-2119488734-24- XXXX	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 2,5 - < 5
diphenyl tolyl phosphate	26444-49-5 247-693-8	Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 2,5 - < 5
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 2,5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic[®]-641



evision Date: 08.05.2025 ate of last issue: 15.03.2024			Print Date 08.05.2025	
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % specific concentration limit Skin Sens. 1; H317 >= 0,5 %	>= 0,25 - < 0,5	
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	mate Acute inhalation tox- icity (dust/mist): 0,031 mg/l Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 0,5	
Substances with a workplace expo				
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 5 - < 10	

For explanation of abbreviations see section 16.



Revision Date: 08.05.2025 Date of last issue: 15.03.2024 Version 4.0

Print Date 08.05.2025

SECTION 4: First aid measures

4.1 Description of first aid measures General advice Move out of dangerous area. : Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled Move to fresh air. : Consult a physician after significant exposure. In case of skin contact Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. In case of eye contact Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eve irritation persists, consult a specialist. If swallowed Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : Allergic reactions **Excessive lachrymation** See Section 11 for more detailed information on health effects and symptoms. Risks irritant effects sensitising effects May cause an allergic skin reaction. Causes serious eye irritation. 4.3 Indication of any immediate medical attention and special treatment needed Treatment Treat symptomatically. 5

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

Sikalastic[®]-641



Revision Date: 08.05.2025 Date of last issue: 15.03.2024		Version 4.0	Print Date 08.05.2025	
5.2 Special hazards arising from	the	e substance or mixture		
		No hazardous combustion products are known		
5.3 Advice for firefighters				
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	apparatus.	
Further information	:	Standard procedure for chemical fires.		
SECTION 6: Accidental release measures				
Personal precautions	:	e equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.		
6.2 Environmental precautions				
Environmental precautions	:	Do not flush into surface water or sanitary sewer If the product contaminates rivers and lakes or du respective authorities.		
6.3 Methods and material for containment and cleaning up				
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	silica gel,	

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical
	Follow standard hygiene measures when handling chemical products



Sikalastic[®]-641

Revision Date: 08.05.2025 Date of last issue: 15.03.2024	Version 4.0	Print Date 08.05.2025
Advice on protection against : fire and explosion	Normal measures for preventive fire protection.	
Hygiene measures :	Handle in accordance with good industrial hygier practice. When using do not eat or drink. When u smoke. Wash hands before breaks and at the er	using do not
7.2 Conditions for safe storage, inc	luding any incompatibilities	
Requirements for storage : areas and containers	Keep container tightly closed in a dry and well-ve place. Containers which are opened must be car sealed and kept upright to prevent leakage. Store ance with local regulations.	efully re-
Further information on stor- : age stability	No decomposition if stored and applied as direct	ed.
7.3 Specific end use(s)		
Specific use(s) :	Consult most current local Product Data Sheet p use.	rior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	OELV - 8 hrs (TWA) (Respira- ble dust)	4 mg/m3	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL
n-butyl acetate	123-86-4	OELV - 8 hrs (TWA)	50 ppm 241 mg/m3	IE OEL
		OELV - 15 min (STEL)	150 ppm 723 mg/m3	IE OEL
		STEL	150 ppm 723 mg/m3	2019/1831/EU
	Further inform	Further information: Indicative		
		TWA	50 ppm 241 mg/m3	2019/1831/EU
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	OELV - 8 hrs (TWA)	0,005 ppm (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asth- ma, rhinitis or extrinsic allergic alveolitis			

Sikalastic[®]-641



Revision Date: 08.05.2025Version 4.0Print Date 08.05.2025Date of last issue: 15.03.2024Version 4.0Print Date 08.05.2025

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment				
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water			
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.			
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.			
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.			
Environmental exposure controls				
General advice :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Sikalastic[®]-641



Revision Date: 08.05.2025 Date of last issue: 15.03.2024		Version 4.0	Print Date 08.05.2025
Physical state Colour	:	liquid dark grey	
Odour	:	mild	
Melting point/ range / Freez- ing point	:	No data available	
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	losive limits	
Upper explosion limit / Up- per flammability limit	-		
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	150 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, dynamic	:	ca. 4.000 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Solubility in other solvents	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikalastic[®]-641



Print Date 08.05.2025

Date of last issue: 15.03.2024		1 min Date 00.00.20
Vapour pressure	: 0,04 hPa	
Density	: ca. 1,427 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information		
No data available		
SECTION 10: Stability and	eactivity	
10.1 Reactivity		
No dangerous reaction kno	vn under conditions of normal use.	
10.2 Chemical stability		
The product is chemically s	able.	
10.3 Possibility of hazardous	eactions	
Hazardous reactions	: No hazards to be specially mentior	ned.
10.4 Conditions to avoid		
Conditions to avoid	: No data available	

Version 4.0

10.5 Incompatible materials

Revision Date: 08.05.2025

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

t

Acute toxicity

Not classified due to lack of data.

Components:

Diphenyl tolyl phosphate MCS:

Sikalastic[®]-641



Revision Date: 08.05.2025 Date of last issue: 15.03.2024	Version 4.0	Print Date 08.05.2025
Acute oral toxicity :	LD50 Oral (Rat): > 5.000 mg/kg	
Acute dermal toxicity :	LD50 Dermal (Rat): > 2.000 mg/kg	
Hardener MTJ (Polyoxypropyle	enetri(morpholinoaldimine)):	
Acute oral toxicity :	LD50 Oral (Rat): > 2.001 mg/kg	
Hardener MI (Isophoronedi(mo	rpholinoaldimine)):	
Acute oral toxicity :	LD50 Oral (Rat): > 2.001 mg/kg	
n-butyl acetate:		
Acute oral toxicity :	LD50 Oral (Rat): > 5.000 mg/kg	
Acute inhalation toxicity :	LC50 (Rat): 23,4 mg/l Exposure time: 4 h Test atmosphere: vapour	
Acute dermal toxicity :	LD50 Dermal (Rabbit): > 5.000 mg/kg	
3-isocyanatomethyl-3,5,5-trime	thylcyclohexyl isocyanate:	
Acute oral toxicity :	LD50 Oral (Rat): 4.814 mg/kg	
Acute inhalation toxicity :	LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
	Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity :	LD50 Dermal (Rat): > 7.000 mg/kg	
Pentamethyl piperidylsebacate	::	
Acute oral toxicity :	LD50 Oral (Rat): 3.230 mg/kg	
Skin corrosion/irritation Not classified due to lack of data		
Components:		
Hardener MI (Isophoronedi(mo	rpholinoaldimine)):	
Method : Result :	Regulation (EC) No. 440/2008, Annex, B.46 Skin irritation	
n-butyl acetate:		
Result :	Repeated exposure may cause skin dryness or c	racking.

Sikalastic[®]-641

Jika®

Revision Date: 08.05.2025 Date of last issue: 15.03.2024 Version 4.0

Print Date 08.05.2025

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Hardener MI (Isophoronedi(morpholinoaldimine)):

Method	:	OECD Test Guideline 405
Result	:	Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Hardener MI (Isophoronedi(morpholinoaldimine)):

Method	:	Regulation (EC) No. 440/2008, Annex, B.42 (LLNA)
Result	:	May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

2

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 08.05.2025 Date of last issue: 15.03.2024 Version 4.0

Print Date 08.05.2025

SECTION 12: Ecological information

12.1 Toxicity

Hardener MTJ (Polyoxyprop	-	
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 45,1 mg/l Exposure time: 48 h
		NOEC (Daphnia magna (Water flea)): 12,5 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 1,56 mg/l Exposure time: 72 h
Hardener MI (Isophoronedi(n	noi	rpholinoaldimine)):
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 40,2 mg/l Exposure time: 48 h
		NOEC (Daphnia magna (Water flea)): 17,1 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 89 n Exposure time: 72 h
n-butyl acetate:		
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): 647,7 m Exposure time: 72 h
Pentamethyl piperidylsebaca	ate	:
Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h
M-Factor (Acute aquatic tox- icity)	:	1
M-Factor (Chronic aquatic toxicity)	:	1

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available



Revision Date: 08.05.2025 Version 4.0 Print Date 08.05.2025 Date of last issue: 15.03.2024 12.5 Results of PBT and vPvB assessment Product: : This substance/mixture contains no components considered Assessment to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.. 12.6 Endocrine disrupting properties **Product:** Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. 12.7 Other adverse effects Product: Additional ecological infor-An environmental hazard cannot be excluded in the event of 5 unprofessional handling or disposal. mation Harmful to aquatic life with long lasting effects. **SECTION 13: Disposal considerations**

13.1 Waste treatment methods

Product	he generation of waste should be avoid therever possible. mpty containers or liners may retain so his material and its container must be of ray. hispose of surplus and non-recyclable p raste disposal contractor. hisposal of this product, solutions and a t all times comply with the requirements rotection and waste disposal legislation boal authority requirements. void dispersal of spilled material and ru poil, waterways, drains and sewers.	ome product residues. disposed of in a safe products via a licensed ny by-products should s of environmental a and any regional
European Waste Catalogue	08 01 11* waste paint and varnish conta ents or other dangerous substances	aining organic sol-
Contaminated packaging	5 01 10* packaging containing residues y dangerous substances	s of or contaminated

Sikalastic[®]-641



Revision Date: 08.05.2025 Date of last issue: 15.03.2024 Version 4.0

Print Date 08.05.2025

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental hazards		

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture						
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable				

REACH Information:

- All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Sikalastic[®]-641



Revision Date: 08.05.2025 Date of last issue: 15.03.2024	Version 4	1.0	Print Date 08.05.2025
REACH - Restrictions on the mar the market and use of certain dar mixtures and articles (Annex XVII	ngerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
			Number on list 20: dibutyltin di- laurate
			Number on list 74: 3- isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate
			Number on list 75
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable
Regulation (EU) No 2024/590 on plete the ozone layer	substances that de-	:	Not applicable
Regulation (EU) 2019/1021 on petants (recast)	ersistent organic pollu-	:	Not applicable
Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable
Seveso III: Directive 2012/18/EU jor-accident hazards involving dar		nent	t and of the Council on the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 5% w/w
	livestock rearing emiss and control)	sion	4 November 2010 on industrial and s (integrated pollution prevention ds (VOC) content: 5,18% w/w

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikalastic[®]-641



Revision Date: 08.05.2025	Version 4.0	Print Date 08.05.2025
Date of last issue: 15.03.2024		

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ- mental regulation/legislation	: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or mixture:	Control of Substances Hazardous to Health Regulations (COSHH)
	May be subject to the Control of Major Accident Hazards
	Regulations (COMAH), and amendments.

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 H315 H317 H319 H330 H334 H335 H336 H361f H400 H410 H411 H412		Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
Full text of other abbreviation Acute Tox. Aquatic Acute Aquatic Chronic Eye Irrit. Flam. Liq. Repr. Resp. Sens. Skin Irrit. Skin Sens. STOT SE 2019/1831/EU	ons : : : : : : : : : : : : : : : : : : :	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation Skin irritation Skin sensitisation Specific target organ toxicity - single exposure Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic[®]-641

_



Revision Date: 08.05.2025 Date of last issue: 15.03.2024		Version 4.0	Print Date 08.05.2025
IE OEL	:	Ireland. List of Chemical Agents and Carcinoger pational Exposure Limit Values - Code of Practionand 2	
2019/1831/EU / TWA		Limit Value - eight hours	
2019/1831/EU / STEL		Short term exposure limit	
IE OEL / OELV - 8 hrs (TWA)	÷	Occupational exposure limit value (8-hour refere	ence period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute re od)	
ÀDR	:	European Agreement concerning the Internation Dangerous Goods by Road	nal Carriage of
CAS	:	Chemical Abstracts Service	
DNEL	:	Derived no-effect level	
EC50	:	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
ΙΑΤΑ	:	International Air Transport Association	
IMDG	:	International Maritime Code for Dangerous Goo	
LD50	:	Median lethal dosis (the amount of a material, g once, which causes the death of 50% (one half) test animals)	
LC50	:	Median lethal concentration (concentrations of the air that kills 50% of the test animals during the coperiod)	
MARPOL	:	International Convention for the Prevention of P Ships, 1973 as modified by the Protocol of 1978	
OEL	:	Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
REACH	:	Regulation (EC) No 1907/2006 of the European and of the Council of 18 December 2006 concer istration, Evaluation, Authorisation and Restriction cals (REACH), establishing a European Chemic	rning the Reg- on of Chemi-
SVHC	:	Substances of Very High Concern	U V
vPvB	:	Very persistent and very bioaccumulative	

Further information

Classification of the mixture:		Classification procedure:
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

Sikalastic[®]-641

Revision Date: 08.05.2025 Date of last issue: 15.03.2024 Version 4.0

Print Date 08.05.2025

IE / EN

