

## PRODUCT DATA SHEET

# S-Glass Fleece-120

### Glass fibre separation layer

#### PRODUCT DESCRIPTION

S-Glass Fleece-120 is a glass fibre separation and fire protection layer.

#### USES

- Separation and fire protection layer between Sarnafil® or Sikaplan® membranes and EPS/XPS insulation.

#### CHARACTERISTICS / ADVANTAGES

- Easily applied
- Recyclable (Delete if recycling facilities or recycling offerings are not available in local country)



#### PRODUCT INFORMATION

<b>Chemical Base</b>	Glass fibre	
<b>Packaging</b>	Rolls wrapped individually in transparent PE-foil.	
	Length	100,00 m
	Width	2,00 m
	Weight	24,00 kg
<b>Appearance / Colour</b>	Surface	Structured
	Colour	White
<b>Shelf Life</b>	5 years from date of production.	
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage. Always refer to packaging.	
<b>Length</b>	100,00 m	
<b>Width</b>	2,00 m (+/- 2 %)	

Thickness	1,25 mm (+/- 10 %)	(EN 9073-2)
Mass per unit area	120 g/m <sup>2</sup> (+/- 10 %)	(EN 29073-1)

## TECHNICAL INFORMATION

Tensile Strength	longitudinal	≥ 190 N/50 mm	(EN 29073-3)
	transversal	≥ 100 N/50 mm	

Reaction to Fire	A2	(EN 13501-1)
------------------	----	--------------

## APPLICATION INFORMATION

Ambient Air Temperature	-20 °C min. / +60 °C max.
-------------------------	---------------------------

Substrate Temperature	- 30 °C min. / + 60 °C max.
-----------------------	-----------------------------

## SYSTEM INFORMATION

System Structure	<p>The following products must be considered for use depending on roof design:</p> <ul style="list-style-type: none"> <li>▪ All types of Sarnafil® and Sikaplan® membranes</li> <li>▪ Sarnacol®-2170</li> <li>▪ Sarnacol® T-660</li> </ul>
------------------	--

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- Do not use for permanent exposure to UV radiation.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

REGULATION (EC) NO 1907/2006 - REACH: This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

## APPLICATION INSTRUCTIONS

### APPLICATION

S-Glass Fleece-120 is loose laid accordance with installation instructions: Sarnafil® and Sikaplan®. If necessary S-Glass Fleece-120 can be spot bonded to the substrate with Sarnacol®-2170 or Sarnacol® T-660. Adjoining sheets must overlap at least 50 mm.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @Sikalreland



#### Product Data Sheet

S-Glass Fleece-120  
February 2026, Version 01.01  
020945051050000007

S-GlassFleece-120-en-IE-(02-2026)-1-1.pdf