

PRODUCT DATA SHEET

Sikalastic® Primer FPO

Primer for Sarnafil® FPO roofing membranes

PRODUCT DESCRIPTION

Sikalastic® Primer FPO is an one-component, transparent, slightly yellowing, solvent-based synthetic polymer primer, specifically formulated to bond Sikalastic®-621 TC onto FPO membranes.

USES

Sikalastic® Primer FPO installation works to be carried out only by Sika Approved Contractors. Please observe information given by Product Data Sheets.

Primer for detailing works with Sikalastic®-621 TC on Sarnafil® T membranes

Suitable substrates:

New installations (less than 3 years old) of the following membranes:

- Sarnafil® TG -66
- Sarnafil® TS -77

CHARACTERISTICS / ADVANTAGES

- One-component - easy and ready to use
- Enhance adhesion to Sarnafil® FPO Membranes
- Fast curing-overcoating possible after max 1 hour

PRODUCT INFORMATION

Chemical Base	Synthetic polymer
Packaging	1000 ml aluminium bottle, 4 aluminium bottles per box
Appearance / Colour	Transparent with a slight yellow colour
Shelf Life	9 months from date of production
Storage Conditions	The product must be stored properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Higher storage temperatures may reduce shelf life of product. Reference shall also be made to the storage recommendations within the safety data sheet.
Density	~0.87 kg/l (23 °C) (EN ISO 2811-1)
Viscosity	20–30 mPas (20 °C)

APPLICATION INFORMATION

Consumption	Apply in one coat, at a coverage rate of 70–140 ml/m ²		
Ambient Air Temperature	+10 °C min. / +30 °C max.		
Relative Air Humidity	80 % r.h. max.		
Dew Point	Beware of condensation. The substrate and uncured coating must be ≥3 °C above dew point.		
Substrate Temperature	+10 °C min. / +30 °C max.		
Substrate Moisture Content	Visibly free from moisture and condensation		
Waiting Time / Overcoating	Temperature	Minimum waiting time	Maximum waiting time
	10 °C	60 min	24 hours
	20 °C	30 min	24 hours
Note: Apply an additional coat if more than 24 hours pass before coating Times are approximate and will be affected by changing ambient conditions, particularly temperature and relative humidity.			

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Do not apply in wet weather or to wet surfaces.
- When using Sikalastic® Primer FPO for detailing only – in conjunction with Sikalastic® 621 TC certain environmental limitations apply.
- Do not use in inverted roof situations.
- When applying to details other materials may be encountered – Please consult PDS of Sikalastic®-621 TC.
- Do not use for areas likely to be exposed to prolonged ponding water.
- Surface temperatures likely to regularly exceed 80 °C may reduce life expectancy.
- Use light colors of Sikalastic®-621 TC where possible to reduce surface temperature.
- Roofs must be correctly designed to falls according to local standards, these may be defined as typically 2 % or 1:40.
- Do not apply close to the air intake vent of a running air conditioning unit.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The surfaces must be clean, dry, free of stripping agents and free of oil, grease, silanes, salts, silicone, siloxanes and other chemicals which could cause poor adhesion.

SUBSTRATE PREPARATION

Heavily soiled old membranes to be coated should be thoroughly cleaned by conventional means. Prior to the application of the Sikalastic® Primer FPO clean with Sarnafil® T Clean and allow surface to dry for a minimum of 15 minutes at 23 °C and 50 % relative humidity. Depending on climate, curing can be faster or slower. If in doubt apply a test area first.

APPLICATION

Shake the can of Sikalastic® Primer FPO very thoroughly. Apply a thin but completely covering coat of Sikalastic® Primer FPO with a solvent resistant roller or brush. Sikalastic® Primer FPO should be applied once only. Care must be taken to ensure that this single application gives adequate and uniform coverage. Allow primer to dry sufficiently (see table waiting time / overcoating) before overcoating.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet

Sikalastic® Primer FPO

August 2025, Version 03.02

020915951000000004

SikalasticPrimerFPO-en-IE-(08-2025)-3-2.pdf

