according to Regulation (EC) No. 1907/2006

## SikaSeal®-170

Date of last issue: 29.09.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaSeal®-170

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Ireland Ltd

Sika House

Ballymun Industrial Estate

Dublin 11

Telephone : +353 1862 0709 E-mail address of person : EHS@UK.Sika.com

responsible for the SDS

### 1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

### **Additional Labelling**

EUH208 Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT). May produce an

allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

## SikaSeal®-170

Date of last issue: 29.09.2023



Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT), 64359-81-5. Please use treated articles responsibly.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### Components

| Chemical name                    | CAS-No.             | Classification      | Concentration |
|----------------------------------|---------------------|---------------------|---------------|
|                                  | EC-No.              |                     | (% w/w)       |
|                                  | Registration number |                     |               |
| Hydrocarbons, C13-C23, n-        | Not Assigned        | Asp. Tox. 1; H304   | >= 20 - < 25  |
| alkanes, isoalkanes, cyclics, <  | 932-078-5           |                     |               |
| 0.03% aromatics                  | 01-2119552497-29-   |                     |               |
|                                  | XXXX                |                     |               |
| triacetoxyethylsilane            | 17689-77-9          | Acute Tox. 4; H302  | >= 1 - < 2,5  |
|                                  | 241-677-4           | Skin Corr. 1B; H314 |               |
|                                  | 01-2119881778-15-   | Eye Dam. 1; H318    |               |
|                                  | XXXX                | EUH014              |               |
| Oligomeric ethyl and methyl ace- | Not Assigned        | Skin Corr. 1B; H314 | >= 1 - < 2,5  |
| toxysilanes                      | Not Assigned        | Eye Dam. 1; H318    |               |
|                                  | _                   |                     |               |

according to Regulation (EC) No. 1907/2006

# SikaSeal®-170

Version 4.1 Print Date 28.03.2025

Revision Date: 30.04.2024 Date of last issue: 29.09.2023

| 4,5-dichloro-2-octyl-2H-isothiazol-<br>3-one (DCOIT) | 64359-81-5<br>264-843-8 | Acute Tox. 4; H302<br>Acute Tox. 2; H330<br>Skin Corr. 1; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>EUH071 | >= 0,025 - <<br>0,1 |
|--|-------------------------|---|---------------------|
|  |                         | M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100   |                     |
|  |                         | specific concentration limit Skin Irrit. 2; H315 0,025 - < 5 % Eye Irrit. 2; H319 0,025 - < 3 % Skin Sens. 1A; H317 >= 0,0015 %   |                     |
|  |                         | Acute toxicity esti-<br>mate  |                     |
|  |                         | Acute oral toxicity:<br>567 mg/kg<br>Acute inhalation tox-<br>icity (dust/mist): 0,16<br>mg/l   |                     |

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

according to Regulation (EC) No. 1907/2006

# SikaSeal®-170

Revision Date: 30.04.2024 Version 4.1 Print Date 28.03.2025

Date of last issue: 29.09.2023

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects **Symptoms** 

and symptoms.

No known significant effects or hazards. Risks

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Water mist Sand

Dry powder

Unsuitable extinguishing

media

Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection see section 8.

6.2 Environmental precautions

Environmental precautions No special environmental precautions required.

according to Regulation (EC) No. 1907/2006

# SikaSeal®-170

Date of last issue: 29.09.2023

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Advice on common storage : No special restrictions on storage with other products.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### **Occupational Exposure Limits**

| Components | CAS-No.   | Value type (Form    | Control parame- | Basis * |
|------------|-----------|---------------------|-----------------|---------|
| Components | 0/10/110. | value type (i oiiii | Control parame  | Dasis   |
|            |           | of exposure)        | ters *          |         |

Contains no substances with occupational exposure limit values.

### Occupational exposure limits of decomposition products

| Components  | CAS-No. | Value type (Form of exposure) | Control parameters * | Basis *     |
|-------------|---------|-------------------------------|----------------------|-------------|
| acetic acid | 64-19-7 | TWA                           | 10 ppm               | 2017/164/EU |

according to Regulation (EC) No. 1907/2006

# SikaSeal®-170

Version 4.1 Print Date 28.03.2025

Revision Date: 30.04.2024 Date of last issue: 29.09.2023

|             |                |   | 25 mg/m3             |             |  |
|-------------|----------------|---|----------------------|-------------|--|
|             | Further infor  | Further information: Indicative   |                      |             |  |
|             |                | STEL  | 20 ppm<br>50 mg/m3   | 2017/164/EU |  |
|             |                | OELV - 8 hrs<br>(TWA)   | 10 ppm<br>25 mg/m3   | IE OEL      |  |
|             |                | OELV - 15 min<br>(STEL)   | 20 ppm<br>50 mg/m3   | IE OEL      |  |
| methanol    | 67-56-1        | TWA   | 200 ppm<br>260 mg/m3 | 2006/15/EC  |  |
|             | Further infor  | Further information: Indicative, Identifies the possibility of signifi- |                      |             |  |
|             | cant uptake    | cant uptake through the skin  |                      |             |  |
|             |                | OELV - 8 hrs<br>(TWA)   | 200 ppm<br>260 mg/m3 | IE OEL      |  |
|             | Further infor  | Further information: Substances which have the capacity to pene-        |                      |             |  |
|             | trate intact s | trate intact skin when they come in contact with it, and be ab-         |                      |             |  |
|             | sorbed into t  | sorbed into the body  |                      |             |  |
| acetic acid | 64-19-7        | TWA   | 10 ppm<br>25 mg/m3   | 2017/164/EU |  |
|             | Further infor  | Further information: Indicative   |                      |             |  |
|             |                | STEL  | 20 ppm<br>50 mg/m3   | 2017/164/EU |  |
|             |                | OELV - 8 hrs<br>(TWA)   | 10 ppm<br>25 mg/m3   | IE OEL      |  |
|             |                | OELV - 15 min<br>(STEL)   | 20 ppm<br>50 mg/m3   | IE OEL      |  |

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Recommended: Butyl rubber/nitrile rubber gloves.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

according to Regulation (EC) No. 1907/2006

# SikaSeal®-170

Revision Date: 30.04.2024 Version 4.1

Date of last issue: 29.09.2023



organic vapor filter (Type A)

ABEK-filter

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### **Environmental exposure controls**

General advice : No special environmental precautions required.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state liquid Appearance paste Colour various

Odour vinegar-like

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit / Lower flammability limit

No data available

Flash point 65 °C

Auto-ignition temperature No data available

No data available Decomposition temperature

pΗ Not applicable

substance/mixture is non-soluble (in water)

according to Regulation (EC) No. 1907/2006

## SikaSeal®-170

Revision Date: 30.04.2024 Version 4.1

Date of last issue: 29.09.2023



**Viscosity** 

Viscosity, kinematic  $> 20,5 \text{ mm}2/\text{s} (40 ^{\circ}\text{C})$ 

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 0.01 hPa

Density 0,98 g/cm3 (23 °C)

No data available Relative vapour density

Particle characteristics No data available

#### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid Water

Incompatible with bases.

Alcohol

No data available

#### 10.6 Hazardous decomposition products

according to Regulation (EC) No. 1907/2006

## SikaSeal®-170

Date of last issue: 29.09.2023

acetic acid

Decomposes in contact with water.

Hazardous decomposition

products

: methanol, acetic acid

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified based on available information.

#### **Components:**

## 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Acute oral toxicity : Acute toxicity estimate: 567 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,16 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

### Skin corrosion/irritation

**Product:** 

Species : Rabbit

Result : No skin irritation

### Serious eye damage/eye irritation

**Product:** 

Species : Bovine cornea

Method : OECD Test Guideline 437

Result : No eye irritation

Species : Rabbit

Result : No eye irritation

### Respiratory or skin sensitisation

**Product:** 

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Result : Not a skin sensitizer.

according to Regulation (EC) No. 1907/2006

# SikaSeal®-170

Date of last issue: 29.09.2023

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

**Product:** 

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 mg/l

Exposure time: 96 h

NOEC (Oncorhynchus mykiss (rainbow trout)): > 1 mg/l

Test Type: Early-life Stage

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

#### **Components:**

### 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Toxicity to fish : LC50 (Fish): 0,0027 mg/l

Exposure time: 96 h

M-Factor (Acute aquatic tox- : 100

icity)

Date of last issue: 29.09.2023

according to Regulation (EC) No. 1907/2006

## SikaSeal®-170

M-Factor (Chronic aquatic

toxicity)

100

#### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

: There is no data available for this product.

### **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Date of last issue: 29.09.2023

according to Regulation (EC) No. 1907/2006

# SikaSeal®-170

Avoid dispersal of spilled material a

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 10 waste adhesives and sealants other than those

mentioned in 08 04 09

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

according to Regulation (EC) No. 1907/2006

## SikaSeal®-170

Date of last issue: 29.09.2023

**REACH Information:** 

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 75

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations

according to Regulation (EC) No. 1907/2006

## SikaSeal®-170

Revision Date: 30.04.2024 Version 4.1 Print Date 28.03.2025

Date of last issue: 29.09.2023

specific for the substance or

mixture:

Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

May cause an allergic skin reaction. H317 Causes serious eye damage. H318

Fatal if inhaled. H330

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. Acute toxicity

Short-term (acute) aquatic hazard Aquatic Acute Aquatic Chronic Long-term (chronic) aquatic hazard

Asp. Tox. Aspiration hazard Eve Dam. Serious eye damage Skin Corr. Skin corrosion Skin Sens. Skin sensitisation

2006/15/EC Europe. Indicative occupational exposure limit values 2017/164/EU Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

IE OEL Ireland. List of Chemical Agents and Carcinogens with Occu-

pational Exposure Limit Values - Code of Practice, Schedule 1

and 2

2006/15/EC / TWA Limit Value - eight hours Short term exposure limit 2017/164/EU / STEL 2017/164/EU / TWA Limit Value - eight hours

Occupational exposure limit value (8-hour reference period) IE OEL / OELV - 8 hrs (TWA) :

IE OEL / OELV - 15 min (STEL)

Occupational exposure limit value (15-minute reference peri-

ADR European Agreement concerning the International Carriage of

> Dangerous Goods by Road Chemical Abstracts Service

CAS **DNEL** Derived no-effect level

EC50 Half maximal effective concentration **GHS** Globally Harmonized System

International Air Transport Association IATA

**IMDG** International Maritime Code for Dangerous Goods

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

according to Regulation (EC) No. 1907/2006

## SikaSeal®-170

Print Date 28.03.2025

Revision Date: 30.04.2024 Date of last issue: 29.09.2023

LC50 : Median lethal concentration (concentrations of the chemical in

Version 4.1

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

IE / EN