

PRODUCT DATA SHEET

Sarnatherm[®] G

PIR THERMAL INSULATION BOARD

PRODUCT DESCRIPTION

SarnaTherm G is a rigid insulation board, faced on both sides with a wet lay coated glass fibre tissue, autohesively bonded to the insulation core during the manufacturing process. The core of SarnaTherm G is a high performance CFC / HCFC – free rigid urethane insulant with a typical density of 32 kg/m³.

USES

Thermal insulation underneath waterproofing layer, in the following roofings systems:

- Sarnafil[®] G 410, G 410 Felt and TG 76 FELT adhered single ply membrane systems
- Sarnafil[®] G 410, TG loose laid membrane systems with ballast

CHARACTERISTICS / ADVANTAGES

- Very low thermal conductivity
- CFC/HCFC-free with zero Ozone Depletion Potential (ODP)
- Ideal for new construction and refurbishment
- No separation layer for membranes is required
- Low adhesive consumption
- High compression strength
- Supports excellent adhesion with appropriate Sarnacol range
- Lightweight and low load on the roofing structure
- Available as uniform thickness or tapered

PRODUCT INFORMATION

Packaging	Please refer to the latest price list
Shelf Life	Will not expire in the short term if stored correctly
Storage Conditions	The packaging of SarnaTherm G shall not be considered adequate for long term outside protection. Ideally, boards shall be stored inside a building. If however, outside storage cannot be avoided the boards shall be stacked clear of the ground and covered with a polythene sheet or weatherproof tarpaulin. Boards that have been allowed to get wet must not be used.



Fibre-free
Core

Density	Typically 32kg/m ³
Dimensions	1200mm x 600mm 2400mm x 1200mm 1200mm x 1200mm (tapered only)
Thickness	Please refer to current price list
Compressive Strength	> 150 kPa at 10% deformation BS EN 826:1996
Dimensional Stability	48 h, 70 °C, 90 % R.H. EN 1604 DS(70,90)3 48 h, -20 °C DS(-20,-)1
Reaction to Fire	Class E EN 13501-1
Thermal Conductivity	d < 80mm; 0.026 80mm ≤ d < 119mm; 0.025 d ≥ 120mm; 0.024

SYSTEM INFORMATION

System Structure	Ancillary products and system components according to the current price list. Roof waterproofing single ply membranes: Sarnafil® G 410 types and TG 76 FELT Fasteners and fixings: Sarnafil® fixing range Adhesives: Sarnacol® range Vapour control layers: Sarnavap® range
-------------------------	---

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The substrate surface must be uniform, smooth and free of any sharp protrusions or burrs, etc. It shall be clean, dry and free of grease and dust.

APPLICATION METHOD / TOOLS

Installation procedure:
SarnaTherm G shall be laid over a suitable vapour control layer. SarnaTherm G must be attached to the substrate either with mechanical fixings or with the appropriate Sika adhesive. Project specific fixing details must be ascertained from the latest Sarnafil project specification.

LIMITATIONS

Installation works to be carried out only by Registered Sarnafil® Contractors. Temperature limits will depend on waterproofing membrane installation limits. Use of some ancillary products, e.g. adhesives is limited to temperatures above +5 °C. Please observe information given by Product Data Sheets.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w). Local safety regulations must be observed. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
Sarnatherm® G
June 2019, Version 01.01
020935012000011104

SarnathermG-en-IE-(06-2019)-1-1.pdf

