

PRODUCT DATA SHEET

Sika® ViscoCrete®-10

HIGH RANGE WATER REDUCING/SUPERPLASTICISING CONCRETE ADMIXTURE

PRODUCT DESCRIPTION

Sika® ViscoCrete®-10is a liquid admixture for concrete which is used as a high-range water reducer/super-plasticiser. It meets the requirements of BS EN 934-2 tables 3.1 & 3.2.

USES

- Sika® ViscoCrete®-10 is a unique product that is suitable for the production of ready mixed concrete
- Applications that require high quality concrete
- Concrete with high water reduction to meet low w/c ratio requirements
- High performance concrete
- Self compacting concrete

CHARACTERISTICS / ADVANTAGES

 High-range water reductions resulting in higher strengths and densities

- Improved consistence retention
- Improved cohesion properties
- Improved early and ultimate strengths
- Improved rheology
- Improved durability
- Reduced segregation and bleeding
- Reduced drying shrinkage
- Reduced mix costs

APPROVALS / STANDARDS

Conforms to the requirements of BS EN 934-2 Tables 3.1 & 3.2

DoP 02 13 01 01 100 0 000084 1088, certified by Factory Production Control Body 0086, Certificate 541325, and provided with the CE mark

PRODUCT INFORMATION

Chemical Base	Modified polycarboxylate
Packaging	25 litre drum, 200 litre drum, 1000 litre IBC and Bulk Tanker
Appearance / Colour	Straw liquid
Shelf Life	12 months from date of production if stored properly in undamaged containers, in dry conditions.
Storage Conditions	In dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight and frost.
Density	1.06 kg/l (at +20°C)
pH-Value	4.2 ± 1.0
Total Chloride Ion Content	≤ 0.1 M%
Equivalent Sodium Oxide	< 0.40 %

Product Data Sheet Sika® ViscoCrete®-10 May 2019, Version 01.01 021301011000000084

TECHNICAL INFORMATION

Concreting guidance	The standard rules of good concreting practice, concerning production and
	placing, are to be followed.
	Laboratory trials shall be carried out before concreting on site, especially
	when using a new mix design or producing new concrete components.
	Fresh concrete must be cured properly and curing applied as early as pos-
	sible.

APPLICATION INFORMATION

Recommended Dosage	0.2 -1.5% by weight of cement
Compatibility	Sika®Admixtures: Compatibility information available on request Cements: All cement combination

DISPENSING

Sika® ViscoCrete®-10 should be dispensed through suitable calibrated dosing equipment.

LIMITATIONS

When using Sika® ViscoCrete®-10 a suitable mix design is required and local material sources should be evaluated.

Support from our Technical Department is recommended

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



SIKA IRELAND LIMITED

Ballymun Industrial Estate Ballymun Dublin 11, Ireland Tel: +353 1 862 0709 Web: www.sika.ie Twitter: @Sikalreland



Product Data Sheet Sika® ViscoCrete®-10 May 2019, Version 01.01 021301011000000084 SikaViscoCrete-10-en-IE-(05-2019)-1-1.pdf

