

PRODUCT DATA SHEET

Sikalastic® Rapid Cleaner

Pre-treatment for non-absorbent surfaces and cleaner for tools

PRODUCT DESCRIPTION

Sikalastic® Rapid Cleaner is used to clean/remove residue of Sikalastic® Rapid PMMA resins from tools. It is also used to clean metal and non-absorbent substrates before Sikalastic® Rapid PMMA resins waterproofing and surfacing systems are applied.

Sikalastic® Rapid Cleaner must never be used as a thinner for Sikalastic® Rapid products.

USES

- Used to clean/remove residue of Sikalastic® Rapid PMMA resins from tools
- Used as a pre-treatment to clean metal and non-absorbent substrates

CHARACTERISTICS / ADVANTAGES

- Highly effective
- Rapid evaporation

PRODUCT INFORMATION

| | |
|---------------------------|---|
| Chemical Base | Ethyl-acetate solvent |
| Packaging | 10 L Tin |
| Shelf Life | |
| Storage Conditions | Store the cleaning agent in its original packaging, sealed so it is airtight, and in a cool, dry place and far from sources of heat and ignition. Direct sunlight on the containers should be avoided, including on site. After removing some of the contents, reseal the containers so they are airtight. The product should only be used in the open air or in well ventilated interiors. Seal the container again so it is airtight immediately after using the cleaner. |
| | Reference should also be made to the storage recommendations of the material safety datasheet. |

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, please refer to

the most recent Safety Datasheet.

APPLICATION INSTRUCTIONS

MIXING

For cleaning tools

Tools should be cleaned thoroughly with the cleaner and a brush directly after they have been used for Sikalastic® Rapid PMMA liquid products. Simply im-

mersing the Tools in the Cleaner will not prevent the material from hardening.

For cleaning metal and non-absorbent substrates

Pour Sikalastic® Rapid Cleaner onto a lint-free cloth and rub down the surfaces. The cleaning agent must have dried completely before Sikalastic® Rapid PMMA liquid products are applied.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
Sikalastic® Rapid Cleaner
January 2021, Version 01.01
020915951000000002

SikalasticRapidCleaner-en-IE-(01-2021)-1-1.pdf

