

PRODUCT DATA SHEET

Sarnafil® T scupper round

Prefabricated FPO roof drain

PRODUCT DESCRIPTION


Sarnafil® T Scupper round is a rigid polyolefin prefabricated FPO (PP) injection moulded rainwater outlet for flat roofs used with Sika Sarnafil T/AT membranes which can be heat welded onto the drain.

USES

- Rainwater outlet through the parapet for use with Sarnafil® T/AT membranes.
Please note:
- The product may only be used by experienced professionals
- The product must not be used in regions with average monthly minimum temperatures lower than -50°C. Permanent ambient temperature during use must not be higher than +50°C.

CHARACTERISTICS / ADVANTAGES

- Resistant to UV exposure
- Membrane can be welded directly to the base plate
- Easily applied
- Hot air weldable



PRODUCT INFORMATION

Chemical Base	Polypropylene (PP)	
Packaging	Depending on the order quantity and product size, the products are packaged on pallets or in cartons. Refer to the current price list for available packaging variations.	
Appearance / Colour	Colour	Beige (nearest to RAL 7032)
Shelf Life	5 years from date of production	
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between + 5 °C and + 30 °C. Always refer to packaging. Do not stack pallets of rolls or any other material on top during transport or storage.	

Dimensions

Spigot Ø outside			Based plate	Flow rates
	length	inclination angle	90° angled B × H/L	Depth of wa- ter 55 mm / 75 mm
40 mm	450 mm	0°	250 mm × 150/100 mm	0,50 l/s ¹⁾ / 0,75 l/s ¹⁾
50 mm	450 mm	0°	250 mm × 150/100 mm	0,70 l/s ¹⁾ /1,00 l/s ¹⁾
63 mm	465 mm	5°	320 mm × 200/120 mm	1,05 l/s / 1,40 l/s
75 mm	465 mm	5°	320 mm × 200/120 mm	1,25 l/s / 1,80 l/s
90 mm	465 mm	5°	320 mm × 200/120 mm	1,45 l/s / 2,35 l/s

¹⁾ Calculated value

Thickness 4,0 mm

Surface smooth

APPLICATION INFORMATION

Ambient Air Temperature -20 °C min. / +60 °C max.

Substrate Temperature -30 °C min. / +60 °C max.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Installation work must only be carried out by Sika® Registered Roofing Contractors, experienced in this type of application
- The use of Sarnafil® T Scupper round is limited to geographical locations with average monthly minimum temperatures of -30 °C Permanent ambient temperature during use is limited to +50 °C
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations

ECOLOGY, HEALTH AND SAFETY

Fresh air ventilation must be ensured, when working (welding) in closed rooms.

REGULATION (EC) NO 1907/2006 - REACH

REGULATION (EC) NO 1907/2006 - REACH: This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION

Refer to the relevant section in the Installation instructions: Sarnafil® T/AT.

IMPORTANT

Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

IMPORTANT

Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

IMPORTANT

Ventilation in confined spaces

Always ensure good ventilation when applying the Product in a confined space.

INSTALLATION PROCEDURE

Before applying the roof membrane, fasten the Product securely to the roof deck or parapet.

For mechanically fastened roofs, design the fasteners to resist the wind load forces at the project location. Reference the current installation instructions for Sarnafil® and Sikaplan® flat-roof waterproofing membranes.

Reference further documentation where applicable, such as relevant method statements, application manuals and installation or working instructions.

Application below +5 °C

Note: Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations. Note: Installation of ancillary products such as contact adhesives or cleaners is limited to temperatures above +5 °C. Refer to the corresponding Product Data Sheets.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet

Sarnafil® T Scupper round
August 2026, Version 01.01
020945032050001000

SarnafilTScupperround-en-IE-(08-2026)-1-1.pdf

