

Revision Date: 18.03.2024 Date of last issue: 01.02.2023 Version 1.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaCeram[®]-621 FlowFix

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Grouting mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Ireland Ltd Sika House
		Ballymun Industrial Estate
		Dublin 11
Telephone	:	+353 1862 0709
E-mail address of person	:	EHS@UK.Sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166 (available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	72/2008)
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Danger

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

SikaCeram[®]-621 FlowFix

Print Date 28.03.2025

Revision Date: 18.03.2024	
Date of last issue: 01.02.2023	

Hazard statements :	H315 H318 H335	Causes skin irritation. Causes serious eye damage. May cause respiratory irritation.
Precautionary statements :	Preventior P261 P264	Avoid breathing dust/ fume/ gas/ mist/ va- pours/ spray. Wash skin thoroughly after handling.
	P280 Response	Wear protective gloves/ eye protection/ face protection.
	P304 + P34	40 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
	P305 + P3	51 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove con- tact lenses, if present and easy to do. Con- tinue rinsing. Immediately call a POISON CENTER/ doctor.
	Storage:	
	P403 + P23	33 Store in a well-ventilated place. Keep con- tainer tightly closed.

Version 1.4

Hazardous components which must be listed on the label:

Cement (chromium reduced)

2.3 Other hazards

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006. The product reacts highly alkaline with water.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Compendito			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Cement (chromium reduced)	65997-15-1	Skin Irrit. 2; H315	>= 20 - < 25
	266-043-4	Eye Dam. 1; H318	
		STOT SE 3; H335	
		(Respiratory system)	



Revision Date: 18.03.2024 Date of last issue: 01.02.2023 Version 1.4

calcium diformate	544-17-2 208-863-7 01-2119486476-24- XXXX	Eye Dam. 1; H318	>= 1 - < 2,5
Substances with a workplace exp	osure limit :		
Quartz (SiO2)	14808-60-7 238-878-4		>= 40 - < 60
Limestone Contains: Quartz (SiO2) <5µm >= 0,1 %	1317-65-3 215-279-6		>= 20 - < 25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures General advice Move out of dangerous area. : Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled Move to fresh air. Consult a physician after significant exposure. In case of skin contact Take off contaminated clothing and shoes immediately. 2 Wash off with soap and plenty of water. If symptoms persist, call a physician. In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. If swallowed Do not induce vomiting without medical advice. · Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Symptoms 2 Couah Respiratory disorder **Excessive lachrymation** Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms. Risks irritant effects



Revision Date: 18.03.2024 Date of last issue: 01.02.2023 Version 1.4

Causes skin irritation. Causes serious eye damage. May cause respiratory irritation.

	:	Treat symptomatically.
SECTION 5: Firefighting meas	sure	es
5.1 Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from	the	substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.
SECTION 6: Accidental releas	se n	neasures
	tive	e equipment and emergency procedures
6.1 Personal precautions, protec		
Personal precautions, protect	:	Use personal protective equipment.
	:	Avoid breathing dust.
•	:	
•	:	Avoid breathing dust.
Personal precautions	:	Avoid breathing dust. Deny access to unprotected persons. Try to prevent the material from entering drains or water
Personal precautions 6.2 Environmental precautions		Avoid breathing dust. Deny access to unprotected persons.
Personal precautions 6.2 Environmental precautions	:	Avoid breathing dust. Deny access to unprotected persons. Try to prevent the material from entering drains or water courses. No special environmental precautions required.

For personal protection see section 8.

Revision Date: 18.03.2024 Date of last issue: 01.02.2023 Print Date 28.03.2025

Version 1.4

SECTION 7: Handling and storage

7.1 Precautions for safe handling

,	Advice on safe handling :	Do not breathe vapours/dust. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
	Advice on protection against : ire and explosion	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
I	Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 C	onditions for safe storage, incl	luding any incompatibilities
	Requirements for storage : areas and containers	Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Further information on stor-	: Keep in a dry place.
age stability	No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Quartz (SiO2)	14808-60-7	OELV - 8 hrs (TWA) (Respira- ble dust)	0,1 mg/m3 (Silica)	IE OEL
		nation: Carcinogenic ures and Processes		inogenic Sub-
Limestone	1317-65-3	OELV - 8 hrs (TWA) (Respira- ble dust)	4 mg/m3	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL
Cement (chromium reduced)	65997-15-1	OELV - 8 hrs (TWA) (Respira-	1 mg/m3	IE OEL



Revision Date: 18.03.2024 Date of last issue: 01.02.2023 Version 1.4

ble dust)

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

general dust value

Form of exposure	Value type	Control parameters	Basis
Respirable dust	OELV - 8 hrs (TWA)	4 mg/m3	IE OEL
inhalable dust	OELV - 8 hrs (TWA)	10 mg/m3	IE OEL

8.2 Exposure controls

Personal protective equipment Safety glasses with side-shields conforming to EN166 Eye/face protection 1 Eye wash bottle with pure water Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Recommended: Butyl rubber/nitrile rubber gloves. Contaminated gloves should be removed. Skin and body protection Dust impervious protective suit Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work. Respiratory protection In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. particulate filter P P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Environmental exposure controls General advice Try to prevent the material from entering drains or water courses. No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Version 1.4

SikaCeram[®]-621 FlowFix

Revision Date: 18.03.2024 Date of last issue: 01.02.2023



5 01 1031 13300. 01.02.2020		
Physical state Appearance Colour	:	solid powder various
Odour	:	odourless
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	-	
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	No data available
Density	:	ca. 0,221 g/cm3 (20 °C)

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

SikaCeram[®]-621 FlowFix



		JING
Revision Date: 18.03.2024 Date of last issue: 01.02.2023	Version 1.4	Print Date 28.03.20
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information		
No data available		
SECTION 10: Stability and	reactivity	
10.1 Reactivity		
No dangerous reaction kno	wn under conditions of normal use.	
10.2 Chemical stability		
The product is chemically s	table.	
10.3 Possibility of hazardous	reactions	
Hazardous reactions	: No hazards to be specially mentioned	d.
10.4 Conditions to avoid		
Conditions to avoid	: No data available	
10.5 Incompatible materials		
Materials to avoid	: No data available	
10.6 Hazardous decompositio	n products	
No decomposition if stored	and applied as directed.	
SECTION 11: Toxicological	information	
SECTION II. TOxicological		
11.1 Information on hazard cla	asses as defined in Regulation (EC) No 127	72/2008
Acute toxicity Not classified based on ava	ailable information	
Components:		
calcium diformate:		

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Revision Date: 18.03.2024 Date of last issue: 01.02.2023

Version 1.4



Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

Revision Date: 18.03.2024 Date of last issue: 01.02.2023

Version 1.4



12.7 Other adverse effects

Product:

Additional ecological information

: There is no data available for this product.

SECTION 13: Disposal considerations

:

13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good

Print Date 28.03.2025

Revision Date: 18.03.2024
Date of last issue: 01.02.2023

Version 1.4

IATA (Cargo)	: Not regulated as a da	ngei	rous good
IATA (Passenger)	: Not regulated as a da	nger	ous good
14.5 Environmental hazards			
Not regulated as a dangerous	good		
14.6 Special precautions for use Not applicable	r		
14.7 Maritime transport in bulk a Not applicable for product as s	-	ents	;
SECTION 15: Regulatory info	rmation		
15.1 Safety, health and environm	ental regulations/legisla	tion	specific for the substance or mixture
International Chemical Weapon Schedules of Toxic Chemicals		:	Not applicable
REACH Information:	All substances contai - registered by our up - registered by us, and - excluded from the re - exempted from the r	strea d/or egula	am suppliers, and/or ation, and/or
REACH - Restrictions on the r the market and use of certain mixtures and articles (Annex)	dangerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Cement (chromium reduced) (Number on list 47)
Regulation (EU) No 649/2012 ment and the Council concern of dangerous chemicals		:	Not applicable
REACH - Candidate List of Su Concern for Authorisation (Art		:	None of the components are listed (=> 0.1 %).
REACH - List of substances s (Annex XIV)	ubject to authorisation	:	Not applicable
Regulation (EC) No 1005/2009 plete the ozone layer	9 on substances that de-	:	Not applicable
Regulation (EU) 2019/1021 or tants (recast)	n persistent organic pollu-	:	Not applicable

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

SikaCeram[®]-621 FlowFix



Revision Date: 18.03.2024 Date of last issue: 01.02.2023 Version 1.4

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties

> Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ- mental regulation/legislation specific for the substance or	: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations
mixture:	(COSHH)
	May be subject to the Control of Major Accident Hazards
	Regulations (COMAH), and amendments.

Other regulations:

This product contains cement. Wet cement or mortar may cause alkali burns if in direct and/or prolonged contact with the skin. Wear protective clothing at all times when working with cement based products.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements		
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H335	:	May cause respiratory irritation.
Full text of other abbreviation	ns	
Eye Dam.	:	Serious eye damage
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occu- pational Exposure Limit Values - Code of Practice, Schedule 1 and 2
IE OEL / OELV - 8 hrs (TWA) ADR	:	Occupational exposure limit value (8-hour reference period) European Agreement concerning the International Carriage of Dangerous Goods by Road

Revision Date: 18.03.2024 Date of last issue: 01.02.2023



CAS		Chemical Abstracts Service
	•	
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT		Persistent, bioaccumulative and toxic
PNEC		Predicted no effect concentration
REACH		Regulation (EC) No 1907/2006 of the European Parliament
REAGI	•	and of the Council of 18 December 2006 concerning the Reg-
		a b
		istration, Evaluation, Authorisation and Restriction of Chemi-
0.410		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Version 1.4

Further information

Classification of the	Classification procedure:	
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H335	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

IE / EN