

## PRODUCT DATA SHEET

# Sikafloor® Comfort Regupol-6015 H

Heavy-duty, polyurethane-rubber shock pad

### PRODUCT DESCRIPTION

Sikafloor® Comfort Regupol-6015 H is a prefabricated rubber shock pad. It is fabricated by bonding rubber crumb with a polyurethane compound.

### USES

Sikafloor® Comfort Regupol-6015 H is a rubber shock pad used for shock and sound absorption as part of the Sika ComfortFloor® flooring range.

Please note:

- The Product may only be used by experienced professionals.
- The Product may only be used for interior applications.

### CHARACTERISTICS / ADVANTAGES

- Very good durability
- Good flexibility
- Very good shock resistance
- Effective sound dampening
- Very good impact resistance
- Easy to apply

### PRODUCT INFORMATION

<b>Packaging</b>	Packaging unit	1 roll 24 m <sup>2</sup>
	Roll width	1.5 m
	Roll length	16 m
	Roll weight	66 kg
	Roll diameter	0.2 m
Refer to the current price list for available packaging variations.		
<b>Appearance / Colour</b>	Black	
<b>Shelf Life</b>	5 years from date of production	
<b>Storage Conditions</b>	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Store in a horizontal position. Always refer to the packaging.	
<b>Thickness</b>	4 mm	
<b>Area Density</b>	2.7 kg/m <sup>2</sup>	

## APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	Maximum	+30 °C
	Minimum	+10 °C
<b>Relative Air Humidity</b>	Maximum	80 %
<b>Dew Point</b>	Beware of condensation. The substrate and uncured applied product must be at least +3 °C above the dew point to reduce the risk of condensation or blooming on the surface of the applied product. Low temperatures and high humidity conditions increase the probability of blooming.	
<b>Substrate Temperature</b>	Maximum	+30 °C
	Minimum	+10 °C

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTS

Refer to the following method statements:

- Sika Method Statement — Evaluation and preparation of surfaces for flooring systems
- Sika Method Statement — Sikafloor® mixing and application

## ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH: This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

#### TREATMENT OF JOINTS AND CRACKS

Construction joints and existing static surface cracks in substrate require pre-treating before full layer application. Use Sikadur® or Sikafloor® resins.

#### SUBSTRATE CONDITION

Cementitious substrates must be structurally sound and of sufficient compressive strength (minimum 25 N/mm<sup>2</sup>) with a minimum tensile strength of 1.5 N/mm<sup>2</sup>.

Substrates must be clean, dry and free of contaminants such as dirt, oil, grease, coatings, laitance, surface treatments and loose friable material.

### APPLICATION

1. Roll out the Product into the wet Sikafloor® Comfort Adhesive.
2. When Sikafloor® Comfort Adhesive is tacky, use a 20 kg carpet and linoleum roller to press the Product into the adhesive.

For more detailed information, refer to the Product Data Sheet of Sikafloor® Comfort Adhesive.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @Sikalreland



**Product Data Sheet**  
Sikafloor® Comfort Regupol-6015 H  
May 2026, Version 02.01  
020816140030000016

SikafloorComfortRegupol-6015H-en-IE-(05-2026)-2-1.pdf

