

## SIKA Release

Colour	Product Code	Pack Size	Box Qty
Pale amber	SKRELEASE5	5ltr	4
	SKRELEASE25	25ltr	1

### Product Description

SIKA RELEASE is a ready to use formwork release agent for concrete and mortar.

### Benefits

- Clean removal after concrete setting.
- Brush roller or spray application.
- Provides a water repellent surface once dry.

### Areas For Use

- As a concrete release agent for precast or in situ concrete.
- As a brush roller or spray applied release agent for clean removal of formwork after concreting work has been completed.
- May be used on steel, shuttering plywood, timber or plastic faced formwork.
- Improves surface finish and increase formwork reuse.

### Limitations

- Always read label before use and wear suitable protective equipment
- Keep away from sources of ignition.
- Only apply a thin film. Overdosing can cause dusting.

### Application

Before casting the concrete apply a thin and uniform film of Sika Release to the formwork or mould. a finely atomized spray coating is the best method to achieve this. Any excess should be removed prior to casting the concrete. Once the formwork has been removed, immediately clean and reapply Sika Release. On smooth and non-porous surfaces, Sika Release will cover up to 60m<sup>2</sup> per litre. Conduct a small trial to ascertain an exact figure.

### Specific Data

TEST	RESULT
Appearance	Pale clear/amber liquid.
Specific Gravity @ 20°C	0.81 approx.
Average coverage	30-60m <sup>2</sup> per litre depending on porosity of formwork/shuttering
Flash point	51°C
Specification	Conforms to C & CA Category 5. Approved product under Water By Law Scheme

**Health & Safety**

Consult MSDS for full list of hazards.

**Storage**

Store upright in original, tightly sealed containers and in a dry cool well-ventilated area. Protect from sunlight and frost.

**Shelf Life**

24 months from date of manufacture in unopened containers.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance*

*with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*