

PRODUCT DATA SHEET

Sika® Silicone Spray

Dry silicone lubricant and mould release agent

PRODUCT DESCRIPTION

Sika® Silicone Spray is a dry silicone lubricant and mould release agent for the easing of friction between two surfaces. Ideal for use in mould making/release industries, to ease installation of rubber and EPDM gaskets to window and door frames and has 100's of uses around the home, garage, workshop and industry.

USES

- Multitude of uses in the mould making and mould release industries.
- Making easy the installation of EPDM gaskets to window and doorframes.
- Restoring the black gloss finish to car vinyl trim without the need for polishing.
- As a general high quality spray lubricant.

CHARACTERISTICS / ADVANTAGES

- Enables friction to be reduced between most surface.
- Eliminates noise and squeak.
- Leaves a bright gloss finish to vinyl.
- Non stick and colourless.

PRODUCT INFORMATION

Packaging	400 ml Aerosol
Appearance / Colour	Colourless
Shelf Life	12 months
Storage Conditions	Store in original packaging away from direct sunlight and sources of ignition between +5 and +25 °C.
Consumption	120-250 g/m ²

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ity before use. As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice.

LIMITATIONS

Test small area of surface to be coated for compatibil-

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Shake the can and spray as required directly onto surface(s) to be lubricated. When used as a mould release agent, spray liberally onto mould and allow to dry.

Depending on type of application, Sika® Silicone Spray should be sprayed onto the surface from 15 cm to 20 cm, if required buff with a clean cloth.

LOCAL RESTRICTIONS

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet

Sika® Silicone Spray
October 2026, Version 01.01
020516020000265637

SikaSiliconeSpray-en-IE-(10-2026)-1-1.pdf

