

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaBond®-52 Parquet

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Ireland Ltd
Sika House
Ballymun Industrial Estate
Dublin 11
Telephone : +353 1862 0709
E-mail address of person : EHS@UK.Sika.com
responsible for the SDS

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166
(available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

Additional Labelling

EUH208 Contains Hardener LI (Isophoronedialdimine), 4,4'-methylenediphenyl diisocyanate, m-tolyldiene diisocyanate. May produce an allergic reaction.

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72-XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
Hardener LI (Isophoronedialdimine)	932742-30-8 700-071-4 01-2119880654-28-XXXX	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0,5 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026

Version 5.1

Print Date 12.03.2026

Date of last issue: 24.04.2025

<p>4,4'-methylenediphenyl diisocyanate</p>	<p>101-68-8 202-966-0 615-005-00-9 01-2119457014-47-XXXX</p>	<p>Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373</p> <hr/> <p>specific concentration limit Eye Irrit. 2; H319 >= 5 %</p> <hr/> <p>specific concentration limit STOT SE 3; H335 >= 5 %</p> <hr/> <p>specific concentration limit Skin Irrit. 2; H315 >= 5 %</p> <hr/> <p>specific concentration limit Resp. Sens. 1; H334 >= 0,1 %</p> <hr/> <p>Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l</p>	<p>< 0,1</p>
--	--	---	-----------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026

Version 5.1

Print Date 12.03.2026

Date of last issue: 24.04.2025

m-tolyldiene diisocyanate	26471-62-5 247-722-4 615-006-00-4 01-2119454791-34-XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 <hr/> specific concentration limit Resp. Sens. 1; H334 >= 0,1 % <hr/> Acute toxicity estimate Acute inhalation toxicity (vapour): 0,107 mg/l	>= 0,025 - < 0,1
---------------------------	--	---	------------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : See Section 11 for more detailed information on health effects and symptoms.
- Risks : No known significant effects or hazards.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : For personal protection see section 8.

6.2 Environmental precautions

Environmental precautions : No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
No special handling advice required.
Follow standard hygiene measures when handling chemical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Advice on common storage : No special restrictions on storage with other products.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
4,4'-methylenediphenyl diisocyanate	101-68-8	OELV - 8 hrs (TWA)	0,005 ppm (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
m-tolylidene diisocyanate	26471-62-5	OELV - 8 hrs (TWA) (Inhalable fraction and vapour)	0,001 ppm (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
		OELV - 15 min (STEL) (Inhalable fraction and vapour)	0,003 ppm (NCO)	IE OEL
		TWA	0,01 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		STEL	0,02 mg/m3 (NCO)	98/24/EC I

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment (PPE)

- | | | |
|--------------------------|---|---|
| Eye/face protection | : | Safety glasses |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Recommended: Butyl rubber/nitrile rubber gloves. |
| Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. |
| Respiratory protection | : | In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. |

Environmental exposure controls

- | | | |
|----------------|---|--|
| General advice | : | No special environmental precautions required. |
|----------------|---|--|

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | | |
|-------------------------------|---|-------------------|
| Physical state | : | liquid |
| Form | : | paste |
| Colour | : | various |
| Odour | : | slight |
| Melting point/ range / Freez- | : | No data available |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

ing point

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,31 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402

Hardener LI (Isophoronedialdimine):

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

Acute toxicity estimate: 1,5 mg/l
Test atmosphere: dust/mist
Method: Calculation method

m-tolyldiene diisocyanate:

Acute inhalation toxicity : LC50 (Rat): 0,107 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute toxicity estimate: 0,107 mg/l
Test atmosphere: vapour
Method: Calculation method

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration hazard

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl]-:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l
Exposure time: 72 h |

Hardener LI (Isophoronedialdimine):

- | | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Fish): 87,2 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): > 100 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | EC50 (Desmodesmus subspicatus (green algae)): 180,4 mg/l
Exposure time: 72 h |

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

- | | | |
|------------|---|---|
| Assessment | : | This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.. |
|------------|---|---|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026

Version 5.1

Print Date 12.03.2026

Date of last issue: 24.04.2025

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026

Version 5.1

Print Date 12.03.2026

Date of last issue: 24.04.2025

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 20: dibutyltin dilaurate

Number on list 52: 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich

Number on list 74:
4,4'-methylenediphenyl diisocyanate, m-tolyldene diisocyanate

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026

Version 5.1

Print Date 12.03.2026

Date of last issue: 24.04.2025

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026

Version 5.1

Print Date 12.03.2026

Date of last issue: 24.04.2025

SECTION 16: Other information

Full text of H-Statements

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
98/24/EC I	:	Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
98/24/EC I / STEL	:	Limit values Short-term
98/24/EC I / TWA	:	Limit values 8 hours
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond®-52 Parquet



Revision Date: 05.03.2026
Date of last issue: 24.04.2025

Version 5.1

Print Date 12.03.2026

MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

IE / EN