

PRODUCT DATA SHEET

Sika® One Strike Filler®

Ready-mixed, quick drying, revolutionary lightweight filler.

PRODUCT DESCRIPTION

Sika® One Strike Filler® is a ready-mixed lightweight filler for the preparation of numerous surfaces prior to painting or wallpapering.

Based on high strength lightweight polymeric fillers, the product outperforms conventional fillers in most applications. Designed for professional and D.I.Y use. Sika® One Strike Filler® finished soft and flexible, requiring little or no sanding. Ready to paint or wallpaper in just 30 minutes.

Drying times will vary depending on application depth, porosity of the substrate and the surrounding temperature.

USES

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

CHARACTERISTICS / ADVANTAGES

- Fills up to 75 mm deep in one application - No need to build up layers of filler.
- Easy to use - lightweight paste is incredibly easy to apply.
- No sanding required - finished to a smooth surface.
- No sagging - the lightweight properties of Sika® One Strike Filler® prevent sagging even on ceilings.
- Non-shrink - will not shrink back whilst drying.
- Quick drying - ready to paint or paper in just 30 minutes.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable.
- Internal and external use.
- Dries brilliant white.

PRODUCT INFORMATION

Packaging	250 mL, 450 mL, 1 L, 2.5 L & 5 L Tubs
Appearance / Colour	Lightweight brilliant white paste
Shelf Life	24 months from date of manufacture when stored according to manufacturers instructions.
Storage Conditions	Store between +5 °C to +25 °C
Density	0.28 - 0.35 g/cm ³
Movement Capability	Low

APPLICATION INFORMATION

Ambient Air Temperature	+5 °C to +30 °C
-------------------------	-----------------

Hole dimension

Maximum width 50 mm
Maximum depth 75 mm

Surface temperature

+5 °C to +30 °C

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Do not use to fill plastic or metals.
- Do not apply when rain is imminent (external use).
- Do not apply in temperatures (ambient and surface) below +5 °C.
- Freezing damages the product.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry and free from dust, grease and other contamination.

APPLICATION

Apply direct from tub with spatula/spreader. Smooth over surface and allow to dry. Sanding is not normally required although the product may be sanded if required.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

**Product Data Sheet**

Sika® One Strike Filler®
June 2025, Version 01.01
021840303000000012

SikaOneStrikeFiller-en-IE-(06-2025)-1-1.pdf

